Multimodal Transportation Assessment

PenPlace

Arlington, VA

December 20, 2021
(Revised January 19, 2022)



Prepared by:



1140 Connecticut Ave NW 3914 Centreville Road 15125 Washington Street 225 Reinekers Lane Suite 600 Suite 330 Suite 212 Suite 750 Washington, DC 20036 Chantilly, VA 20171 Haymarket, VA 20169 Alexandria, VA 22314 T 202.296.8625 T 703.787.9595 T 571.248.0992 T 703.721.3044

www.goroveslade.com

This document, together with the concepts and designs presented herein, as an instrument of services, is intended for the specific purpose and client for which it was prepared. Reuse of and improper reliance on this document without written authorization by Gorove/Slade Associates, Inc., shall be without liability to Gorove/Slade Associates, Inc.

CONTENTS

Executive Summary	1
Introduction	4
Purpose of Study	4
Study Tasks	4
Project Summary	4
Contents of Study	5
Study Area Overview	14
Major Transportation Features	14
Future Projects	19
Project Design	26
PenPlace PDSP	26
Adjacent Roadways	26
Site Access and Circulation	33
Loading	33
Parking	34
Bicycle and Pedestrian Facilities	34
Curbside Management	36
Transit	42
Metrorail Service	42
Bus Service	43
Crystal City Potomac Yard Metroway	43
Planned Transit Facilities	43
Bicycle Facilities	54
Existing Bicycle Facilities	54
Planned Bicycle Facilities	55
Pedestrian Facilities	60
Pedestrian Study Area	60
Existing Pedestrian Facilities	60
Planned Pedestrian Facilities	61
Travel Demand Assumptions	70
Mode Split Methodology	70
Trip Generation Methodology	71
Distribution and Assignment Methodology	73
Traffic Operations	83
Study Area, Scope, & Methodology	
Traffic Volume Assumptions	86
Geometry and Operations Assumptions	103
Signal Warrant Analysis	116
Operations Analysis Results	
Transportation Management Plan	162

goroveslade.com

	Participation and Funding	162
	Facilities and Improvements	162
	Carpool and Vanpool Parking	162
	Promotions, Services, Policies	162
	Performance and Monitoring	163
S	ummary and Conclusions	164

LIST OF APPENDICES

Appendix A	. – Signed	Scoping	Document

Appendix B - Site Visit Notes

Appendix C - Access and Loading Memo

Appendix D - Existing Turning Movement Counts

Appendix E – Approved VISSIM Calibration Memo

Appendix F - 2020 Existing VISSIM Delay and Queue Results

Appendix G – Background Development Trips

Appendix H – 2025 Re-Routed Peak Hour Volumes

Appendix I - 2025 Background VISSIM Delay and Queue Results

Appendix J – 2025 Mitigated Future VISSIM Delay and Queue Results

Appendix K - 2031 Re-Routed Peak Hour Volumes

Appendix L - 2031 Background VISSIM Delay and Queue Results

Appendix M - 2031 Mitigated Future VISSIM Delay and Queue Results

January 19, 2022

LIST OF FIGURES

Figure 1: Summary of 2025/2031 Mitigated Future Scenario Findings	3
Figure 2: Major Regional Transportation Facilities	6
Figure 3: Site Location	7
Figure 4: Parcel Map (Source: Arlington County Real Estate Map, September 2016)	8
Figure 5: Planned Land Uses (Source: Arlington General Land Use Plan (GLUP), February 2020)	9
Figure 6: Zoning Map (Source: Arlington County)	10
Figure 7: Site Plan – Ground Floor Plan	11
Figure 8: Site Plan – B2 Level Plan	12
Figure 9: Study Intersections	13
Figure 10: Major Local Transportation Facilities	16
Figure 11: Summary of Walk Score and Bike Score	18
Figure 12: Street Typology (Source: Arlington County Master Transportation Plan, 2019)	24
Figure 13: Existing and Planned Bicycle Facilities (Source: Arlington County Master Transportation Plan, 2019)	25
Figure 14: Typical Cross-Section of Army Navy Drive	28
Figure 15: Typical Cross-Section of S Eads Street	29
Figure 16: Typical Cross-Section of S Fern Street	30
Figure 17: Typical Cross-Section of 12 th Street S	31
Figure 18: Cycle Track and Protected Bicycle Lanes	32
Figure 19: Site Access	38
Figure 20: Circulation Plan	39
Figure 21: Existing Curbside Management	40
Figure 22: Proposed Curbside Management	41
Figure 23: Existing Transit Facilities	45
Figure 24: Annual Metro Ridership at Pentagon City and Crystal City Metro Stations (Source: 22202 Transportation Study)	46
Figure 25: Peak Hour Boardings and Alightings by Stop	51
Figure 26: Approximate Transit Travel Times	52
Figure 27: Planned Transit Improvements	53
Figure 28: Existing Bicycle Facilities	57
Figure 29: Approximate Bicycle Travel Times	58
Figure 30: Future Bicycle Facilities	59
Figure 31: 2020 Existing Peak Hour Pedestrian Volumes	63
Figure 32: Pedestrian Pathways	64
Figure 33: Approximate Pedestrian Travel Times	65
Figure 34: Existing Pedestrian Facilities	66
Figure 35: 2025/2031 Site-Generated Peak Hour Peak Hour Pedestrian Volumes	67
Figure 36: 2025/2031 Mitigated Future Peak Hour Pedestrian Volumes	68
Figure 37: Planned and Proposed Pedestrian Improvements	69

Figure 38: Origin-Destination Zones Used in StreetLight InSight Analysis	74
Figure 39: Home Locations of Commuters to Pentagon City	75
Figure 40: Work Locations of Commuters from Pentagon City	76
Figure 41: Inbound Distribution StreetLight InSight Results	77
Figure 42: Outbound Distribution Streetlight InSight Results	78
Figure 43: Inbound Trip Distribution	79
Figure 44: Outbound Trip Distribution	80
Figure 45: Transportation Analysis District (TAD) in Study Area	81
Figure 46: Origins of Driving Commuters with Destinations in project TAD	82
Figure 47: 2020 Existing Peak Hour Traffic Volumes (Balanced)	93
Figure 48: Future Background Developments	94
Figure 49: 2025 Background Development Peak Hour Traffic Volumes	95
Figure 50: 2025 Background Peak Hour Traffic Volumes (without the proposed development)	96
Figure 51: 2025 Site-Generated Peak Hour Traffic Volumes	97
Figure 52: 2025 Mitigated Future Peak Hour Traffic Volumes (with the proposed development)	98
Figure 53: 2031 Background Development Peak Hour Traffic Volumes	99
Figure 54: 2031 Background Peak Hour Traffic Volumes (without the proposed development)	100
Figure 55: 2031 Site-Generated Peak Hour Traffic Volumes	101
Figure 56: 2031 Mitigated Future Peak Hour Traffic Volumes (with the proposed development)	102
Figure 57: 2020 Existing Lane Configurations and Traffic Controls	108
Figure 58: 2025 Background Lane Configuration and Traffic Controls (without the proposed development)	109
Figure 59: 2025 Mitigated Future Lane Configuration and Traffic Controls (with the proposed development)	110
Figure 60: Lane Configuration and Traffic Controls Comparison by Scenario (2025)	111
Figure 61: Site Plan and Proposed Turning Lane Storage Lengths	112
Figure 62: 2031 Background Lane Configuration and Traffic Controls (without the proposed development)	113
Figure 63: 2031 Mitigated Future Lane Configuration and Traffic Controls (with the proposed development)	114
Figure 64: Lane Configuration and Traffic Controls Comparison by Scenario (2031)	115
Figure 65: Expected Site Generated Bicycle Volumes	118
Figure 66: Expected Site Generated Pedestrian Volumes	119
Figure 67: Warrant 3, Peak Hour Vehicle Volume – Army Navy Drive and Parking Lot/Site Driveway	120
Figure 68: Warrant 4, Pedestrian Peak Hour – Army Navy Drive and Parking Lot/Site Driveway	120
Figure 69: Warrant 3, Peak Hour Vehicle Volume – S Eads Street and 11th Street S/Site Driveway	121
Figure 70: Warrant 4, Pedestrian Peak Hour – S Eads Street and 11 th Street S/Site Driveway	121
Figure 71: Warrant 3, Peak Hour Vehicle Volume – S Fern Street and Site Driveway	122
Figure 72: Warrant 4, Pedestrian Peak Hour – S Fern Street and Site Driveway	122
Figure 73: AM Peak Hour Level of Service Comparison by Scenario (2025)	128
Figure 74: PM Peak Hour Level of Service Comparison by Scenario (2025)	129
Figure 75: AM Peak Hour Level of Service Comparison by Scenario (2031)	147
Figure 76: PM Peak Hour Level of Service Comparison by Scenario (2031)	148

LIST OF TABLES

Table 1: Summary of Recommended Mitigation Measures	1
Table 2: Carshare Locations	18
Table 3: Vehicle Parking Summary	37
Table 4: Bicycle Parking Summary	37
Table 5: Bus Stop Inventory	47
Table 6: Bus Route Information	48
Table 7: Bus Stop Boarding and Alighting Weekday Information – Peak Hours	49
Table 8: Sidewalk Recommendations per Arlington County Master Transportation Plan	61
Table 9: Summary of Office Mode Split Data	70
Table 10: Summary of Neighborhood Retail Mode Split Data	70
Table 11: Summary of Mode Split Assumptions by Land Use	71
Table 12: Multi-Modal Trip Generation (2025 and 2031 Horizon Years)	72
Table 13: Existing Roadway Network	85
Table 14: Traffic Generated by 2025 Background Developments	88
Table 15: Traffic Generated by 2031 Background Developments	91
Table 16: Signal Warrant Analysis Summary	117
Table 17: VISSIM Modeling Calibration Criteria and Results	124
Table 18: Number Vehicles Entered into Network (2025)	127
Table 19: AM Peak Hour Simulated Travel Time Results (2025)	127
Table 20: PM Peak Hour Simulated Travel Time Results (2025)	127
Table 21: AM Vehicular Delay and Maximum Queue Length (2025)	130
Table 22: PM Vehicular Delay and Maximum Queue Length (2025)	135
Table 23: Bicycle and Pedestrian Delay (2025)	140
Table 24: Number Vehicles Entered into Network (2031)	146
Table 25: AM Peak Hour Simulated Travel Time Results (2031)	146
Table 26: PM Peak Hour Simulated Travel Time Results (2031)	146
Table 27: AM Vehicular Delay and Maximum Queue Length (2031)	149
Table 28: PM Vehicular Delay and Maximum Queue Length (2031)	154
Table 29: Bicycle and Pedestrian Delay (2031)	159

Executive Summary

The following report is a Multimodal Transportation Assessment (MMTA) for the PenPlace development in National Landing, and more specifically within the Pentagon City area of Arlington, Virginia.

Site Location and Study Area

The proposed development site is located in the Pentagon City neighborhood of Arlington, Virginia and is bounded by Army Navy Drive to the north, S Eads Street to the east, 12th Street S to the south, and S Fern Street to the west, as shown in Figure 3. The general extents of the study area are S Hayes Street to the west, Route 1 to the east, I-395 to the north, and 15th Street S to the south.

The vehicular study area consists of 22 intersections along S Hayes Street, S Fern Street, S Eads Street, Army Navy Drive, 12th Street S, 13th Street S, 14th Street S, 15th Street S, and I-395, as vetted and approved by Arlington County and VDOT during the scoping process.

The proposed development site currently consists of an undeveloped parcel and a former hotel on the northwest corner of the site. The site is zoned as C-O-2.5: Mixed Use District and is shown as a mix of high-medium residential and medium office-apartment-hotel land use in the General Land Use Plan (GLUP).

Proposed Project

The proposed development is the second phase of Amazon's new headquarters in Pentagon City. The Metropolitan Park 6, 7, and 8 project, approved in 2019, is the first phase of Amazon's new headquarters and consisted of two buildings with approximately 2.1 million square feet of office space and 55,000 square feet of neighborhood-serving ground floor retail space. It is envisioned that there will be transportation synergies between the PenPlace and Metropolitan Park projects, including but not limited to eastbound and westbound median transit stops near 12th Street S and S Elm Street, significant new bicycle amenities and infrastructure in and surrounding the two projects, and amenities that facilitate pedestrian movement and connectivity between the two projects.

The proposed development will consist of four (4) buildings with approximately 2.8 million square feet of office space, 388,000 square feet of amenity space, 14,500 square feet of daycare, 82,600 square feet of neighborhood-serving ground floor retail space, and 27,000 square feet of community space.

The southeastern building (Tower 1) will include a total of approximately 937,675 square feet of office space, approximately 28,964 square feet of retail, and 274 secure long-term bicycle spaces.

The southwestern building (Tower 2) will include a total of approximately 911,163 square feet of office space, approximately 24,336 square feet of retail, and 244 secure long-term bicycle spaces.

The northwestern building (Tower 3) will include a total of approximately 928,240 square feet of office space, approximately 14,527 square feet of daycare space, 27,000 square feet of community space, and 312 secure long-term bicycle spaces.

The northeastern building (Helix Building) will include a total of approximately 388,272 square feet of amenity space and approximately 8,546 square feet of retail. Secure long-term bicycle spaces will be provided in the southeastern building (Tower 1), the southwestern building (Tower 2), and the northwestern building (Tower 3).

Three (3) retail pavilions will include a total of approximately 20,763 square feet of retail.

The proposed development will provide 1,984 parking spaces in a below-grade parking garage shared between the four (4) buildings. Vehicular access to the shared below-grade parking garage will be provided via Army Navy Drive, S Fern Street, and S Eads Street. Loading access to the below-grade shared loading area will be provided via Army Navy Drive. The number of parking spaces on-site will accommodate the practical needs of the site.

The proposed development will provide seven (7) large loading berths and six (6) van parking stalls, for a total of 13 loading spaces, in the loading area shared by the four (4) buildings on the B2 level of the parking garage. The number of loading facilities on-site will accommodate the practical needs of the site. While the loading dock and ramp have been designed to accommodate a WB-67, trucks of this size will be very infrequent. The arrival of a WB-67 would be scheduled and permitted during off-peak only.

A number of significant infrastructure improvements are being proposed as part of this development:

- Improving pedestrian facilities along the perimeter of the site to meet or exceed Arlington County and ADA standards;
- 2. The signalization of two (2) existing intersections and the addition of one (1) new signalized intersection within the vicinity of the proposed development, providing access to the on-site loading facilities and below-grade garage, allowing streets to function as a complete network rather than a series of major corridors for commuter traffic, and providing signalized pedestrian crossings where none currently exist;
- The reconfiguration of S Eads Street adjacent to the site, to include southbound protected bicycle lanes and onstreet parking; and
- 4. The reconfiguration of S Fern Street adjacent to the site, to include northbound protected bicycle lanes between Army Navy Drive and 12th Street S and southbound protected bicycle lanes between Army Navy Drive and 11th Street S/Site Driveway, new striped medians, and onstreet parking.
- 5. The reconfiguration of the Army Navy Drive and S Eads Street intersection to add a northbound thru lane.
- 6. The reconfiguration of the 12th Street S and S Eads Street intersection to add a dedicated southbound left-turn lane.
- 7. The reconfiguration of the 12th Street S and S Fern Street intersection to add a dedicated southbound left-turn lane.

Policies and Goals

The Arlington County Master Transportation Plan (MTP) adopted in 2011 and updated in 2019, outlines goals to improve various modes of transportation throughout the County. Similarly, the Crystal City Sector Plan, adopted by the County Board in 2010, developed a series of goals and objectives specifically for Crystal City. Although the PenPlace development is located in Pentagon City, just outside of the Sector Plan's extents, this development achieves several of the goals and policies of both the MTP, Sector Plan, and other guiding documents for the County.

The Pentagon City Plan, which was released as a draft in November 2021, and accompanying transportation analysis, which was released in October 2021, identifies potential improvements to the multi-modal transportation system to better accommodate additional trips generated by future redevelopment. The analysis that is being conducted as part of this MMTA is being coordinated with the County so as to complement the transportation analysis being conducted as part of the Pentagon City PDSP.

There are a number of other transportation related initiatives such as the Army Navy Drive Complete Street Project and the S

Eads Street Complete Street Project that are discussed in more detail later in this report.

Multi-Modal Overview

Transit

The subject site is well-served by transit:

- The site is located 0.2 miles from the Pentagon City Metro Station, 0.5 miles from the Pentagon Metro Station, and 0.6 miles from the Crystal City Metro Station, which are served by the Blue and Yellow lines.
- The Pentagon City Metro is served by 10 bus routes provided by Metrobus, Metroway, ART, and other regional bus routes. The Pentagon Metro Station is served by 21 bus routes provided by Metrobus, ART, and other regional bus routes. The Crystal City Metro is served by eight (8) bus routes provided by Metrobus, Metroway, ART, and other regional bus routes.
- There are 16 bus stops within a quarter-mile of the site.
 These stops are directly served by WMATA (Metrobus),
 Metroway, Arlington Transit (ART), OmniRide, Fairfax
 Connector, and Loudoun County Commuter routes.
- Metroway is a premium bus service that connects the Pentagon City, Crystal City, and Potomac Yards neighborhood (National Landing), as well as the Braddock Road neighborhood in Alexandria, VA. Metroway buses travel in mixed traffic adjacent to the site along 12th Street and in other segments; however, there are also sections of the route in Crystal City and Potomac Yards where Metroway buses operate in dedicated bus-only lanes. The nearest stop to the site is at the corner of 12th Street S and S Hayes Street adjacent to the Pentagon City Metro entrance at the end of the Metroway line. All buses from that stop proceed south to Crystal City and the Braddock Road Metro Station.
- The Crystal City VRE station is located approximately 0.5 miles southeast of the proposed development site on the east side of Crystal Drive.

Bus stops adjacent to the site are well used, with the Columbia Pike-Pentagon City line seeing the highest boardings and alightings at bus stops near the site.

Improvements to transit facilities will be made as part of the 12th Street S Complete Street project and Pentagon City Transitway Extension project. As part of the 12th Street Complete Street project, improvements will include dedicated center-running transit-only lanes extending along 12th Street S from S Army-Navy Drive to S Hayes Street. Two (2) median bus stops will be added near the intersection of 12th Street S and S Elm Street.

adjacent to the site. As part of the Crystal Drive segment of the Transitway Extension to Pentagon City project, improvements will initially include curbside rush hour bus-only lanes from 15th Street S to 12th Street S and Long Bridge Drive and five (5) new transitway stations, with two (2) additional stations included in later phases.

As part of the proposed development, one (1) existing bus stop adjacent to the site on S Eads Street and Army Navy Drive will be relocated to the far side of the S Eads Street and 11th Street S/Site Driveway intersection.

Bicycle

The site has access to several on- and off-street bicycle facilities, including bicycle lanes on S Eads Street, S Hayes Street, and 15th Street S, which connect to the Mt. Vernon Trail to the east and Four Mile Run Trail to the south. These in turn provide regional access to destinations within Virginia and the District. Several of the existing bicycle facilities have been identified by the Arlington County Master Transportation Plan and Crystal City Sector Plan to be upgraded in the future.

The recently adopted Bicycle Element of the Arlington County
Master Transportation Plan identifies Army Navy Drive, between
12th Street S and S Joyce Street, and 15th Street S as Primary
Bicycling Corridors. The plan makes the following
recommendations for roadways in the vicinity of the site:

- Bi-directional, protected bicycle lanes along Army Navy Drive from S Joyce Street to 12th Street S.
- Construct an off-street cycle track connecting the planned Army Navy Drive protected bicycle lane at 12th Street S to 18th Street S and the Crystal City Metrorail station.
- Upgrade the existing bicycle lanes on S. Joyce Street and 15th Street South between Army Navy Drive and S. Hayes Street to include more separation from motor vehicle traffic.
- Develop an enhanced bicycle facility on S. Fern Street between the Pentagon reservation and 18th Street South. The proposed development will provide a northbound protected bike lane along the eastern side between Army Navy Drive and 12th Street S and a southbound protected bike lane along the western side between Army Navy Drive and 11th Street S/Site Driveway.

While the PenPlace development is located in Pentagon City, just outside of the Crystal City Sector Plan's extents, the plan makes the following recommendations for roadways in the vicinity of the site:

- Extending on-street routes along S Fern Street;
- Adding on-street routes along 12th Street S from S Hayes Street to S Clark Street; and
- Adding bicycle lanes along Army Navy Drive between S Hayes Street and 12th Street S.

A number of planned or approved projects will improve bicycle infrastructure and connectivity in the vicinity of the proposed development:

- As part of the Army Navy Drive Complete Street project, separated two-way bicycle lanes (cycle track) will be installed along the south side of Army Navy Drive between S Joyce Street and 12th Street S.
- As part of the S Eads Street Complete Street project, buffered bicycle lanes will also be installed the east side of S Eads Street from Army Navy Drive to 12th Street S.
- As part of the S Eads Street Protected Bicycle Lanes
 Extension and Metropolitan Park 6, 7, 8 project, protected bicycle lanes will be installed along both sides of S Eads
 Street from 12th Street S to 15th Street S and the S Eads
 Street and 15th Street S intersection will be reconfigured as a protected intersection.
- As part of the 12th Street South Complete Street project, shared lanes are planned from S Eads Street to Clark Street/Long Bridge Drive, connecting to the existing bicycle lanes on Crystal Drive east of the site.
- As part of the 12th Street S/S Clark-Bell Street Realignment project, an off-street trail will be installed along the west side of S Clark Street.
- As part of the Metropolitan Park 6, 7, 8 project, separated bicycle lanes will be installed along the west side of S Eads Street from 12th Street S to 15th Street S, protected bicycle lanes will be provided along both sides of 15th Street S between S Elm Street and Route 1, and a protected intersection will be provided at S Eads Street and 15th Street S. Protected intersections improve sightlines and provide more separation between bicycles and vehicles.

Plans for the proposed development include protected southbound bicycle lanes along the western side of S Eads Street between Army Navy Drive and 12th Street S, protected northbound bike lanes along the eastern side of S Fern Street between Army Navy Drive and 12th Street S, and protected southbound bike lanes along the western side of the S Fern Street between Army Navy Drive and 11th Street S/Site Driveway.

While 502 long-term bicycle parking spaces are required, the proposed development will significantly exceed zoning

requirements for bicycle parking by providing a total of 830 longterm bicycle parking spaces for office, and retail use on the ground floor of each building. The proposed development will provide:

- 274 spaces in the southeastern building (Tower 1);
- 244 spaces in the southwestern building (Tower 2); and
- 312 spaces in the northwestern building (Tower 3).

Secure long-term bicycle spaces for the northeastern building (Helix) will be provided in the southeastern building (Tower 1), the southwestern building (Tower 2), and the northwestern building (Tower 3).

Each bicycle room will contain lockers, showers, and bicycle repair stations, making cycling to and from the proposed development convenient and user-friendly. The proposed development will also provide 176 short-term bicycle parking spaces within and along the perimeter of the site on Army Navy Drive, 12th Street South, S Fern Street and S Eads Street.

On-site bicycle facilities including the amount of long- and shortterm bicycle parking, and the amount of bicycle storage and lockers exceeds County requirements and will encourage commuting by bicycles to and from the proposed development.

Pedestrian

The site is surrounded by a well-connected pedestrian network. Pedestrian facilities around the site provide a quality walking environment. There are a number of gaps in infrastructure, such as temporary asphalt sidewalks adjacent to the site on the east side of S Eads Street, the north side of 12th Street S, and the east side of S Fern Street. In addition, there are sidewalks closed due to construction south of the site along 13th Street S, 15th Street S, S Elm Street, and S Eads Street. Some barriers exist east of the site due to Route 1 and north of the site due to I-395, but overall, there is good connectivity and facilities.

A number of planned and approved projects will improve pedestrian infrastructure and connectivity in the vicinity of the proposed development. This includes improvements to sidewalks and streetscape as part of the S Eads Complete Street project, adding crosswalks and shortening existing crosswalks on Army Navy Drive as part of the Army Navy Drive Complete Streets project, and the conversion of Route 1 into an urban at-grade boulevard as part of the Route 1 Multimodal Improvements Study.

As a result of the proposed development, pedestrian facilities along the perimeter of the site will be enhanced by improving sidewalks adjacent to the site so that they meet or exceed Arlington County and ADA standards. The proposed development will improve pedestrian connectivity by providing three (3) signalized intersections, including signalized pedestrian crosswalks.

The proposed development will result in new or improved sidewalks along the perimeter of the site. This will be particularly impactful along segments where sidewalks do not meet County and ADA standards. New pedestrian facilities are expected to meet or exceed County requirements with an emphasis on pedestrian safety and comfort. This includes sidewalks that meet or exceed the width requirements, crosswalks at all necessary locations, curb ramps with detectable warnings, and additional design elements such as curb extensions. In addition, the construction of a series of interconnected plazas consisting of both active and passive open spaces will further improve pedestrian connectivity and porosity, breaking up a superblock. Consistent with the Pentagon City Plan, the proposed development will also provide an east-west multimodal path through the site that improves pedestrian connectivity and site porosity. Pedestrians are seen as the primary users of the PenPlace's internal spaces. The combination of aestheticallypleasing design elements creates a pedestrian environment that is safe, functional, and visually appealing.

Vehicular

The site is well connected via several principal arterials such as Route 1, VA-27 (Washington Boulevard), VA-244 (Columbia Pike), and VA-110. The arterials create connections to I-395, I-66, George Washington Memorial Parkway, and ultimately the Capital Beltway (I-495) and I-95. These principal arterial roadways bring vehicular traffic within half-mile of the site, at which point minor arterials, collectors, and local roads can be used to access the site directly.

Consistent with a number of Arlington County policies and goals, the proposed development will limit on-site parking by providing a total of 1,984 parking spaces. The amount of on-site parking will meet the practical needs of the site while promoting the use of non-auto modes of travel to and from the proposed development.

Existing Simulation Model Calibration

Compared to typical macroscopic analysis tools, such as Synchro, VISSIM is a microsimulation modelling tool that measures the performance of individual vehicles as they travel through the network while accounting for the influence of other vehicles, transit, pedestrians, and cyclists. Given the multimodal nature of Pentagon City and planned improvements, particularly streets directly adjacent to the site where a cycle track, protected bicycle lanes, and dedicated transit lanes will be in place, VISSIM was determined to be the appropriate analysis tool for this development as agreed upon during the scoping process.

The base VISSIM model provided by Arlington County was reviewed and updated based on the study area characteristics, available data, and VDOT TOSAM criteria.

Model calibration is the process of performing adjustments to the model to better simulate local driving behavior and operational performance. The calibration process typically compares field data (volumes, speed, travel time, queue length, etc.) to the simulation output so that the model represents actual traffic conditions in the study area. A model that is appropriately calibrated improves the model's ability to assess the future conditions of the study area. The calibration criteria were scoped and approved by Arlington County. The turning movement volumes at signalized intersections and travel time field measurements, provided by Arlington County, were utilized as metrics to recalibrate the base VISSIM model.

Some model parameters were adjusted to reflect actual network performance and driver behaviors. The models were run with adjusted parameters and the outputs were examined against field measurements.

The VISSIM modeling calibration used in this analysis met the calibration acceptance targets in 100% of cases, which is consistent with VDOT TOSAM guidance.

Travel Demand Assumptions

Mode split (also called mode share) is the percentage of travelers using a particular type (or mode) of transportation when traveling. The main source of mode split information for this report was based on Census data using Transportation Analysis Districts (TADs) and data contained in the 2016 State of the Commute, the Crystal City Multimodal Transportation Study, the WMATA Ridership Survey, and the Arlington County Mode Share Assumptions for Pentagon City. The following mode splits were assumed in the analysis:

- Office
 - Auto 30%, Transit 54%, Bicycle 6%, Walk 10%
- Amenity Use
 - o Auto 30%, Transit 54%, Bicycle 6%, Walk 10%
- Daycare
 - o Auto 50%, Transit 20%, Bicycle 5%, Walk 25%
- Neighborhood Retail
 - Auto 5%, Transit 15%, Bicycle 5%, Walk 75%
- Community
 - Auto 50%, Transit 20%, Bicycle 5%, Walk 25%

Weekday peak hour trip generation is calculated based on the methodology outlined in the Institute of Transportation Engineers' (ITE) <u>Trip Generation</u>, 10th Edition.

Office trip generation is based on the development program of 2.8 million square feet. Office trip generation was calculated based on ITE Land Use 710 (General Office Building), using the setting/location of Center City Core, splitting trips into different modes using assumptions outlined in the mode split section of this report.

Amenity trip generation is based on the development program of 388,000 square feet. The amenity use will include support space for the site, including the Helix building, and is anticipated to generate minimal additional trips during the morning and afternoon peak hours. The amenity space will primarily be used off-peak and by office users already on-site. The Helix building will be opened to the public several days per month for public tours but will be closed to the public on a typical weekday. Amenity office trip generation was based on ITE Land Use 580 (Museum) to be conservative, using the setting/location of General Urban/Suburban, splitting trips into different modes using assumptions outlined in the mode split section of this report.

Daycare trip generation is based on the development program of 14,500 square feet. Daycare trip generation was calculated based on ITE Land Use 565 (Day Care Center), using the setting/location of General Urban/Suburban, splitting trips into different modes using assumptions outlined in the mode split section of this report.

Neighborhood retail trip generation is based on the development program of 82,600 square feet of neighborhood-serving ground floor retail. Retail trip generation was calculated based on ITE's

baseline vehicular trips for Land Use 820 (Shopping Center), using the setting/location of General Urban/Suburban (limited data is available for person trips), splitting trips into different modes using assumptions outlined in the mode split section of this report.

Community space trip generation is based on the development program of 27,000 square feet. Community space trip generation was calculated based on ITE Land Use 495 (Recreational Community Center), using the setting/location of General Urban/Suburban, splitting trips into different modes using assumptions outlined in the mode split section of this report.

At the request of VDOT, Local and Regional trip distribution was based primarily on data collected from StreetLight, by mapping the general home location of commuters to Pentagon City and the general work locations of residents in Pentagon City.

StreetLight metrics are derived from a combination of two types of locational data: navigation-GPS data and Location-Based Services (LBS) data, including historical data, with a sample size of approximately 23% of the adult population. This data is then transformed into contextualized, aggregated, and normalized travel patterns that can be used to create origin and destination analyses. The results of the Home and Work Analysis were then used to define the major roadways used for regional trips, and the distribution of trips with an origin or destination in neighborhoods proximate to PenPlace. This analysis results in an assignment of trips to the roadway network.

Future Improvements

A number of planned transportation improvements in the vicinity of the PenPlace development are expected to be complete by 2025 and 2031. The full list of improvements is detailed in the report, but examples include:

- Army Navy Drive Complete Street
- 12th Street S Complete Street
- 15th Street S/S Clark-Bell Street Realignment
- Crystal City Transitway Extension
- Route 1 Multimodal Improvements Study

Future Traffic Operations

A capacity analysis was developed to compare the future roadway network without the proposed development. Intersection capacity analysis were performed for the morning and afternoon peak hours at study area intersections. VISSIM version 11.00-14 was used to analyze the study area

intersections using an agreed upon set of Measures of Effectiveness (MOEs).

Traffic projections for 2025 and 2031 are based on existing volumes, plus traffic generated by approved nearby background developments, regional growth on the roadway, and traffic generated by the proposed PenPlace development.

This study uses a hybrid approach to estimate traffic growth factors by utilizing the MWCOG model results and approved local background developments. The process begins with collecting turning movement counts for each study intersection, and adding trips generated by approved local background developments to the turning movements at the study intersections. Since that accounts for local background growth, a regional growth rate is also applied to accounts for trips generated outside the study area. The regional growth rate is estimated by deducting the trips generated by approved local background form the MWCOG traffic projections for a given year. This process is conducted to avoid double-counting the trips generated by the approved local background developments. In locations where the MWCOG model growth was higher than the growth based on background developments, the difference was applied to through volumes, as outlined in the report; if the growth rates determined by the MWCOG model were lower than those determined by the background developments, no additional growth rate was applied. This procedure, rather than a growth rate, determined by only the MWCOG model was used to provide more specificity at study intersections. The methodology of using background development trips is consistent with other MMTAs in Arlington County and has been vetted and approved by the County and VDOT.

Mitigations

As described in the Geometry and Operations section of this report, the proposed development will include several improvements to adjacent roadways, including the signalization of three (3) intersections and the addition of protected bike facilities.

Based on the results of the VISSIM analysis, potential mitigation measures were explored at study area intersections and included the following recommendations for both 2025 and 2031 Mitigated Future Conditions (detailed in Table 1 and Figure 1):

- Adjustments to signal timings at nine (9) intersections
- Modifications to signal phasing and adjustments to signal timings at seven (7) intersections

- Signal modifications at seven (7) intersections
- Re-striping at eight (8) intersections
- Relocating one (1) existing bus stop along S Eads Street
- Adding new signals at three (3) intersections, including Army Navy Drive/Parking Lot/Site Driveway, S Eads Street/11th Street S/Site Driveway, and S Fern Street/Site Driveway
- Providing a protected southbound bike lane along S Eads
 Street between Army Navy Drive and 12th Street S, a
 northbound protected bike lane along S Fern Street between
 Army Navy Drive and 12th Street S, and a southbound bike
 lane along S Fern Street between Army Navy Drive and 11th
 Street S/Site Driveway

With the recommended mitigations in place, the VISSIM analysis shows, at the majority of intersections in the network, the vehicular delay results under the 2025 and 2031 Mitigated Future scenarios, with added site traffic and recommended mitigation measures, are comparable to that under the 2025 and 2031 Background scenarios. Nevertheless, as can be expected of urban infill there are still certain locations that are projected to experience delay and queuing issues where traffic is concentrated, especially along Army Navy Drive and S Eads Street, which funnel traffic to/from I-395, where congestion exists today. A comparison of the level of service (LOS) between scenarios is provided in Figure 73 and Figure 74 for 2025 and Figure 75 and Figure 76 for 2031.

It is important to note that VISSIM is a microscopic analysis rather than a macroscopic analysis. Mitigation measures are recommended such that the results are comparable or better than the Background conditions throughout the network. The recommended mitigation measures are in place to address targeted issues at specific intersections, as well as increase the vehicular throughput of the overall network, particularly at exterior intersections that are responsible for metering vehicles entering the network. Due to the increased number of vehicles being processed in the network compared to Background conditions, there may be locations where delays are higher than that seen under Background conditions.

Most vehicular capacity concerns in the study area can be alleviated through signal timing changes that adapt to changes in volume patterns, but at some locations, operational changes alone cannot mitigate future delays. As part of the proposed PenPlace project, a Transportation Management Plan (TMP) will be provided based on the County's requirements, and a framework for a TMP is included in this report, to further reduce

vehicular trips generated by the proposed development during peak period travel times.

Transportation Management Plan

A Transportation Management Plan (TMP) will be provided for the project based on the County's requirements, and a framework for a TMP is included in this report. This TMP will include typical components such as the establishment of a TMP coordinator, the distribution of transit literature, the establishment of ride-sharing programs, and the on-site sale of discounted fare media. Management measures taken by the PenPlace project can be monitored and adjusted as needed to continually create opportunities to reduce the amount of vehicular traffic generated by the site.

Summary and Recommendations

This report concludes that the proposed development has many positive elements contained within its design that minimize potential transportation impact, including:

- The proposed development's close proximity to the Pentagon City Metro Station, Pentagon Metro Station, Crystal City Metro and VRE Stations, and multiple bus lines.
- Improvements to the pedestrian facilities adjacent to the site that meet or exceed Arlington County and ADA requirements.
- Limited on-site parking, which will promote the use of nonauto modes of travel to and from the proposed development.
- The installation of new signals on Army Navy Drive, S Fern Street, and S Eads Street which provide additional signalized pedestrian crossing points, significantly improving pedestrian infrastructure near the site.
- The inclusion of publicly accessible plazas, parks, a northsouth forest walk, and an east-west multimodal path that improve pedestrian circulation and break-up a superblock.
- The provision of protected southbound bike lanes along the
 western side of S Eads Street between Army Navy Drive
 and 12th Street S, northbound protected bike lanes on S
 Fern Street S between Army Navy Drive and 12th Street S,
 and southbound protected bike lanes on S Fern Street
 between Army Navy Drive and 11th Street S/Site Driveway.
- The inclusion of secure-long-term bicycle parking significantly exceeding zoning requirements.
- The installation of short-term bicycle parking spaces within and around the perimeter of the site that meet zoning requirements.

- The inclusion of shower and locker facilities within each building that meet or exceed zoning requirements.
- A Transportation Management Plan (TMP) that aims to reduce the demand of single-occupancy, private vehicles to/from the proposed development during peak period travel times or shifts single-occupancy vehicular demand to offpeak periods.

Table	Table 1: Summary of Recommended Mitigation Measures					
	Intersection	Peak Hour				Nam Cianal
			Signal Timings	Signal Phasing	·	New Signal
1.	S Hayes St & Army Navy Dr ¹	AM PM	Yes	Modified NBL from leading to lagging phase	NB Approach: Modified to include dual left-turn lanes SB Approach: Modified to	
	Aimy Navy Di	1 101	103	to lagging phase	include dual left-turn lanes	
2.	S Fern St & Army Navy Dr	AM	Yes		NB Approach: Modified to convert the thru/right lane to a right-turn lane	
		PM	Yes		SB Approach: Modified to convert the thru/right lane to a right-turn lane	
	Danish Lat C	AM			Added NB approach	New
3.	Parking Lot & Army Navy Dr	PM		Modified to include protected EBR phasing	EB Approach: Modified to add left/thru lane and a right-turn lane	signal added
		AM	Yes	Modified SBL from	NB Approach: Modified to	
4.	S Eads St & Army Navy Dr	PM	Yes	protected-permissive to permissive Modified NBL from leading to lagging phase	 include an additional thru lane Relocate SB bus stop to the far side of the S Eads Street and 11th Street S/Site Driveway intersection 	
5.	110 Ramp &	AM	No mitigation req	uired		
<u> </u>	Army Navy Dr	PM	ga			
6.	S Eads St & 11th St	PM			 Added EB approach NB Approach: Modified to add a left-turn lane providing access into site SB Approach: Modified to convert the thru lane to a left/thru lane; and add a right- turn lane providing access into site 	New signal added
_	12th St & S	AM	Yes		o one	
7.	Hayes St	PM	Yes			
	.,	AM	Yes	Modified NBL from		
8.	12th St & S Fern St	PM	Yes	permissive to protected- permissive • Modified SBL from permissive to protected- permissive	SB Approach: Modified to add a left-turn lane	
9.	12th St & S Elm	AM	Yes			
J.	St	PM	Yes			
10.	12th St & S Eads	AM	Yes	Modified SBL from permissive to protected-	SB Approach: Modified to add a left-turn lane	
	St	PM	Yes	permissive		
11.	12th St & Army Navy Dr	AM	Yes			
	12th St & S Clark	PM	Yes			
12.		AM PM	Yes Yes			
	13th St & S Fern	AM	A1	. ,		<u> </u>
13.	St	PM	No mitigation req	uirea		
14.	13th St & S Eads	AM	Yes			
	St	PM	Yes			
15.		AM	No mitigation req	uired		

Intersection Peak			2025/2031 Mitigated Future Scenario			
	Hour		Signal Timings	Signal Phasing	Restriping/Geometric Change	New Signal
	14th St & S Fern St	PM				
	15th St & S Fern St	AM	Yes	Modified SBL from		
16.		PM	Yes	permissive to protected- permissive		
17.	15th St & S Elm	AM	Yes			
17.	St	PM	Yes			
		AM	Yes	Modified EBL from		
18.	15th St & S Eads St	PM	Yes	permissive to protected- permissive (leading protected phase) Modified WBL from permissive to protected- permissive (leading protected phase)		
	S Eads St & I- 395 Ramps (South) ²	AM	Yes			
19.		PM	Yes	Modified NBL from protected to protected- permissive		
	S Eads St & I-	AM	Yes			
20.	395 Ramps (North)	PM	Yes			
21.	14th St & S Eads	AM	Yes			
۷۱.	St	PM	Yes			
		AM			Added WB approach	
22.	S Fern St & Site Driveway	PM			NB Approach: Modified to convert the thru lane to a thru/right lane providing access into site SB Approach: Modified to include a left-turn lane providing access into site	New signal added

¹ A meeting was conducted with VDOT on November 19, 2021 regarding the proposed restriping at the S Hayes St/Army Navy Drive intersection.

² Discussions with Transurban regarding the proposed phasing changes at the S Eads Street/I-395 HOT Lanes (South) intersection are ongoing.




Figure 1: Summary of 2025/2031 Mitigated Future Scenario Findings

Introduction

This report presents the findings of a Multimodal Transportation Assessment (MMTA) conducted for the proposed PenPlace development in Arlington, VA. The site currently consists of vacant space and a hotel, and the proposed development will improve the site by adding approximately 2.8 million square feet of office space, 388,000 square feet of amenity uses, 14,500 square feet of daycare, 82,600 square feet of neighborhood-serving ground floor retail space, and 27,000 square feet of community space. The proposed project build-out year is 2025.

This site is currently zoned C-O-2.5 and is shown as a mix of high-medium residential and medium office-apartment-hotel land uses in the General Land Use Plan (GLUP).

Purpose of Study

This purpose of this study is to evaluate the transportation network in the vicinity of the site and identify any potential transportation impacts that may result from the proposed redevelopment. Elements of this report include a description of the proposed development, an evaluation of the existing multimodal network, and findings of a microscopic vehicular analysis (using VISSIM).

The scope of the analysis contained within this report was extensively discussed with and agreed to with Arlington County and VDOT staff. The general methodology of the analysis follows national, Arlington County, and VDOT guidelines on the preparation of evaluations of site development.

Study Tasks

The following tasks were completed as part of this study.

- A scoping meeting was held on October 27, 2020 with representatives from Arlington County, with a follow-up meeting held on November 13, 2020. A scoping meeting was held on November 17, 2020 with representatives from both Arlington County and the Virginia Department of Transportation (VDOT). An updated scope dated September 30, 2021, was submitted by Gorove Slade to Arlington County and VDOT. This scope includes discussions about the parameters of the study and relevant background information. A copy of the signed scoping document is included in Appendix A.
- Field reconnaissance in the vicinity of the site was performed to collect information related to the existing traffic controls, signal timings, roadway geometry, traffic flow characteristics, sidewalk conditions, bicycle facilities, and

- transit stop amenities. Notes related to the site visit are included in Appendix B.
- Traffic counts at the study area intersections were conducted by Arlington County in 2019 and early 2020 during the morning and evening peak periods.
- As outlined in the scoping document, a number of proposed developments in the vicinity of the site were assumed to be in place for the Future (2025) and Future (2031) Conditions.
- Proposed site traffic volumes were generated based on the methodology outlined in Trip Generation, 10th Edition published by the Institute of Transportation Engineers (ITE).
- Intersection capacity analysis were performed for the morning and afternoon peak hours at study area intersections. VISSIM version 11.00-14 was used to analyze the study area intersections using an agreed upon set of Measures of Effectiveness (MOEs).
- A Transportation Management Plan (TMP) framework was developed as a TMP will be necessary to meet County requirements.

Project Summary

Site Location

The project site is located in the Pentagon City area of Arlington, Virginia.

Figure 2 shows the regional location of the project. The project site is bounded by Army Navy Drive to the north, S Eads Street to the east, 12th Street S to the south, and S Fern Street to the west. The site location is shown in Figure 3.

Parcel Information

The existing site is currently occupied by vacant space and a hotel. A parcel map showing the location of the property is presented in Figure 4.

General Land Use Plan Recommendations

According to Arlington County's General Land Use Plan (GLUP), this site is listed as a mix of high-medium residential and medium office-apartment-hotel land uses. The GLUP map for the site is shown in Figure 5. The site is currently zoned C-O-2.5: Mixed-Use District. The zoning map is shown in Figure 6.

Proposed Site Plan

The proposed development site currently consists of vacant space and a hotel. The proposed development will redevelop the site to include four (4) buildings with a total of approximately 2.8 million square feet of office space 388,000 square feet of amenity uses, 14,500 square feet of daycare, 82,600 square feet of neighborhood-serving ground floor retail space, and 27,000 square feet of community space. Approximately 1,984 parking spaces will be provided in a below-grade parking garage. Vehicular access to the below-grade parking will be provided via Army Navy Drive, S Fern Street and S Eads Street. Loading access will be provided via Army Navy Drive. The proposed build-out year is 2025. The proposed site plan is shown in Figure 7 and Figure 8.

Scope and Limits of the Study Area

The study area is generally bounded by S Hayes Street to the west, Route 1 to the east, I-395 to the north, and 15th Street S to the south. The following intersections were identified for inclusion in the vehicular study area, as shown in Figure 9.

- 1. Army Navy Drive and S Hayes Street/I-395 Ramp
- 2. Army Navy Drive and S Fern Street
- 3. Army Navy Drive and Parking Lot
- 4. Army Navy Drive and S Eads Street
- 5. Army Navy Drive and VA 110 Off-Ramp
- 6. 11th Street S and S Eads Street
- 7. 12th Street S and S Hayes Street
- 8. 12th Street S and S Fern Street
- 9. 12th Street S and S Elm Street
- 10. 12th Street S and S Eads Street
- 11. 12th Street S and Army Navy Drive
- 12. 12th Street S and Long Bridge Drive/S Clark Street
- 13. 13th Street S and S Fern Street
- 14. 13th Street S and S Eads Street
- 15. 14th Street S and S Fern Street
- 16. 15th Street S and S Fern Street
- 17. 15th Street and S Elm Street
- 18. 15th Street S and S Eads Street
- 19. S Eads Street and I-395 HOT Lanes (South Node)
- 20. S Eads Street and I-395 HOT Lanes (North Node)
- 21. 14th Street S and S Eads Street (Planned)
- 22. S Fern Street and Site Driveway (Planned)

Data Sources

Sources of data for this study include Arlington County, the Virginia Department of Transportation (VDOT), the Institute of Transportation Engineers (ITE) <u>Trip Generation</u>, 10th Edition, StreetLight Data, Census Transportation Planning Products

(CTPP), VIKA Virginia, NBBJ, and the office files and field reconnaissance efforts of Gorove Slade Associates, Inc.

Contents of Study

This report contains nine (9) chapters as follows:

Study Area Overview

This chapter reviews the area near and adjacent to the project and includes an overview of the site location.

Transit

This chapter summarizes the existing and future transit service adjacent to the site, reviews how the project's transit demand will be accommodated, outlines impacts, and presents recommendations as needed.

Pedestrian Facilities

This chapter summarizes existing and future pedestrian access to the site, reviews walking routes to and from the project site, outlines impacts, and presents recommendations as needed.

Bicycle Facilities

This chapter summarizes existing and future bicycle access to the site, reviews the quality of cycling routes to and from the project site, outlines impacts, and presents recommendations as needed.

Project Design

This chapter reviews the transportation components of the project, including the site plan and access.

• Travel Demand Assumptions

This chapter outlines the travel demand of the proposed project. It summarizes the expected mode splits, multimodal trip generation, and trip distribution of the project.

Traffic Operations

This chapter provides a summary of the existing and future roadway facilities, and existing and future roadway capacity in the study area. It summarizes the distribution and routing assumptions used in the analysis. This chapter highlights the vehicular impacts of the project, including presenting mitigation measures for minimizing impacts as needed.

• Transportation Management Plan

This chapter outlines the various components of the proposed development's Transportation Management Plan (TMP).

• Summary and Conclusions

This chapter presents a summary of the recommended mitigation measures by mode and presents overall findings and conclusions.




Figure 2: Major Regional Transportation Facilities




Figure 3: Site Location




Figure 4: Parcel Map (Source: Arlington County Real Estate Map, September 2016)




Figure 5: Planned Land Uses (Source: Arlington General Land Use Plan (GLUP), February 2020)




Figure 6: Zoning Map (Source: Arlington County)




Figure 7: Site Plan - Ground Floor Plan




Figure 8: Site Plan - B2 Level Plan




Figure 9: Study Intersections

Study Area Overview

This chapter reviews the existing conditions of the surrounding transportation network and includes an overview of the site location, including a summary of the major transportation characteristics of the area and of future regional projects. Detailed characteristics of each mode and their subsequent study areas will be defined in the following chapters.

The following conclusions are reached within this chapter:

- The site is surrounded by an extensive regional and local transportation system that will accommodate the employees and patrons of the proposed development.
- The site is well-served by public transportation with access to the Metrorail's Blue and Yellow lines, the VRE, and several local and regional bus lines.
- The site is surrounded by a well-connected pedestrian environment. In the vicinity of the site, sidewalks generally meet standards recommended by the Arlington County Master Transportation Plan with some gaps in the system.
- The site has access to several on- and off-street bicycle facilities, including bicycle lanes on S Eads Street, 12th Street S, S Hayes Street, 15th Street S, 18th Street S, and S Bell Street which connect to the Mt. Vernon Trail to the east and Four Mile Run Trail to the south.
- Several local initiatives will positively impact the study area, including the S Eads Street Complete Street project, Army Navy Drive Complete Street project, the 12th Street South Complete Street project, the 15th Street Realignment project, and the Route 1 Multimodal Improvements Study.

Major Transportation Features

Overview of Regional Access

Under existing conditions, the proposed development site has ample access to regional vehicular and transit-based transportation options, as shown in Figure 2, that connect the site to destinations within Virginia, the District, and Maryland.

The site is accessible from several principal arterials such as Route 1, VA-27 (Washington Boulevard), VA-244 (Columbia Pike), and VA-110. The arterials create connections to I-395, I-66, George Washington Memorial Parkway, and ultimately the Capital Beltway (I-495) and I-95. These principal arterial roadways bring vehicular traffic within half-mile of the site, at which point minor arterials, collectors, and local roads can be used to access the site directly.

The site has access to the Blue and Yellow Lines via the Pentagon City Metro Station, Pentagon Metro Station, and Crystal City Metro Station, which provide connections to areas in Virginia, the District, and Maryland. The Blue Line connects Springfield, VA with Largo, MD and the Yellow Line connects Huntington, VA with Greenbelt, MD, with both lines providing access to the District core. Both lines provide connections to the Red Line, which provides a direct connection to Union Station, a hub for commuter rail – such as Amtrak, MARC, and VRE – in addition to all additional Metrorail lines, allowing for access to much of the DC Metropolitan area. The site is located approximately 0.5 miles northwest of the Crystal City VRE station.

The proposed development is located approximately 0.6 miles from the Mount Vernon Trail, an 18-mile off-street bicycle trail running along the Potomac River from George Washington's Mount Vernon estate to Theodore Roosevelt Island, just across the river from downtown Washington, DC. The Mount Vernon Trail connects to the W&OD, Four Mile Run, and Custis Trails in Arlington County, as well as the Capital Crescent Trail in Washington, DC, providing regional bicycle connectivity to Rosslyn and the District. A detailed review of existing bicycle infrastructure is provided in a later chapter of this report.

Overall, the site has access to several regional roadways, transit, and bicycle options, making it convenient to travel between the site and destinations in Virginia, the District, and Maryland.

Overview of Local Access

There are several local transportation options near the site that serve vehicular, transit, walking, and cycling trips under existing conditions, as shown on Figure 10.

In addition to several principal arterials, the site is served by a local vehicular network that includes several minor arterials and collectors such as 12th Street S, Army Navy Drive, Long Bridge Drive, S Eads Street, S Fern Street, S Hayes Street, and 15th Street S. In addition, there is an existing network of local roadways that provide access to the site.

Several bus systems provide local transit service in the vicinity of the site, including connections to several neighborhoods within Virginia, the District, and additional Metro stations. As shown in Figure 10, there are multiple bus routes that serve the site. In the

vicinity of the site, the majority of routes travel along Army Navy Drive, S Eads Street, 15th Street S, and S Hayes Street.

There are existing bicycle facilities that connect the site to areas within Arlington, Virginia, and the District, most notably the Mount Vernon Trail. There are bicycle lanes on S Eads Street, S Hayes Street, and 15th Street S, and protected and buffered bicycle lanes along a portion of S Eads Street south of the site, between 12th Street S and 15th Street S. There are also signed bicycle routes along Army Navy Drive and S Fern Street. A detailed review of existing and proposed bicycle facilities and connectivity is provided in a later chapter of this report.

In the vicinity of the site, most sidewalks meet Americans with Disabilities Act (ADA) standards and standards recommended by the Arlington County Master Transportation Plan. Anticipated pedestrian routes, such as those to public transportation stops, retail zones, nearby residential areas, and community amenities, provide well-connected pedestrian facilities. A detailed review of existing and proposed pedestrian access and infrastructure is provided in a later chapter of this report.

Overall, the site is surrounded by an extensive local transportation network that allows for efficient transportation options via transit, bicycle, walking, or vehicular modes.




Figure 10: Major Local Transportation Facilities

Car-sharing

Car-sharing service in Arlington is provided by Zipcar. This is a private company that provides registered users access to a variety of automobiles. Zipcar has designated spaces for their vehicles. Four (4) Zipcar locations are located within a quartermile of the site. These locations and the number of available vehicles are listed in Table 2.

E-Scooters and Dockless E-Bicycles

Four (4) electric-assist scooter (e-scooter) and electric-assist bicycle (e-bicycle) companies provide Shared Mobility Device (SMD) service in Arlington County: Bird, Helbiz, Lime and Spin. These SMDs are provided by private companies that give registered users access to a variety of e-scooter and e-bicycle options. These devices are used through each company-specific mobile phone application. Many SMDs do not have designated stations where pick-up/drop-off activities occur like with Capital Bikeshare; instead, many SMDs are parked in public space, most commonly in the "furniture zone" (the portion of sidewalk between where people walk and the curb, often where other street signs, street furniture, trees, parking meters, etc. are found). At this time, SMD pilot/demonstration programs are underway in Arlington County, the District, Fairfax County, the City of Alexandria, and Montgomery County.

Walk Score and Bike Score

Walkscore.com is a website that provides scores and rankings for the walking, biking, and transit conditions for an area. This project site is located in an area that has a walk score of 81 (or "Very Walkable"), transit score of 77 (or "Excellent Transit"), and a bicycle score of 86 (or "Very Bikeable"). Figure 11 shows the neighborhood borders in relation to the site location and displays a heat map for walkability and bikeability.

The site is situated in an area with a "Very Walkable" walk score because of the abundance of neighborhood serving retail locations, where daily errands can be completed by walking.

The proposed development is located in an area with an "Excellent Transit" transit score because of its proximity to the Pentagon City Metro Station, Pentagon Metro Station, and Crystal City Metro Station, as well as its proximity to multiple bus lines.

The site is situated in an area with a "Very Bikeable" bicycle score due to its proximity to low volume roadways, a number of bicycle lanes and trails, including the Mount Vernon Trail, and flat topography.

Table 2: Carshare Locations

Carshare Location	Number of Vehicles	
Zipcar		
Acadia at Metropolitan Park Apartments (13th Street S & S Fair Street)	1 vehicle	
Meridian at Pentagon City (1221 S Eads Street)	1 vehicle	
S Fern Street and 15 th Street S	2 vehicles	
Lenox Club Apartments (12th Street S and Army Navy Drive)	1 vehicle	
Total	5 vehicles	




Figure 11: Summary of Walk Score and Bike Score

Future Projects

There are a few County-wide initiatives, local initiatives, and planned improvements located in the vicinity of the site. These planned projects are summarized below.

County-wide Initiatives

Arlington County Master Transportation Plan (2011)

The Arlington County Master Transportation Plan (MTP), adopted in 2011 and updated in 2019, outlines goals to improve various modes of transportation throughout the County. The MTP identifies goals and objectives for each mode to improve safety and access for all users, particularly for pedestrians, bicyclists, and transit users. The Arlington County Master Transportation Plan's recommended policies for transportation in the County that apply to the PenPlace development are outlined as follows:

- Streets (2016) The County will address the street system and enhance the transportation network by: (1) Utilizing the plan's street typology to guide street planning and ensure each street type supports the general policies of complete streets and adjacent land uses; (2) Including appropriate facilities to meet and balance the needs of all modes; (3) Constructing/converting some local streets to a pedestrian priority or a shared street; (4) Accommodating travel growth through shifts to non-auto modes; (5) Designing streets to favor lower vehicular speeds; and (6) Maintaining a grid-style network to enhance connectivity. The improvements planned surrounding the site as part of the MTP are shown in Figure 12.
- Transit (2016) The County will address the transit system by: (1) Developing a Premium Transit Network of high-frequency service connecting major destinations; (2)
 Operating a Secondary Transit Network of fixed route services that improves access to destinations across Arlington; (3) Making transit more accessible and convenient to all through enhanced facilities and transit-oriented land use policies; (4) Improving Metrorail services and stations; and (5) Expanding pedestrian access to transit facilities.
- Pedestrian (2011) The County will address the pedestrian system by: (1) Completing the walkway network with appropriate facilities on both sides of arterial streets and at least one side of neighborhood streets; (2) Upgrading existing pedestrian facilities to comply with current standards; (3) Implementing measures aimed at changing motorist behavior to manage vehicular speed and minimize vehicle/pedestrian conflicts; and (4) Developing strategies to encourage more people to walk.

- Bicycle (2019) The County will address the bicycle system by: (1) Making existing streets safer and more comfortable for bicycling by all users; (2) Expanding travel safety education programs; (3) Providing a network of low-traffic-stress bicycle routes that connect all land uses; (4) Accommodating bicycle infrastructure as part of all street improvement projects; (5) Establishing bicycles as a mainstream travel mode; and (6) Encouraging bicycle facilities, including parking, showers, and lockers. The improvements planned for the bicycle facilities surrounding the site as part of the MTP are shown in Figure 13.
- Parking and Curb Space (2009) The County will address
 the parking system by: (1) Prioritizing the use of curb space,
 matching the various types of uses to the most appropriate
 locations; (2) Promoting on-street parking within residential
 neighborhoods and on commercial streets to calm traffic; (3)
 Ensuring the minimum parking needs are met and limit
 excessive parking; (4) Discouraging off-street surface
 parking; and (5) Allowing reduced parking space
 requirements for new developments in close proximity to
 frequent transit service and requiring enhanced TDM
 measures.
- Transportation Demand Management (2008) The County will address transportation demand management by: (1)
 Incorporating comprehensive TDM plans for all site plans to minimize vehicular trips and maximize the use of other modes; (2) Exploring strategies and incentives to achieve TDM measures in existing private buildings; and (3)
 Applying TDM programs to non-work travel, as well as commuting, through marketing strategies.

A number of elements in the proposed development are consistent with these policies:

Streets:

 Introducing publicly accessible open space and plazas throughout the site, breaking-up a superblock and introducing porosity and connectivity.

Pedestrian:

- Improvements to the adjacent sidewalks so that they meet or exceed County and ADA standards.
- The creation of signalized crossings at adjacent intersections.
- The inclusion of publicly accessible plazas, parks, a north-south forest walk, and an east-west multimodal path that improve pedestrian circulation and porosity.
- Providing two (2) fewer curb cuts along the perimeter of the site that reduce number of pedestrian crossings.

Bicycle:

- Short-term bicycle parking will be provided within and along the perimeter of the site.
- Bicycle rooms will be provided at the ground-level in three (3) buildings on-site, to include secure, long-term parking, showers, and lockers.
- Protected southbound bike lanes along the western side of S Eads Street between Army Navy Drive and 12th Street S and protected northbound bike lanes along the eastern side of S Fern Street between Army Navy Drive and 12th Street S, protected southbound bike lanes along the western side of S Fern Street between Army Navy Drive and 11th Street S.

Parking and Curb Space:

- On-site parking will be located in an off-street, belowgrade parking garage.
- On-site parking which meets the practical needs of the site while promoting the use of non-auto modes of travel to and from the proposed development.
- Transportation Demand Management:
 - A TMP will be implemented for the development to discourage auto travel and encourage the travel by other modes.

The MTP also identifies the following recommendations in the vicinity of the PenPlace development:

Transit:

 Expansion of the Crystal City/Potomac Yard transitway into Pentagon City, running adjacent to the development site.

• Bicycle:

- Bi-directional, protected bicycle lanes along Army Navy Drive from S Joyce Street to 12th Street S.
- Construct an off-street cycle track connecting the planned Army Navy Drive protected bicycle lane from 12th Street S to 18th Street S and the Crystal City Metrorail station.
- Upgrade the existing bicycle lanes on S Joyce Street and 15th Street S between Army Navy Drive and S Hayes to include more separation from vehicular traffic.
- Develop enhanced bicycle lanes along S Fern Street from the Pentagon Transit Center to 18th Street S. The proposed development will provide a northbound protected bike lane along the eastern side between

- Army Navy Drive and 12th Street S and a southbound protected bike lane along the western side between Army Navy Drive and 11th Street S/Site Driveway.
- Reconstruct 18th Street S between Richmond Highway (Rt. 1) and Crystal Drive to include an enhanced onstreet bicycle facility and improve the connection with the Crystal City Connector Trail, also identified in the Crystal City Sector Plan.

In direct relation to the PenPlace development, these recommendations would create additional multi-modal capacity and connectivity to the site.

Local Initiatives

Crystal City Sector Plan (2010)

The Crystal City Sector Plan, adopted in 2010, outlines the vision to transform Crystal City with more ground floor retail, high-quality office space, and more housing options through improvements to existing street, sidewalk, and bicycle networks. The key transportation-related goals of the Sector Plan include:

- Creating a high-quality public realm that strengthens the sense of community
- Providing a mix of office, residential, retail, cultural, and civic uses
- Preserving the integrity of the single-family neighborhoods
- Enhancing multimodal access and connectivity

The PenPlace development is located in Pentagon City, just outside of the Sector Plan's extents. However, the development is consistent with the outlined goals. The development includes ground floor retail and high-quality office space in all four (4) buildings and provides ample bicycle accommodations on-site. Additionally, recommendations in the Sector Plan may positively impact the connectivity of the development to the surrounding areas. Recommendations include bicycle lanes on Army Navy Drive, Long Bridge Drive, and 12th Street S, cycle tracks on S Clark Street/S Bell Street, and signed bicycle routes on S Fern Street, 12th Street S, and 15th Street S.

Crystal City Multimodal Transportation Study (2010)

The Crystal City Multimodal Transportation Study is a supporting document of the Crystal City Sector Plan that further evaluates the existing and future multimodal transportation network in Crystal City. The study highlights recommendations to improve accommodations for all travel modes, including a Complete Streets program, with recommendations for sidewalks,

crosswalks, bicycle lanes, transit facilities, on-street parking, and left-turn lanes.

Although the PenPlace development is not located in Crystal City, portions of the study extents are directly related, particularly S Eads Street. The study recommends: (1) 7- to 8-foot-wide parallel parking lanes on sections of S Eads Street; (2) Extension of bicycle lanes along S Eads Street from 15th Street S to 23rd Street S; and (3) On-street signed bicycle routes along S Eads Street from 15th Street S to Army Navy Drive, S Fern Street from 15th Street S to 12th Street S, and 15th Street S from S Fern Street to Crystal Drive.

22202 Study (2016)

In response to community concerns regarding the development impacts in Crystal City and Pentagon City, Arlington County completed a study including transportation material, data, and plans for the 22202 Zip Code. The study presents data on past, present, and projected vehicular traffic and multimodal trends for the entire zip code. Among the data presented in the report is the Journey to Work Mode Split information by census tract, which shows a 35% auto mode split in the Crystal City area and a 28% auto mode split in the Pentagon City area, which supports the mode splits assumed in this report.

Planned Improvements

S Eads Street Complete Street (2014)

Arlington County began implementing a S Eads Street complete streets project between 12th Street S and 23rd Street S in 2014. This project included the conversion of the four-lane roadway into three lanes, with two through vehicular travel lanes, a center two-way left turn lane, and new protected bicycle facilities. Pedestrian crossings were improved and parking lanes were reconfigured. The next phase of the project includes improvements along S Eads Street between 12th Street S and Army Navy Drive.

In direct relation to the PenPlace development, improvements will include a new protected bicycle lane, sidewalk, streetscape, and lighting near the development on S Eads Street, improving the multimodal connectivity to/from the site.

Army Navy Drive Complete Street (2017)

The Army Navy Drive Complete Street project will reconfigure Army Navy Drive between S Joyce Street and 12th Street S to create a multimodal complete street, featuring enhanced transit, bicycle, and pedestrian facilities. This project will include a

physically separated two-way bicycle lane along the south side of Army Navy Drive, shorter and safer pedestrian crossings, and will accommodate future dedicated transit lanes. Vehicular travel lanes will be reduced where appropriate and will be narrowed for a slower urban context. The project will also extend the Crystal City Potomac Yard Transitway into Pentagon City by adding one dedicated transit lane in each direction along Army Navy Drive between S Joyce Street and S Hayes Street. Vehicular travel lanes will be reduced where appropriate and narrowed to promote a slower, urban environment. The existing raised medians will be re-built as planted medians. The project is expected to be complete by 2024.

In direction relation to the PenPlace development, improvements will include a new separated two-way bicycle lane along the north side of the site on Army Navy Drive, reduced vehicular travel lanes, and enhanced pedestrian facilities near the development, improving the multimodal connectivity to/from the site. Signal timing and phasing at signalized intersections within this project's extent will include modifications to minimize conflicts with the cycle track along the south side of Army Navy Drive, including protected turning movements. Details on roadway reconfigurations and signal timing and phasing at signalized intersections are provided in the Traffic Operations section of this report.

12th Street S Complete Street (2016)

This project is planned in conjunction with the Crystal City
Potomac Yard Transitway extension and will include
landscaping, sidewalk, curb ramp, crosswalk, and lighting
improvements. New transportation facilities include dedicated
center-running transit lanes, shared bicycle lanes west of Army
Navy Drive, and a two-way cycle track east of Army Navy Drive.

In direct relation to the PenPlace development site, plans for the 12th Street S Complete Street project show dedicated centerrunning transit lanes extending across S Eads Street to the section of 12th Street S along the proposed development site frontage. The dedicated transit lanes will require adjustments to the signal operations at the intersections at S Eads Street, S Fern Street, and S Hayes Street. At the time of scoping, signal phasing was under study as part of a dedicated transitway study effort, led by Arlington County, and is set to be finalized. As such, signal timings, phasing, and lane configuration assumptions were based on the signal timings and phasing included in the 2025 No-Build VISSIM files provided by the County and discussions with County staff and lane

configurations included in the Transitway Extension to Pentagon City plans provided by the County.

Crystal City Transitway Extension (2019)

This project is the planned extension of the Crystal City Potomac Yard Transitway north and west into Pentagon City. It will add 1.1 miles to the existing 4.5-mile transitway, providing high-frequency, premium transit service between the Braddock Road Metrorail station and the Pentagon City Metrorail station. The project will be separated into a 12th Street S segment, from Long Bridge Drive to S Hayes Street, a Crystal Drive segment, from 15th Street S to 12th Street S and Long Bridge Drive, and a S Hayes Street segment, from 12th Street S to Army Navy Drive.

As part of the 12th Street S segment of the project, the project will add dedicated bus lanes, mixed traffic lanes, traffic signal upgrades, and three (3) new transitway stations on 12th Street S from the intersection of S Hayes Street and 12th Street S to the intersection of Long Bridge Drive and 12th Street S. New eastbound and westbound transitway stations will be provided at S Elm Street and a new eastbound station will be provided at S Hayes Street. The 12th Street S segment is currently in the concept phase.

As part of the Crystal Drive segment of the project, the project will add curbside rush hour bus-only lanes on Crystal Drive from the intersection of 15th Street S and Crystal Drive to the intersection of 12th Street S and Long Bridge Drive. The project will also add two (2) new transitway stations. One (1) station will be located on the east side of Crystal Drive at 15th Street S and one (1) station will be located on the north side of 12th Street S at Long Bridge Drive. The Crystal Drive segment is currently in the design phase, and construction will be coordinated with the 12th Street S Complete Street project in 2021/2022.

As part of the S Hayes Street segment of the project, the transitway will connect to WMATA's planned Pentagon City Center bus bays project on Army Navy Drive. The S Hayes Street segment is currently in the design phase.

At the time of scoping, signal phasing was under study as part of a dedicated transitway study effort, led by Arlington County, and is set to be finalized. As such, signal timings, phasing, and lane configuration assumptions were based on the signal timings and phasing included in the 2025 No-Build VISSIM files provided by the County and discussions with County staff and lane configurations included in the Transitway Extension to Pentagon City plans provided by the County.

In direct relation to the PenPlace development, the project will improve transit access to the site from the south by increasing the amount of dedicated rush hour bus-only lanes.

15th Street S/S Clark-Bell Street Realignment (2010)

The Crystal City Sector Plan and Crystal City Multimodal Transportation Study recommend improvements to 15th Street S to improve vehicular and pedestrian safety and conditions. In accordance with these recommendations, 15th Street S between Crystal Drive and S Clark Street and S Bell Street will ultimately be realigned such that a 3/4-acre garden park is created in the median. The project also includes improvements to S Clark-Bell Street, including traffic signals, street lighting, crosswalks, a northbound bicycle lane, street trees, and wider sidewalks. The project is currently in the design stage, with construction to be determined.

In direct relation to the PenPlace development, the project will improve the navigability of Crystal City by converting S Clark-Bell Street from a one-way grade-separated roadway to a two-way at-grade roadway.

Route 1 Multimodal Improvements Study (2021)

The Route 1 Multimodal Improvements Study (Phase 1), published by VDOT in October 2021, aims to identify opportunities for enhanced multimodal connectivity through Pentagon City and Crystal City. The study recommends that Route 1 be integrated within the urban fabric of Pentagon City and Crystal City as a multimodal, urban boulevard consistent with the context of existing and future development.

The study recommends bringing Route 1 down to grade at the existing grade-separated intersections of 15th Street S and 18th Street S. The recommended at-grade alternative for Route 1 between 12th Street S and 23rd Street S includes a total of sixlanes plus left turn lanes at 15th Street S, no left turn lanes at 18th Street S, a wide median, and a wide, urban sidewalk.

Phase 2 of the study is expected to begin in late 2021 and will include an updated analysis of the recommended alternative, a comprehensive TDM strategy to reduce future volumes along Route 1 and mitigate future congestion, and additional exploration of feasibility.

In direct relation to the PenPlace development, the recommended changes to Route 1 would improve safety and accessibility within the Pentagon City neighborhood. Additionally, the improvements identified as part of the Route 1 Multimodal

Improvements Study would enhance multimodal connectivity between Pentagon City and Crystal City.

Pentagon City Plan (2019)

Arlington County initiated the Pentagon City Planning Study in 2019 to help guide future development in Pentagon City and define the capacity for the future growth in the Pentagon City Phased Development Site Plan (PDSP). As part of this project, a transportation analysis was conducted that evaluates a series of preliminary land use scenarios and serves as the foundation for the planning study. The draft report for the study, released in November 2021, identifies potential improvements to the multimodal transportation system to better accommodate additional trips generated by future redevelopment. Multi-modal improvements recommended by the Pentagon City Plan near the PenPlace site include:

- Minimum 8-10 ft clear zone for passage along sidewalks on S Fern Street, S Eads Street, and 12th Street S;
- Creation of the Green Ribbon, which at full build-out would create approximately three (3) miles of new or improved pedestrian walks and four (4) acres of new public park space;
- Public passage for pedestrians and cyclists along the 11th
 Street corridor at the Pen Place site; and

 Enhanced bicycle facilities on S Fern Street, protected bicycle lanes on S Eads Street, a two-way cycle facility along 12th Street S under the Route 1 bridge, and protected bicycle lanes along 15th Street S.

Arlington National Cemetery's Southern Expansion (2019)

The Arlington National Cemetery's Southern Expansion project will establish a single contiguous parcel of land south of the cemetery by closing, realigning, and relocating local roadways. This project will realign Columbia Pike, modify the S Joyce Street intersection and the Columbia Pike/Washington Boulevard (Route 27) interchange, and replace Southgate Road with a new segment of S Nash Street. Roadway realignment will improve multimodal capacity and safety by adding pedestrian and bicycle facilities as well as street lighting. The realigned Columbia Pike will be rebuilt as a four-lane roadway with sidewalks on both sides and a cycle track on the north side. Construction of this project started in fall 2021 and is anticipated to be completed in 2027.




Figure 12: Street Typology (Source: Arlington County Master Transportation Plan, 2019)




Figure 13: Existing and Planned Bicycle Facilities (Source: Arlington County Master Transportation Plan, 2019)

Project Design

This chapter reviews the transportation components of the PenPlace development, including the proposed site plan and access points. It includes descriptions of the site's vehicular access, loading, parking, bicycle, and pedestrian facilities.

The proposed development site is located in the Pentagon City area of Arlington, Virginia and is bounded by Army Navy Drive to the north, S Eads Street to the east, 12th Street S to the south, and S Fern Street to the west. The site location is shown in Figure 3. The proposed site plan for the redevelopment is shown in Figure 7, and Figure 8.

The proposed development will include redeveloping the existing vacant and hotel space into four (4) buildings and three (3) retail pavilions with a total of approximately 2.8 million square feet of office space, 388,000 square feet of amenity space, 14,500 square feet of daycare, 82,600 square feet of neighborhood-serving ground floor retail space, and 27,000 square feet of community space.

The southeastern building (Tower 1) will include a total of approximately 937,675 square feet of office space, approximately 28,964 square feet of retail, and 274 secure long-term bicycle spaces.

The southwestern building (Tower 2) will include a total of approximately 911,163 square feet of office space, approximately 24,336 square feet of retail, and 244 secure long-term bicycle spaces.

The northwestern building (Tower 3) will include a total of approximately 928,240 square feet of office space, approximately 14,527 square feet of daycare space, approximately 27,000 square feet of community space, and 312 secure long-term bicycle spaces.

The northeastern building (Helix Building) will include a total of approximately 388,272 square feet of amenity office space and approximately 8,456 square feet of retail space. Secure long-term bicycle spaces will be provided in the southeastern building (Tower 1), the southwestern building (Tower 2), and the northwestern building (Tower 3).

Three (3) retail pavilions will include a total of approximately 20,763 square feet of retail.

The loading area will be located on the B2 level of the parking garage and will be shared by the four (4) buildings. A total of seven (7) large loading berths and six (6) van parking stalls will

be provided in the shared loading area. The shared loading area will be accessible from the driveway on Army Navy Drive.

Below-grade parking to approximately 1,984 parking spaces shared by the four (4) buildings will be accessible from driveways on Army Navy Drive, S Fern Street, and S Eads Street. A total of 176 short-term bicycle parking spaces, serving office, amenity, daycare, community, and retail uses for the four (4) buildings will be located within and around the perimeter of the site.

PenPlace PDSP

The PenPlace Phased Development Site Plan (PDSP) is bounded by Army Navy Drive to the north, 12th Street S to the south, S Eads Street to the east, and S Fern Street to the west. Key design guidelines of the PenPlace PDSP include:

- A publicly accessible open space feature;
- 12th Street S activation with ground floor retail; and
- Sidewalks along the perimeter of the site.

The proposed PenPlace development is consistent with the guidelines outlined above that are included in the PenPlace PDSP. This includes:

- The inclusion of three (3) publicly accessible plazas that extend throughout the site;
- Providing pedestrian access to the central plaza from every frontage of the site, which is generally consistent with the location and envisioned circulation of the original PDSP;
- The inclusion of 83,000 square feet of neighborhood serving ground-floor retail including two (2) retail pavilions along 12th Street S; and
- The inclusion of sidewalks along the perimeter of the site with other pedestrian passageways, including the addition of signalized crosswalks, pedestrian plazas, and multimodal streets to enhance access to the site.

Adjacent Roadways

Consistent with the PenPlace PDSP, the proposed development will provide improved multimodal infrastructure along the adjacent and roadways.

Army Navy Drive

As part of the proposed development and the Army Navy Drive Complete Street project, Army Navy Drive will be improved from S Fern Street to S Eads Street. Army Navy Drive is envisioned to

be an urban, tree-lined street that provides a safe and more comfortable pedestrian environment and accommodates multiple modes. Streetscape elements that contribute to this include a cycle track along the south side of Army Navy Drive, wide sidewalks, and a reduction in vehicular travel lanes that will provide short and safer pedestrian crossings. The proposed development will provide a 10-foot sidewalk and 5-foot tree area along the south side of Army Navy Drive. In addition, the proposed development will signalize the intersection of Army Navy Drive and the Parking Lot/Site Driveway.

Figure 14 shows the typical cross-section and design elements that can be expected along Army Navy Drive as part of the proposed development and the Army Navy Drive Complete Street project. Figure 18 shows the cycle track proposed for Army Navy Drive.

S Eads Street

As part of the proposed development and other approved development on the east side of S Eads Street, S Eads Street will be improved from Army Navy Drive to 12th Street S. S Eads Street is envisioned to be an urban, tree-lined street that provides a safe pedestrian environment, safe and convenient curbside management, and accommodates multiple modes. Streetscape elements that contribute to this include protected bicycle lanes along both sides of S Eads Street, on-street parking lanes along both sides of S Eads Street, and wide sidewalks. The proposed development will provide a 10-foot sidewalk, a 5-foot tree area, and a 6-foot protected bicycle lane on the west side of S Eads Street from 12th Street S to Army Navy Drive. In addition, the proposed development will signalize the intersection of S Eads Street and 11th Street S. Improvements on the east side of the street will be completed by others.

Figure 15 shows the typical cross-section and design elements that can be expected along S Eads Street when fully complete. Figure 18 shows the protected bicycle lanes proposed for S Eads Street.

S Fern Street

As part of the proposed development, S Fern Street is envisioned to be an urban, tree-lined street that provides a safe pedestrian environment, safe and convenient curbside management, and accommodates multiple modes. Streetscape elements that contribute to this include protected bicycle lanes along S Fern Street, on-street parking lanes along the east side

of S Fern Street, and wide sidewalks. The proposed development will provide a 10-foot sidewalk, 5-foot tree area along the east side of the S Fern Street, a 6-foot protected bicycle lane on the east side of S Fern Street from 12th Street S to Army Navy Drive, and a 6-foot protected bicycle lane on the west of S Fern Street from Army Navy Drive to 11th Street S/Site Driveway. In addition, the proposed development will signalize the intersection of S Fern Street and the site driveway. Improvements on the west side of the street will be completed by others as development occurs.

Figure 16, shows the typical cross-section and design elements that can be expected along sections of S Fern Street when fully complete. Figure 18 shows the protected bicycles lanes proposed for S Fern Street.

12th Street S

As part of the proposed development and the 12th Street S
Complete Street project, 12th Street S will be improved from S
Fern Street to S Eads Street. 12th Street S is envisioned to be an urban, tree-lined street that provides a safe and more comfortable pedestrian environment, and accommodates multiple modes. Streetscape elements that contribute to this include on-street parking lanes, wide sidewalks, eastbound and westbound dedicated center bus lanes, and two (2) median bus stops. The proposed development will provide a 12-foot sidewalk and 5-foot tree area on the north side of 12th Street S from S
Fern Street to S Eads Street. Figure 17 shows the typical cross-section and design elements that can be expected along 12th Street S when fully constructed.




Figure 14: Typical Cross-Section of Army Navy Drive




Figure 15: Typical Cross-Section of S Eads Street




Figure 16: Typical Cross-Section of S Fern Street




Figure 17: Typical Cross-Section of 12th Street S




Figure 18: Cycle Track and Protected Bicycle Lanes

Site Access and Circulation

Pedestrian Access

As shown in Figure 19, pedestrian access to the office component for the four (4) buildings is primarily from the central plaza. Additional pedestrian access to the office component is along 12th Street S for the southeastern building (Tower 1), along S Fern Street for the southwestern building (Tower 2), along S Fern Street and Army Navy Drive for the northwestern building (Tower 3), and along S Eads Street for the northeastern (Helix) building. Pedestrian retail access will be primarily along 12th Street S, from the central plaza. There will also be stairs and a ramp (or other accessible accommodations) provided on the north side of the site to provide access from Army Navy Drive. A circulation plan showing expected pedestrian routes is shown in Figure 20.

Bicycle Access

Bicycle access to the secure long-term bicycle parking on the ground floor of each building will be from S Eads Street for the southeastern building (Tower 1), from S Fern Street for the southwestern building (Tower 2), and from Army Navy Drive for the northwestern building (Tower 3). The northeastern building (Helix) will have access to the secure long-term bicycle parking provided in the southeastern building (Tower 1), the southwestern building (Tower 2), and the northwestern building (Tower 3). Short-term bicycle parking spaces will be placed within the site and along the perimeter of the site, along 12th Street S, Army Navy Drive, S Fern Street, and S Eads Street. Bicycle access to the site is primarily expected to occur via 12th Street S, and S Fern Street for retail use. There will also be a bike runnel provided on the north side of the site to provide access from Army Navy Drive. A circulation plan showing expected bicycle routes is shown in Figure 20.

Vehicular Access

By design there is limited direct vehicular access to each of the buildings of the proposed development. Access to the belowgrade parking garage shared among the four (4) buildings will be provided via Army Navy Drive, S Fern Street, and S Eads Street.

There are a number of on-street parking and pick-up/drop-off spaces located along the frontage of each of the four buildings. There are on-street parking and pick-up/drop-off spaces on S Fern Street, 12th Street S, and S Eads Street which provide convenient and proximate access to each of the four buildings.

A circulation plan showing expected vehicular routes is shown in Figure 20. A proposed curbside management plan is shown on Figure 22.

Loading Access

Loading access to the below-grade shared loading area will be provided via the Army Navy Drive access point, as shown on Figure 19. Trucks will be permitted to access the site by turning right from eastbound Army Navy Drive. All turns across the planned cycle track on the south side of Army Navy Drive will be protected movements (i.e., requiring a protected green arrow and "No Turn on Red"). Westbound left-turning access will be restricted. Vehicles will be permitted to make left- and right-turns when exiting the site. It is expected that most loading vehicles will exit toward I-395. While the loading dock and ramp have been designed to accommodate a WB-67, trucks of this size will be very infrequent. The arrival of a WB-67 would be scheduled and permitted during off-peak only.

A circulation plan showing expected loading routes is shown in Figure 20. AutoTURN exhibits showing the turning paths of trucks as they enter and exit the ramp to the internal, belowgrade loading are included in the Technical Appendix.

For security purposes, all delivery vehicles will be scheduled in advance and access the loading area uninterrupted. If a truck arrives unscheduled, it will be required to pull off into a separate screening area. The under-truck screening area will be located within the site, along the ramp to the loading area, to prevent trucks queuing on Army Navy Drive. A loading memorandum detailing loading access, screening procedures, and anticipated daily loading activity is included in the Technical Appendix.

Loading

Per the Zoning Ordinance, the following outlines the loading facility requirements for land uses of the development:

Office

Buildings with over 6,000 square feet of office space are required to provide one (1) loading space.

Retail

Buildings with over 3,000 square feet of retail space are required to provide one (1) loading space, with one (1) additional space for more than 15,000 square feet, one (1) additional space for more than 50,000 square feet, and one additional space for each 100,000 square feet.

Per these requirements, the proposed development is required to provide three (3) loading spaces for office use and four (4)

loading spaces for retail use, for a total of seven (7) spaces required. The PenPlace development will provide seven (7) large loading berths and six (6) van parking stalls, for a total of 13 loading spaces, which exceeds County requirements. The number of on-site loading facilities will accommodate the practical needs of the site. Figure 8 shows the locations of the loading berths and service/delivery spaces.

Parking

Based on the Arlington County Zoning Ordinance, the following outlines the vehicular parking requirements for the proposed development:

Office

One (1) space per 250 square feet of floor area on the first floor, one (1) space per 300 square feet of floor area located in the basement or on the 2nd through 5th floors, and one (1) space per 400 square feet of floor area located above the 5th floor.

Retail

One (1) space per 250 square feet of floor area on the first floor and one (1) space per 300 square feet of floor area located elsewhere in the building.

Per the Zoning Ordinance, the proposed development is required to provide 8,510 parking spaces. However, per the Reduced Parking Policy for Site Plan Office Buildings adopted in 2013, the County identified a baseline parking ratio for office buildings in Pentagon City of one (1) space per 975 square feet of floor area. A proposed development may choose to provide even less parking than this threshold via mitigations, such as:

- By supporting Transportation Demand Management programs which encourage employees to commute in ways other than driving alone;
- 2. By contributing to transit operating costs; or
- By contributing to transportation capital costs such as those related to transit, bicycle and pedestrian facilities either through direct compensation to the County or through infrastructure supplied by the developer.

The proposed development will provide 1,984 parking spaces in a below-grade parking garage shared among the four (4) buildings. The Applicant will meet County standards for providing less parking than stipulated in the County's adopted Reduced Parking Policy for Site Plan Office Buildings by providing one or more of the mitigation options listed above. This is consistent with a number of Arlington County policies and goals, the proposed development will limit on-site parking by providing a

total of 1,984 parking spaces. The amount on-site parking will meet the practical needs of the site while promoting the use of non-auto modes of travel to and from the proposed development.

A summary of the proposed parking supply by parking type is shown in Table 3.

Bicycle and Pedestrian Facilities

Bicycle Facilities

The proposed PenPlace development will make significant bicycle related improvements over existing conditions in and around the site.

On-Street Bicycle Facilities

Consistent with the Arlington County Master Transportation Plan, the proposed development will improve S Eads Street to include a 6-foot-wide southbound protected bicycle lane on the west side of S Eads Street from Army Navy Drive to 12th Street S. This facility will connect to the planned cycle track on Army Navy Drive and to the planned protected bicycle lanes south of 12th Street S. A northbound separated bicycle lane will be provided by others.

In addition, the proposed development will improve S Fern Street to include a northbound protected bike lane along the eastern side between Army Navy Drive and 12th Street S and a southbound protected bike lane along the western side between Army Navy Drive and 11th Street S/Site Driveway. Based on coordination with the County, staff has focused on creating high-quality bicycle facilities on other north-south corridors such as S Eads and S Joyce Streets, both a block away in either direction. Figure 18 shows the on-street bicycle facilities that are proposed to be provided as part of the PenPlace development.

Bicycle Parking

Per the Standard Site Plan Conditions, the following outlines the bicycle parking requirements for land uses of the development:

Office

Provide one (1) long-term space for every 6,000 square feet of office space; and one (1) short-term space for every 20,000 square feet of office space.

Retail

Provide one (1) long-term space for every 25,000 square feet of retail space; and two (2) short-term spaces for every 10,000 square feet of the first 50,000 square feet of retail space and one (1) additional space for every 12,500 square feet of additional space.

Long-Term Bicycle Parking

Per these requirements, the proposed development is required to provide:

- 157 long-term spaces for office use and two (2) long-term space for retail use in the southeastern building (Tower 1);
- 152 long-term spaces for office use and two (2) long-term space for retail use in the southwestern building (Tower 2);
- 155 long-term spaces for office use and one (1) long-term space for retail use in the northwestern building (Tower 3);
 and
- 35 long-term spaces for office use and no long-term spaces for retail use in the northeastern (Helix) building.

While 504 long-term bicycle parking spaces are required, the proposed development will provide 830 long-term bicycle parking spaces for office, and retail use, significantly exceeding zoning requirements. Secure long-term bicycle parking for the development will be located in the bicycle/locker room on the ground floor of the buildings on-site in the following locations:

- 274 spaces in the southeastern building (Tower 1);
- 244 spaces in the southwestern building (Tower 2); and
- 312 spaces in the northwestern building (Tower 3).

Secure long-term bicycle spaces for the northeastern building (Helix) will be provided in the other buildings. A bicycle repair station will be provided in each bicycle/locker room.

Short-Term Bicycle Parking

Per these requirements, the proposed development is required to provide 150 short-term spaces for office, and 20 short-term spaces for retail use. Consistent with these requirements, the proposed development will provide 176 short-term parking spaces for office and retail use. Short-term bicycle parking spaces will be placed within the site and along the perimeter of the site, along 12th Street S, Army Navy Drive, S Fern Street and S Eads Street.

A summary of the proposed bicycle parking supply is shown in Table 4.

Bicycle Showers and Lockers

Per the Standard Site Plan Conditions, the following outlines the bicycle shower and locker requirements for the office and retail uses of the development:

Showers

For office/retail buildings greater than 300,000 square feet, three (3) showers per gender, plus one (1) shower per gender for each additional 100,000 square feet or portion thereof above the first 300,000 square feet.

Lockers

For every required employee bicycle parking space, either:

- A minimum of one (1) clothes storage locker per gender shall be installed in gender-specific changing rooms; or
- 2. A minimum of one (1) clothes locker shall be installed adjacent to, but outside of changing rooms.

Per these requirements, the proposed development is required to provide:

- 10 showers per gender and 158 lockers in the southeastern building (Tower 1)
- 10 showers per gender and 153 lockers in the southwestern building (Tower 2);
- 10 showers per gender and 156 lockers in the northwestern building (Tower 3); and
- Two (2) showers per gender and 36 lockers in the northeastern (Helix) building for office and retail use.

The proposed development will provide a total of:

- 31 showers and 298 lockers in the southeastern building (Tower 1);
- 31 showers and 306 lockers in the southwestern building (Tower 2); and
- 31 showers and 316 lockers in the northwestern building (Tower 3).

Shower and lockers for the northeastern building (Helix) will be provided in the other buildings' bicycle/locker rooms.

On-site bicycle facilities including the amount of long- and shortterm bicycle parking, and the amount of bicycle storage and lockers exceeds County requirements and will encourage commuting by bicycles to and from the proposed development.

Pedestrian Facilities

Pedestrian facilities directly surrounding the site will be significantly improved along S Eads Street, S Fern Street, Army Navy Drive, and 12th Street S to provide a more inviting pedestrian environment and comply with the improvements laid

out in the Arlington County Master Transportation Plan. The existing pedestrian facilities around the site provide a quality walking environment with issues in certain locations due to sidewalk width deficiencies or substandard materials such as asphalt. This project will reduce deficiencies by adding new sidewalks and streetscape features along the perimeter of the site.

New pedestrian facilities are expected to meet or exceed Arlington County requirements with an emphasis on pedestrian safety and comfort. This includes providing one (1) fewer curb cut along the perimeter of the site compared to existing conditions that reduce the number of pedestrian crossings, sidewalks that meet or exceed the width requirements, crosswalks at all necessary locations including a number of new signalized crossing points, and curb ramps with detectable warnings. The development will also include publicly available plazas throughout the site that will significantly improve pedestrian circulation and porosity compared to existing conditions.

In addition to improvements along the perimeter of the site, consistent with the Pentagon City PDSP plan, the proposed development will provide a north-south forest walk and an east-west multimodal path through the site that improves pedestrian connectivity and site porosity.

As part of the development, the installation of three (3) traffic signals at adjacent intersections will provide additional signalized pedestrian crossing points. Signals are proposed at the following intersections:

- Army Navy Drive and Parking Lot
- S Fern Street and Site Driveway
- S Eads Street and 11th Street S/Site Driveway

These signals will help accommodate the additional pedestrian demand that the development will generate as well as significantly improve the pedestrian connectivity near the site.

Curbside Management

A review of the existing curbside management was conducted and is shown on Figure 21. Currently, on-street parking is provided along Army Navy Drive (18 parking spaces), 12th Street S (20 parking spaces), S Fern Street (18 parking spaces), and S Eads Street (19 parking spaces), for a total of 75 on-street parking spaces along the site frontage.

The proposed development includes a number of improvements to curbside management along 12th Street S, Army Navy Drive, S Fern Street, and S Eads Street fronting the perimeter of the site to be coordinated with Arlington County. Figure 22 shows the proposed curbside management to include the following improvements:

- 12th Street S will be improved by adding two (2) median bus stops, serving the planned transitway extension to Pentagon City. No changes to on-street parking are proposed.
- Army Navy Drive will be improved by removing on-street parking to facilitate vehicular access to and from the site driveway on the southern side of Army Navy Drive and to accommodate the physically separated, two-way cycle track added along the south side of Army Navy Drive as part of the Army Navy Drive Complete Street project.
- <u>S Fern Street</u> will be improved by removing several onstreet parking spaces to facilitate vehicular access to and from the site driveway on the eastern side of S Fern Street.
 20 on-street parking spaces will be provided along the site frontage.
- <u>S Eads Street</u> will be improved by relocating and upgrading
 the existing southbound bus stop at the southwest corner of
 Army Navy Drive and S Eads Street to the far side of the S
 Eads Street and 11th Street S intersection, and by removing
 several on-street parking spaces to facilitate vehicular
 access to and from the site on the western side of S Eads
 Street. 11 on-street parking spaces will be provided along
 the site frontage.

Overall, a total of 51 on-street parking spaces are proposed for streets adjacent to the site, a decrease of 24 on-street parking spaces over existing conditions.

Table 3: Vehicle Parking Summary

Building	Land Use	Development Size	Vehicle Parking Requirements	Vehicular Parking Spaces Provided
Tower 1*	Office	937,675 SF	2,544 spaces	-
Tower i	Retail	49,727 SF	116 spaces	-
Tower 2	Office	911,163 SF	2,476 spaces	-
rower z	Retail	24,336 SF	97 spaces	-
Tower 3	Office	928,240 SF	2,522 spaces	-
TOWEI 3	Daycare	14,527 SF	58 spaces	-
Helix*	Office	212,200 SF	653 spaces	-
TICIIX	Retail	8,546 SF	34 spaces	-
	Total	3,086,414 SF	8,510 spaces	1,984 spaces

^{*}This includes the square footage associated with the retail pavilions

Table 4: Bicycle Parking Summary

Building	Land Use	Development Size		Parking ements	Bicycle Parking Provided		
			Long Term	Short Term	Long Term	Short Term	
Tower 1*	Office	937,675 SF	157 spaces	47 spaces	274 spaces	-	
TOWCIT	Retail	49,727 SF	2 spaces	11 spaces	21 + 3pacc3		
Tower 2	Office	911,163 SF	152 spaces	46 spaces	244 spaces	_	
	Retail	24,336 SF	2 spaces	5 spaces	opacco		
Tower 3	Office	928,240 SF	155 spaces	46 spaces	312 spaces	-	
	Daycare	14,527 SF	1 space	3 spaces	0 . <u>2</u>		
Helix***	Office	212,200 SF	35 spaces	11 spaces	_	_	
Tionx	Retail	8,546 SF	-	1 space			
	Total	3,086,414 SF	504 spaces	170 spaces	830 spaces*	176 spaces	

Total 3,086,414 SF 504 spaces 170 spaces 830 *Long-term bicycle parking spaces for the Helix building will be provided in Tower 1, Tower 2, and Tower 3.

^{**}This reflects the above-grade square footage for the Helix building

^{**}This includes the square footage associated with the retail pavilions

^{***}This reflects the above-grade square footage for the Helix building




Figure 19: Site Access




Figure 20: Circulation Plan




Figure 21: Existing Curbside Management




Figure 22: Proposed Curbside Management

Transit

This chapter discusses the existing and planned transit facilities in the vicinity of the site, accessibility to transit, and evaluates the overall transit impacts of the project.

The following conclusions are reached within this chapter:

- The development has excellent access to transit.
- The development is located 0.2 miles from the Pentagon City Metro Station, 0.5 miles from the Pentagon Metro Station, and 0.6 miles from the Crystal City Metro Station.
- There are 16 bus stops within a quarter-mile of the site.
 These stops are directly served by WMATA (Metrobus),
 Metroway, Arlington Transit (ART), OmniRide, Fairfax
 Connector, and Loudoun County Commuter routes.

The site is well-served by numerous transit options under existing conditions. Combined, these transit services provide local, citywide, and regional transit connections and link the site with major cultural, residential, employment, and commercial destinations throughout the region. Figure 23 identifies the major transit routes, stations, and stops in the study area.

Metrorail Service

The site is located approximately 0.2 miles, 0.5 miles, and 0.6 miles from the Pentagon City Metro Station, Pentagon Metro Station, and Crystal City Metro Station, respectively. The Pentagon City Metro Station is located southwest of the development site between 12th Street S and 15th Street S on S Hayes Street. It can be reached by walking west from the site on 12th Street S. The Pentagon Metro Station is located north of the development site inside the Pentagon Transit Center. It can be reached by walking north from the site on S Fern Street. The Crystal City Metro station is located southeast of the development site between 15th Street S and 18th Street S on S Bell Street. It can be reached by walking south from the site on S Eads Street and east on 18th Street S. There are sidewalks, curb ramps, and crosswalks along routes to all three (3) Metro stations. However, along the routes to Pentagon City and Crystal City Metro Stations, there is a temporary asphalt sidewalk along the east side of S Fern Street and the north side of 12th Street S, adjacent to the site, and sidewalks closed due to construction to the south of the site along 12th Street S and S Eads Street, reducing the quality of the walking environment.

The Pentagon City, Pentagon and Crystal City Metro stations serve the Blue and Yellow lines. The average daily ridership at

the Pentagon City, Pentagon, and Crystal City stations in 2019 was approximately 12,500, 15,000, and 11,700 boardings on weekdays, respectively, according to the WMATA Ridership Data Portal. The Blue Line travels north from Springfield, VA to Rosslyn then continues east to Largo, MD. Trains run approximately every 8 minutes during the morning and afternoon peak periods. They run about every 12 minutes during weekday non-peak periods, every 20 minutes on weekday evenings after 9:30pm, and every 12-20 minutes on weekends. The Yellow Line travels north from Huntington, VA to the Pentagon, east to the District core, and continues north to Greenbelt. Trains run approximately every 8 minutes during the morning and afternoon peak periods. They run about every 12 minutes during weekday evenings after 9:30pm, and every 12-20 minutes on weekends.

Figure 24 shows the average annual weekday passenger boardings for Metro stations in the 22202 Zip Code area from 1977, when the system opened, to 2015. Metrorail ridership in 22202 zip code is down 18% from its peak in 2010 and 2011. Ridership throughout the entire system is down five percent. According to the 22202 Transportation Study, three factors have contributed to the decline in ridership including high office vacancy rates in Crystal City from Base Realignment and Closure (BRAC), changes to Blue Line service (Rush Plus/Silver Line), and an overall decrease in rider satisfaction by Metrorail users. The decline in boardings at the stations near the site indicates there is available capacity at these stations. WMATA has initiated the Back2Good plan to improve safety, reduce delays, and build rider confidence in Metrorail. Since its implementation, Metrorail has reached its highest on-time performance in the last seven years. The proposed development will increase the amount of office space in Pentagon City/Crystal City which thereby increases the number of potential riders of Metrorail. The proposed development will implement Transportation Demand Management (TDM) measures that will incentivize the use of non-auto modes of travel, including Metrorail, and discourage the use of single-occupancy auto modes of travel.

At the Pentagon City Metro Station, which is a transfer point for regional and local transit buses and bus services, a second elevator is planned on the west side of S Hayes Street.

Currently, there is a single elevator serving the station, which is located on the east side of S Hayes Street. The new elevator will

improve access for patrons and will provide redundancy when one elevator is out of service.

In order to accommodate the projected increase in demand at the Crystal City Metro Station as a result of redevelopment in Crystal City, a second entrance is planned for the station. The new entrance will provide improved access from Crystal Drive, the VRE station, and the nearby Metroway station. The project will also include improvements and upgrades to elevator and lobby facilities at the station. The second entrance is planned to open in 2025.

Bus Service

A review of the existing Metrobus stops within a quarter-mile radius of the site, detailing individual bus stop amenities and conditions, is shown in Table 5. There are 16 bus stops within one quarter-mile of the site: four (4) on Army Navy Drive, four (4) on S Eads Street, five (5) on 15th Street S, and three (3) on S Hayes Street. These stops are served by 12 WMATA (Metrobus) routes, two (2) Arlington Transit (ART) routes, one (1) OmniRide route, one (1) Fairfax Connector route, and one (1) Loudoun County Commuter Bus route. Metroway bus service is available from the Crystal City and Pentagon City Metro stations.

The site is served by several bus lines and routes along multiple primary corridors. These bus lines connect the site to many areas of Virginia and the District, including several Metrorail stations serving all of the six (6) Metrorail lines. Table 6 shows a summary of the bus route information for the routes that serve the site, including service hours, headway, and distance to the nearest bus stop.

Table 7 presents the average weekday peak hour boarding and alighting information for the bus stops previously detailed. This information is based on WMATA ridership data provided by Arlington County for 2017. Existing peak hour boarding and alighting information for these bus stops is shown on Figure 25.

Crystal City Potomac Yard Metroway

Metroway is an enhanced bus route that provides a connection between the Crystal City Metro, Pentagon City Metro, and Braddock Road Metro, traveling through Pentagon City, Crystal City, and Potomac Yard. Arlington's section of Metroway opened in April 2016 and includes an all-day dedicated transit lane through Potomac Yard, a peak period transit lane through Crystal City, and seven new transit stations. The Potomac Yard Line provides 4.5 miles of service between the Crystal City, Pentagon City, and Braddock Road Metro stations with faster,

more reliable bus service along the Route 1 corridor, with a ridership of approximately 2,400 passengers per day.

Metroway buses travel in dedicated bus-only lanes adjacent to the site along 12th Street S; however, there are also sections of the route in Crystal City and Potomac Yard where Metroway buses operate in mixed traffic, such as Army Navy Drive adjacent to the site. The nearest stop to the site is at the corner of 12th Street S and S Hayes Street adjacent to the Pentagon City Metro entrance at the end of the Metroway line. All buses from that stop proceed south to Crystal City and the Braddock Road Metro Station.

Figure 26 shows the 10-minute, 20-minute, and 30-minute transit travel shed to and from the proposed development. As shown in the transit travel shed, most of the District and Northern Virginia area is accessible via transit within 30 minutes from the proposed development. Several destinations in the District, Arlington, and Alexandria are accessible within a 20-minute transit trip from the proposed development, including Ronald Reagan Washington International Airport, Downtown DC, and Metro stations served by all metro lines in the area.

Planned Transit Facilities

Improvements to transit facilities will be made as part of the Army Navy Drive Complete Street project, the 12th Street S Complete Street project, and the Pentagon City Transitway Extension project.

- As part of the Army Navy Drive Complete Street project, improvements will include a dedicated transit-only lane in each direction extending along Army Navy Drive between S Joyce Street and S Hayes Street.
- As part of the 12th Street S Complete Street project, improvements will include dedicated center-running transitonly lanes extending along 12th Street S from Army Navy Drive to S Hayes Street.
 - At the time of scoping, signal phasing was in development as part of a dedicated transitway study effort, led by Arlington County. Signal timings, phasing, and lane configurations along 12th Street S were consistent with those included in the base VISSIM model provided by Arlington County and the Interim Condition Plan for 12th Street S. Details on roadway reconfigurations and signal timing and phasing at signalized intersections are provided in the Traffic Operations section of this report.
- As part of the Crystal Drive segment of the Transitway Extension to Pentagon City project, improvements will

initially include curbside rush hour bus-only lanes from 15th Street S to 12th Street S and Long Bridge Drive and five (5) new transitway stations, with two (2) additional stations included in later phases.

Planned transit improvements are shown in Figure 27.




Figure 23: Existing Transit Facilities

Annual Average Passenger Boardings

Pentagon City and Crystal City Metrorail Stations (1977 - 2015)



Figure 24: Annual Metro Ridership at Pentagon City and Crystal City Metro Stations (Source: 22202 Transportation Study)

Table 5: Bus Stop Inventory

Location	Stop ID	Buses Served	Stop Condition
15th Street & Fern Street (EB)	6000208	7A, 7F, 10A, 22A	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, information case, seating, shelter, trash receptacle
15th Street & Fern Street (WB)	6000212	7A, 7F, 10A, 10N, 22A	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, information case, seating, no shelter
15th Street & S Eads Street	6000214	10A	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter
15th Street & S Eads Street	6000217	10A, 10N, 599	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter
15th Street S & Hayes Street S	6000224	7A, 7F, 10A, 10N, 22A, Fairfax Connector	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter
Army Navy Drive & S Eads Street	6000268	10A, 10E, 16A, 16C, 16E, 42, 87, 87A, 87P, 599	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, information case, no seating, no shelter
Army Navy Drive & Fern Street	6000272	10A, 10E, 16A, 16C, 16E, 42, 87, 87A, 87P	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, information case, no seating, no shelter
Army Navy Drive & S Hayes Street	6000273	10A, 16E, 16G, 16H, 42, 87, 87A, 87P	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, information case, no seating, no shelter
Army Navy Drive & S Hayes Street	6000281	10A, 16A, 16C, 16E, 16G, 16H, 42, 87, 87A, 87P	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, information case, seating, shelter
S Eads Street & Army Navy Drive	6000878	7A, 7F, 7Y, 10N, 22A, Loudoun County Commuter	Sign, ADA Clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter
S Eads Street & 15th Street S	6000879	7A, 7F, 7Y, 10N, 22A	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, information case, no seating, no shelter
13th Street & S Eads Street	6001375	7A, 7F, 7Y, 10N, 22A	Sign, ADA clearance, acceptable sidewalk clearance, no street lighting, no information case, no seating, no shelter
S Hayes Street & 12th Street	6001385	7A, 7F, 22A	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, no information case, seating, shelter
Pentagon City Station & Bus Bay B	6001401	10N, 16E, 16G, 16H	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter
Pentagon City Station & Bus Bay C	6001402	7A, 7F, 22A, Metroway	Sign, ADA clearance, acceptable sidewalk clearance, street lighting, no information case, seating, shelter
12th Street & S Eads Street	Eads12NB	OmniRide (L-200)	Sign, no ADA clearance, acceptable sidewalk clearance, street lighting, no information case, no seating, no shelter

Table 6: Bus Route Information

Route Number	Route Name	Service Hours	Headway	Walking Distance to Nearest Bus Stop	
10A 10E, 10N	Alexandria-Pentagon Line	Weekdays: 5:00AM-2:55AM Weekend: 5:30AM-2:55AM	— 30-60 min	<0.1 miles, 1 minute	
7A, 7F, 7Y	Lincolnia-North Fairlington Line	Weekdays: 5:09AM-12:18AM Weekend: 7:00AM-2:00AM	- 7-30 min	0.2 miles, 4 minutes	
16A, 16C, 16E	Columbia Pike Line	Weekdays: 4:57AM-2:39AM Weekend: 5:39AM-2:39AM	5-25 min	<0.1 miles, 1 minute	
16G, 16H	Columbia Pike-Pentagon City Line	Weekdays: 5:24AM-11:00PM Weekend: 6:25AM-10:55PM	- 6-30 min	0.2 miles, 4 minutes	
22A	Barcroft-South Fairlington Line	Weekdays: 9:39AM-3:09PM, 8:09PM-10:09PM Weekend: 6:39AM-9:39PM	30-60 min	0.2 miles, 4 minutes	
ART 42	Ballston-Pentagon Line	Weekdays: 6:08AM-8:00PM Weekend: 7:12AM-7:42PM	15-30 min	<0.1 miles, 1 minute	
ART 87	Pentagon Metro - Army Navy Drive - Shirlington Line	Weekdays: 6:20AM-11:16PM Weekend: 7:28AM-11:28PM	20-33 min	<0.1 miles, 1 minute	
LC Commuter	Telos-Arlington/Washington DC Line	Weekdays: 6:35AM-8:35AM, 3:10PM-5:23PM	5-70 min	0.2 miles, 4 minutes	
599	Pentagon-Crystal City Express Line	Weekdays: 6:14AM-8:44AM, 3:32PM-6:02PM	20-35 min	0.2 miles, 4 minutes	
L-200	Lake Ridge-Pentagon & Crystal City	Weekdays: 6:21AM-7:55AM, 12:24PM-6:49PM	10-30 min	0.2 miles, 4 minutes	
Metroway	Potomac Yard Line	Weekdays: 5:30AM-12:00AM Weekend: 6:30AM-12:00AM	- 6-30 min	0.3 miles, 5 minutes	

Table 7: Bus Stop Boarding and Alighting Weekday Information – Peak Hours

	Stop ID	Routes	AM Peak Period		PM Peak Period		Daily	Daily
Stop		Served	Boardings	Alightings	Boardings	Alightings	Boardings	Alightings
		7A	0	0	0	0	0	0
15th Street & Fern Street (EB)		7F	0	0	0	0	0	0
	6000208	10A	3.5	1.1	8.6	1.8	26.4	5.9
		22A	0	0	0	0	1.4	7.3
		7A	0	0	0	0	0	0
		7F	0	0	0	0	0	0
15th Street & Fern Street (EB)	6000212	10A	1.1	4.5	3.1	5.3	7.3	17.3
		10N	0	0	0	0	0.3	0
		22A	0	0	0.4	0	2.7	0.4
15th Street & S Eads Street (EB)	6000214	10A	1.4	0.7	13.3	0.6	21.5	3.2
451.00	0000017	10A	0.1	6.6	1.7	2	2.3	17.6
15th Street & S Eads Street	6000217	10N	0	0	0	0	0	0
		7A	0	0	0	0	0	0
		7F	0	0	0	0	0	0
4Eth Stroot C & Have Court C	6000004	10A	0	5.1	0.3	8.7	0.8	28.8
15th Street S & Hayes Street S	6000224	10N	0	0	0	0	0	0
		22A	0	0	0.2	0	1.8	0.1
		599	NA	NA	NA	NA	NA	NA
		10A	2.3	0.3	4.4	0.8	7.2	1.1
		10E	0	0	5.6	0.5	5.6	0.5
	6000268	16A	5.2	1.1	15.4	0.7	21.3	2
		16C	15.2	10	37.1	17.5	53.2	27.6
		16E	0	0	0	0	0.3	0.2
Army Navy Drive & S Eads Street		42	0	0	0	0	4	2
		87	0	0	0	0	3	1
	42202	87A	0	0	0	0	0	0
		87P	0	0	0	0	0	0
		599	NA	NA	NA	NA	NA	NA
		10A	1	0.7	1.6	0.3	2.8	1
		10E	0	0	1	0	1	0
	6000272	16A	1	1.1	2.7	0.1	4.7	1.3
		16C	0.8	1.2	8	4.1	10.5	5.7
		16E	0	0	0	0	0.9	0.4
Army Navy Drive & Fern Street		42	0	0	0	0	3	2
		87	0	0	0	0	2	1
	42203	87A	0	0	0	0	1	0
		87P	0	0	0	0	0	0
		Loudoun						
		Commuter	NA	NA	NA	NA	NA	NA
		Commuter 10A	0	0.4	0.1	1.8	1.4	7.8
		10E	0.4	12.3	0.1	0	0.4	14
	600273	16E	0.4	0	0	0	0.4	0.7
Army Navy Drive & S Hayes	000213	16G	0.5	6.2	0.3	12.9	1.8	42.3
Street		16H	0.5	0.2	0.3	0	0	0
	-	42	NA	NA	NA	NA	NA	NA
	42205	87	NA NA	NA NA	NA NA	NA NA	NA NA	NA NA
	6000281	10A	1.9	0.4	10.2	2.1	21.1	4
	-	IUA	1.5	0.4	10.2	۷.۱	۷۱.۱	+

Ston	Stop ID	Routes Served	AM Peak Period		PM Peak Period		Daily	Daily
Stop			Boardings	Alightings	Boardings	Alightings	Boardings	Alightings
		10E	0	0	13.4	0.7	13.4	0.7
		16A	1.4	0.5	14.5	2.3	42.9	5.9
		16C	3.4	1.8	42.2	17.8	74.2	23.7
Army Navy Drive & S Hayes		16E	0	0	0	0	25.7	0.8
Street		16G	3.3	0.1	40.1	1.1	99.9	4.7
		16H	0	0	0	0	0	0
	40004	42	NA	NA	NA	NA	NA	NA
	42204	87	NA	NA	NA	NA	NA	NA
		7A	0	0	0	0	0	0
		7F	0	0	0	0	0	0
	6000878	7Y	24.4	33.3	0	0	25	35.1
S Eads Street & Army Navy Drive		10N	0	0	0	0	0	0
		22A	0	0	0.3	0	0.7	0.1
		Loudoun County Commuter	NA	NA	NA	NA	NA	NA
		7A	0	0	0	0	0	0
		7F	0	0	0	0	0	0
S Eads Street & 15th Street	6000879	7Y	15.5	13.7	0	0	16.7	15.5
		10N	0	0	0	0	0	1
		22A	0	0	0	0	1.2	0.3
		7A	0	0	0	0	0	0
		7F	0	0	0	0	0	0
S Eads Street & 13th Street	6001375	7Y	35.6	28.2	0	0	37.9	29.5
		10N	0	0	0	0	0.2	0
		22A	0	0	0	0	0.3	0.1
		7A	0	0	0	0	0	0
S Hayes Street & 12th Street	6001385	7F	0	0	0	0	0	0
		22A	0	0	0	0	1	21
		10N	0	0	0	0	0	0
Pentagon City Station & Bus Bay	6001401	16E	0	0	0	0	49.4	7.1
В		16G	29.7	207.9	278.3	78.6	526.9	524.3
		16H	0	0	0	0	0	0
		7A	0	0	0	0	0	0
Pentagon City Station & Bus Bay	6004400	7F	0	0	0	0	0	0
C	6001402	22A	0	0	1.7	0.1	22	1.7
IMPAGE Did out to Date out the Aut		Metroway	75.9	41.3	81.7	100.4	284.2	282.4

WMATA Ridership Data provided by Arlington County

NA: Ridership data unavailable




Figure 25: Peak Hour Boardings and Alightings by Stop




Figure 26: Approximate Transit Travel Times




Figure 27: Planned Transit Improvements

Bicycle Facilities

This chapter summarizes existing and future bicycle access and reviews the quality of cycling routes to and from the site.

The following conclusions are reached within this chapter:

- The site has access to several on- and off-street bicycle facilities, including bicycle lanes on S Eads Street, S Hayes Street, 15th Street S, 18th Street S, and Crystal Drive which connect to the Mt. Vernon Trail to the east and Four Mile Run Trail to the south.
- Future planned projects in the vicinity of the site include bicycle lanes along Army Navy Drive, S Eads Street, and 12th Street as part of the Army Navy Drive, S Eads Street, and 12th Street South Complete Street projects. These will further improve bicycle access and connectivity by upgrading bicycle facilities along these routes.
- Consistent with the Arlington County Master Transportation Plan, the proposed development will provide southbound protected bicycle lanes on S Eads Street from Army Navy Drive to 12th Street S and northbound protected bicycle lanes on S Fern Street from Army Navy Drive to 12th Street S.
- As part of the proposed development, short- term bicycle
 parking spaces will be provided along the perimeter of the
 site. Long-term bicycle parking spaces, showers, and
 lockers will be provided for use of the employees of the site.

Existing Bicycle Facilities

The site has access to several existing on- and off-street bicycle facilities, including bicycle lanes on S Hayes Street, S Eads Street, 15th Street S, and Crystal Drive. Figure 28 shows the existing facilities within the study area. There are also protected and buffered bicycle lanes along a portion of S Eads Street south of the site, between 12th Street S and 23rd Street S. Protected bicycle lanes provide physical separation such as an on-street parking lane between bicycles and motor vehicles (also known as a cycle track) and buffered bicycle lanes have the same function as standard bicycle lanes with a marked buffer on one side of the lane. These bicycle facilities connect to a network of bicycle facilities that provide connections to the Mt. Vernon Trail to the east and Four Mile Run Trail to the south.

Arlington County publishes an annual Bicycle Comfort Level Map highlighting the most comfortable bicycle routes throughout Arlington County. The map uses a rating system of "perception of comfort" to show which routes are most comfortable. Routes are rated as 'Easy', 'Medium', 'Challenging', 'Expert Level', or

'Prohibited'. The most recent publication of the map (2020) shows the majority of bicycle routes in the vicinity of the site rated as 'Medium' and 'Challenging'. S Eads Street is rated 'Medium', and Army Navy Drive is rated 'Challenging' adjacent to the site.

No bicycle parking is provided along the perimeter of the site under existing conditions. Short-term bicycle racks are available at the Pentagon City, Pentagon, and Crystal City Metro Stations as well as at the Metroway stop in the vicinity of the site.

Figure 29 shows the 10-minute, 20-minute, and 30-minute bicycle travel shed for the proposed development. Within a 10-minute bicycle ride, the proposed development has access to several destinations including the Mount Vernon and Four Mile Run trails, public transportation stops, Metro stations served by the Blue and Yellow lines, the Crystal City VRE Station, retail zones, residential neighborhoods, and community amenities. Within a 20-minute bicycle ride, the proposed development has access to destinations in the District, Arlington, and Alexandria such as Custis Trail, Arlington Memorial Bridge, Lincoln Memorial, residential neighborhoods, and retail zones. Within a 30-minute bicycle ride, the proposed development is accessible to most of Arlington and Alexandria, and several destinations in the District including Downtown, and the Southwest Waterfront.

Capital Bikeshare

In addition to personal bicycles, the Capital Bikeshare program provides additional cycling options for residents and patrons of the proposed development. The Bikeshare program has placed over 550 Bikeshare stations across Washington, DC, Arlington County, VA, City of Alexandria, VA, Montgomery County, MD, Fairfax County, VA, Prince George's County MD, and most recently the City of Falls Church, VA, with over 4,500 bicycles provided. There are three (3) existing Capital Bikeshare stations that house a total of 50 bicycles within a quarter-mile of the site, located along S Eads Street, S Fern Street, and S Hayes Street. There are six (6) additional stations located within one half-mile of the site.

E-Scooters and Dockless E-Bicycles

Four (4) electric-assist scooter (e-scooter) and electric-assist bicycle (e-bicycle) companies provide Shared Mobility Device (SMD) service in Arlington County: Bird, Helbiz, Lime and Spin. These SMDs are provided by private companies that give

registered users access to a variety of e-scooter and e-bicycle options. These devices are used through each company-specific mobile phone application. Many SMDs do not have designated stations where pick-up/drop-off activities occur like with Capital Bikeshare; instead, many SMDs are parked in public space, most commonly in the "furniture zone" (the portion of sidewalk between where people walk and the curb, often where other street signs, street furniture, trees, parking meters, etc. are found). At this time, SMD pilot/demonstration programs are underway in Arlington County, the District, Fairfax County, the City of Alexandria, and Montgomery County.

Planned Bicycle Facilities

Existing bicycle facilities have been recommended by the Arlington County Master Transportation Plan and Crystal City Sector Plan to be upgraded in the future, as shown on Figure 13, including adding bicycle lanes along Army Navy Drive between S Joyce Street and 12th Street S, adding bicycle lanes along S Eads Street between Army Navy Drive and 12th Street S, adding bicycle lanes along S Fern Street between the Pentagon Transit Center and 18th Street S, and adding off-street bicycle facilities along S Clark Street/S Bell Street between 12th Street S and 18th Street S.

The recently adopted Bicycle Element of the Arlington County Master Transportation Plan identifies 15th Street S as a Primary Bicycling Corridor. The plan makes the following recommendations:

- Reconstruct Army Navy Drive to include bi-directional, protected bicycle lanes from S Joyce Street to 12th Street S.
- Construct an off-street cycle track connecting the planned Army Navy Drive protected bicycle lane at 12th Street S to 18th Street S and the Crystal City Metrorail station
- Reconstruct 18th Street S between Richmond Highway (Rt. 1) and Crystal Drive to include an enhanced on-street bicycle facility and improve the connection with the Crystal City Connector Trail. Also identified in the Crystal City Sector Plan.
- Upgrade the existing bicycle lanes on S Joyce Street and 15th Street S between Army Navy Drive and S Hayes Street to include more separation from motor vehicle traffic.
- Develop an enhanced bicycle facility on S. Fern Street between the Pentagon reservation and 18th Street South. The proposed development will provide a northbound protected bike lane along the eastern side between Army Navy Drive and 12th Street S and a southbound protected

bike lane along the western side between Army Navy Drive and 11th Street S/Site Driveway.

In December 2020, County staff developed recommendations for a bicycle network that provides new north-south bicycle facilities along with improvements to east-west streets in Crystal City. Following public input in 2021, the updated Recommended Crystal City Bike Network includes:

- Southbound protected bicycle lane on Crystal Drive between 18th Street S and 23rd Street S.
- Northbound, contraflow protected bicycle lane on S
 Clark/Bell Street between 26th Street S and 20th Street S.
- Protected or buffered/partially buffered eastbound and westbound bicycle lanes on 15th Street S, 18th Street S and 23rd Street S.
- Westbound buffered bicycle lane connecting Crystal Drive and the contraflow bicycle lane on S Clark/Bell Street.

Several bicycle infrastructure improvements are planned in the study area as parts of other planned projects:

- As part of the Army Navy Drive Complete Street project, separated two-way bicycle lanes will be installed along the south side of Army Navy Drive between S Joyce Street and 12th Street S.
- As part of the S Eads Street Complete Street project, buffered bicycle lanes will also be installed on the east side of S Eads Street from Army Navy Drive to 12th Street S.
- As part of the S Eads Street Protected Bicycle Lanes
 Extension and Metropolitan Park 6, 7, 8 project, protected bicycle lanes will be installed along both sides of S Eads
 Street from 12th Street S to 15th Street S and the S Eads
 Street and 15th Street S intersection will be reconfigured as a protected intersection.
- As part of the 12th Street S Complete Street project, shared lanes are planned from S Hayes Street to Clark Street/Long Bridge Drive, connecting to the existing bicycle lanes on Crystal Drive east of the site.
- As part of the 12th Street S/S Clark-Bell Street Realignment project, an off-street trail will be installed along the west side of S Clark Street.
- As part of the Metropolitan Park 6, 7, 8 project, separated bicycle lanes will be installed along the west side of S Eads Street from 12th Street S to 15th Street S, protected bicycle lanes will be provided along both sides of 15th Street S between S Elm Street and Route 1, and a protected intersection will be provided at S Eads Street and 15th Street

S, improving sightlines and providing more separation between bicycles and vehicles.

PenPlace Related Improvements

The proposed PenPlace development will make significant bicycle related improvements over existing conditions in and around the site.

On-Street Bicycle Facilities

Consistent with the Arlington County Master Transportation Plan, the proposed development will improve S Eads Street to include a 6-foot-wide southbound protected bicycle lane on the west side of S Eads Street from Army Navy Drive to 12th Street S. This facility will connect to the planned cycle track on Army Navy Drive and to the planned protected bicycle lanes south of 12th Street S. A northbound protected bicycle lane will be provided by others.

In addition, the proposed development will improve S Fern Street to include a northbound protected bike lane along the eastern side between Army Navy Drive and 12th Street S and a southbound protected bike lane along the western side between Army Navy Drive and 11th Street S/Site Driveway. Based on coordination with the County, staff has focused on creating high-quality bicycle facilities on other north-south corridors such as S Eads and S Joyce Streets, both a block away in either direction. Figure 18 shows the on-street bicycle facilities that are proposed to be provided as part of the PenPlace development.

Bicycle Parking

The proposed development will include both short- and long-term bicycle parking spaces. The proposed development will provide 176 short-term parking spaces for office and retail use, meeting zoning requirements. The proposed development will provide 830 long-term bicycle parking spaces for office, and retail use, significantly exceeding zoning requirements. Secure long-term bicycle parking for the development will be located on the ground floor of each building on-site, with 274 spaces in the southeastern building (Tower 1), 244 spaces in the southwestern building (Tower 2), and 312 spaces in the northwestern building (Tower 3). Secure long-term bicycle spaces for the northeastern building (Helix) will be provided in the southeastern building (Tower 1), the southwestern building (Tower 2), and the northwestern building (Tower 3). Short-term bicycle parking spaces will be placed within the site and along the perimeter of the site, along Army Navy Drive, 12th Street S, S Fern Street, and S Eads Street.




Figure 28: Existing Bicycle Facilities




Figure 29: Approximate Bicycle Travel Times




Figure 30: Future Bicycle Facilities

Pedestrian Facilities

This chapter summarizes the existing and future pedestrian access to the site and reviews walking routes to and from the site.

The following conclusions are reached within this chapter:

- The existing pedestrian infrastructure surrounding the site provides a quality walking environment. There are sidewalks along the majority of primary routes to pedestrian destinations with a number of gaps in the system.
- Planned and proposed improvements to the pedestrian infrastructure surrounding the site will improve pedestrian comfort and connectivity.
- The proposed development will provide a more inviting pedestrian environment by adding new sidewalks and streetscape features along the perimeter of the site that meet or exceed Arlington County requirements. The project will include publicly available plazas throughout the site to improve pedestrian circulation.

Pedestrian Study Area

Pedestrian facilities within a quarter-mile of the site were evaluated as well as routes to nearby transit facilities, including routes to Pentagon City Metro Station to the west, Pentagon Metro Station to the north, and Crystal City Metro Station to the south. The site is accessible to transit options such as the bus stop adjacent to the site on S Eads Street and the Metroway at the Pentagon City Metro Station 0.2 miles west from the site. In general, existing pedestrian facilities surrounding the site provide comfortable walking routes to and from nearby transit options. However, there are some areas of concern within the study area that negatively impact the quality and attractiveness of the walking environment. This includes physical barriers that limit pedestrian connectivity.

Figure 32 shows expected pedestrian pathways, walking time and distances, and barriers or areas of concern. Route 1 bifurcates through Crystal City from north to south. Although Route 1 is not a full pedestrian barrier, it presents challenges for pedestrians by limiting east-west connection points to approximately every 1000 feet. The study area is also bordered by I-395 further to the west and to the north, as well as the Pentagon which limits pedestrian connectivity to areas to the west and north of Pentagon City.

Figure 33 shows the 10-minute, 20-minute, and 30-minute walk travel shed for the proposed development. Within a 10-minute

walk, the proposed development has access to several destinations including public transportation stops, Metro stations served by the Blue and Yellow lines, Long Bridge Park, the Pentagon Transit Center, the Crystal City VRE Station, the Mount Vernon Trail, retail zones, nearby residential neighborhoods, and community amenities. Within a 20-minute walk, the proposed development has access to destinations such as residential neighborhoods to the south and west, retail zones in Crystal City, and Arlington National Cemetery. Within a 30-minute walk, the proposed development has access to destinations including Ronald Reagan Washington International Airport, Four Mile Run Trail, and residential neighborhoods to the south and west.

Existing Pedestrian Facilities

A review of pedestrian facilities surrounding the proposed development shows that many facilities provide a quality walking environment. Figure 28 shows a detailed inventory of the existing pedestrian infrastructure surrounding the site. Sidewalks, crosswalks, and curb ramps are evaluated based on the guidelines set forth by the Arlington County, and ADA standards. Sidewalk and buffer widths and recommendations are shown in Table 8. It should be noted that the sidewalk widths shown in Figure 34 reflect the total sidewalk widths based on observations in the field taken from curb to building, with pinch points and locations with a clear width of less than four (4) feet noted.

ADA standards require that curb ramps be provided wherever an accessible route crosses a curb and must have a detectable warning. Additionally, curb ramps shared between two crosswalks is not desired. As shown in Figure 34, under existing conditions the majority of curb ramps meet ADA standards.

Within the study area, the majority of roadways have existing sidewalks on both sides, with some deficiencies. Of note, portions of the sidewalk along the east side of S Eads Street, the east side of S Fern Street adjacent to the site, and the north side of 12th Street S adjacent to the site that have a temporary asphalt sidewalk. In addition, there are sidewalks closed due to construction to the south of the site along 13th Street S, S Eads Street, S Elm Street, and 15th Street S, which reduce the quality of the walking environment toward the Pentagon City and Crystal City Metro Stations. Despite some deficiencies, all primary

Table 8: Sidewalk Recommendations per Arlington County Master Transportation Plan

Street Name	Section	Minimum Sidewalk Width	Minimum Sidewalk Width Met	Sidewalk Width*	Minimum Buffer Width	Minimum Buffer Width Met	Buffer Width*
Army Navy Drive	S Hayes Street to S Fern Street	6-12 ft	N	5 ft	6 feet	Υ	6 ft
Army Navy Drive	S Fern Street to S Eads Street	6-12 ft	N	< 5 ft	6 feet	Υ	6 ft
Army Navy Drive	S Eads Street to 12 th Street S	6-12 ft	N	< 5 ft	6 feet	N	None
S Hayes Street	Army Navy Drive to 12 th Street S	6-12 ft	Υ	12+ ft	6 feet	Υ	6 ft
S Hayes Street	12 th Street S to 15 th Street S	6-12 ft	Υ	12+ ft	6 feet	Υ	6 ft
12 th Street S	S Hayes Street to S Fern Street	10-12 ft	N	7 ft	6 feet	Υ	6 ft
12 th Street S	S Fern Street to S Eads Street	10-12 ft	Υ	10 ft	6 feet	Υ	6 ft
12th Street S	S Eads Street to Crystal Drive	6-12 ft	Υ	8 ft	6 feet	N	None
S Fern Street	Army Navy Drive to 12th Street S	6-12 ft	N	< 5 ft	6 feet	Υ	7 ft
S Fern Street	12 th Street S to 15 th Street S	6-12 ft	Υ	6 ft	6 feet	N	4 ft
S Eads Street	Army Navy Drive to 12th Street S	6-12 ft	N	< 5 ft	6 feet	N	None
S Eads Street	12 th Street S to 15 th Street S	6-12 ft	Υ	8 ft	6 feet	Υ	7 ft
S Elm Street	12 th Street S to 13 th Street S	6-8 ft	Υ	10 ft	4-6 feet	Υ	6 ft
S Elm Street	14 th Street S to 15 th Street S	6-8 ft	Υ	None	4-6 feet	N	None
13 th Street S	S Fern Street to S Eads Street	6-8 ft	Υ	10 ft	4-6 feet	Υ	5 ft
14 th Street S	S Fern Street to S Elm Street	6-8 ft	Υ	9 ft	4-6 feet	Υ	6 ft
15 th Street S	S Hayes Street to S Fern Street	6-12 ft	Υ	6 ft	6 feet	Υ	6 ft
15 th Street S	S Fern Street to S Eads Street	6-12 ft	Υ	9 ft	6 feet	N	4 ft
15 th Street S	S Eads Street to Crystal Drive	10-16 ft	Υ	12+ ft	6 feet	Υ	None
12 th Road S	S Elm Street to S Fair Street	6-8 ft	Υ	10 ft	4-6 feet	Υ	6 ft
S Fair Street	12 th Road S to 14 th Road S	6-8 ft	Υ	6 ft	4-6 feet	Υ	6 ft
14 th Road S	S Fair Street to S Elm Street	6-8 ft	Υ	9 ft	4-6 feet	Υ	6 ft

^{*} Widths based most narrow measurement along either side of roadway section

pedestrian destinations are accessible via routes with sidewalks, most of which meet Arlington County and ADA standards.

Overall, the site is situated within an urban transportation network, with quality pedestrian access. Figure 31 shows the existing pedestrian peak hour volumes at study area intersections. The most heavily-used crosswalk in the study area is across S Fern Street on the north side of 12th Street S, most likely a result of the proximity to the Pentagon City Metro Station on the southwest corner of S Hayes Street and 12th Street S.

Planned Pedestrian Facilities

As a result of the development, pedestrian facilities around the perimeter of the site will be improved to meet Arlington County and ADA standards. This includes the improvement of sidewalks along the site frontage along S Eads Street, S Fern Street, Army Navy Drive, and 12th Street S so that they meet or exceed width requirements and provide a more inviting pedestrian

environment. The development will also include publicly available plazas that will improve pedestrian circulation.

Additional improvements will be made as part of the Army Navy Drive Complete Street project, the S Eads Street Complete Street project, and the 12th Street S Complete Street project.

The proposed development will reduce deficiencies by providing improved sidewalk and streetscape features throughout the site. In addition to improvements along the perimeter of the site, consistent with the Pentagon City PDSP plan, the proposed development will provide a north-south forest walk and an east-west multimodal path through the site that improves pedestrian connectivity and site porosity.

As part of the development, signals are proposed at the following intersections:

- · Army Navy Drive and Parking Lot
- S Fern Street and Site Driveway

S Eads Street and 11th Street S/Site Driveway

The installation of signals at these intersections will provide additional signalized pedestrian crossing points which will help accommodate the additional pedestrian demand that the development will generate as well as significantly improve the pedestrian facilities near the site. Figure 35 shows the sitegenerated peak hour pedestrian volumes and Figure 36 shows the future peak hour pedestrian volumes at study area intersections. Planned and proposed pedestrian improvements are shown in Figure 37.




Figure 31: 2020 Existing Peak Hour Pedestrian Volumes




Figure 32: Pedestrian Pathways




Figure 33: Approximate Pedestrian Travel Times




Figure 34: Existing Pedestrian Facilities

PenPlace Multimodal Transportation Assessment (MMTA)




Figure 35: 2025/2031 Site-Generated Peak Hour Peak Hour Pedestrian Volumes

PenPlace Multimodal Transportation Assessment (MMTA)




Figure 36: 2025/2031 Mitigated Future Peak Hour Pedestrian Volumes




Figure 37: Planned and Proposed Pedestrian Improvements

Travel Demand Assumptions

This chapter outlines the transportation demand of the proposed PenPlace development. It reviews the expected mode splits, multimodal trip generation, and the trip distribution and routing assumptions, which forms the basis for the chapters that follow.

Mode Split Methodology

Mode split (also called mode share) is the percentage of travelers using a particular type (or mode) of transportation when traveling. The main source of mode split information for this report was based on Census data using Transportation Analysis Districts (TADs) and data contained in the State of the Commute 2016, the Crystal City Multimodal Transportation Study, the WMATA Ridership Survey, and the Arlington County Mode Share Assumptions for Pentagon City.

Office Mode Splits

Office mode splits were primarily based on Census data at the TAD level for commuters with destinations in the TAD. Figure 45 shows the TAD used in the analysis in relation to the proposed development and Figure 46 shows the origins of driving commuters with destinations in the project TAD. Table 9 summarizes the data that was used to establish the office mode split assumptions for this report. Given the low parking ratio proposed for the site compared to other sites in the area, and planned improvements to transit, bicycle, and pedestrian access in the vicinity of the site, a reduced office auto mode split was assumed for the proposed development.

Table 9: Summary of Office Mode Split Data

Information			Mod	е	
Source	SOV Carpool		Transit	Bicycle / Walk	Telecommute / Other
State of the Commute 2016 (of District employees)	38%	6%	45%	6%	5%
Crystal City Multimodal Transportation Study (Table 3.7)	39% AM / 50% PM		27%	28%	
Crystal City Multimodal Transportation Study (Figure 3.4)			46% - 50%		
WMATA Ridership Survey (Suburban Inside the Beltway)	6	6%	30%	6%	

WMATA Ridership Survey (Suburban outside the Beltway)	89%	11%	0%	
Arlington County Mode Share Assumptions for Pentagon City	30%	61%	9%	

Amenity Space Mode Splits

The amenity space component of the proposed development includes support space for the site, including the Helix building. This space will primarily be used off-peak and by office users already on-site. The Helix building will be opened to the public several weekends per month for public tours but will be closed to the public on a typical weekday. As such, amenity mode splits were primarily based on the anticipated usage on the site, as agreed upon with Arlington County staff during the scoping phase of the project.

Daycare Mode Splits

The daycare component of the proposed development is primarily intended to serve the office users of the site. Daycare mode splits were primarily based on the anticipated usage on the site, as agreed upon with Arlington County staff during the scoping phase of the project.

Neighborhood Retail Mode Splits

Neighborhood retail mode splits were primarily based on information contained in WMATA's 2005 *Development-Related Ridership Survey*. Table 10 summarizes the data that was used to establish the neighborhood retail mode split assumptions for this report.

Table 10: Summary of Neighborhood Retail Mode Split Data

Information	Mode						
Source	SOV Carpool		OV Carpool Transit Bicycle/ Walk		Telecommute/ Other		
WMATA Ridership Survey (Crystal City Shops)	:	27%	37%	36%			
WMATA Ridership Survey (Crystal Plaza Shops)	:	24%	41%	35%			

Community Space Mode Splits

Based on preliminary discussions, the community space component of the proposed development may consist of some classrooms, meetings rooms, and/or instructional space. As a

conservative measure, the same mode splits as those assigned to the daycare use were applied to the community space component, as agreed upon with Arlington County staff during the scoping phase of the project.

The site has multiple bus stops surrounding it and three (3) Metro stations near the site. It is expected that a significant portion of trips will be by Metrorail, bus, bicycle, or on foot during the morning and afternoon peak hours, rather than by personal vehicle. Based on this, the auto mode splits for the development were determined to be 30% for the office component, 30% for the amenity space component, 50% for the daycare component, 5% for the neighborhood retail component, and 50% for community space component. The proposed mode splits were vetted and approved by Arlington County and VDOT during the scoping process. Table 11 shows the mode split assumptions for the proposed development.

Table 11: Summary of Mode Split Assumptions by Land Use

Land Use		Mode						
Lanu Use	Auto	Transit	Bicycle	Walk				
Office	30%	54%	6%	10%				
Amenity	30%	54%	6%	10%				
Daycare	50%	20%	5%	25%				
Neighborhood Retail	5%	15%	5%	75%				
Community	50%	20%	5%	25%				

Trip Generation Methodology

Weekday peak hour trip generation is calculated based on the methodology outlined in the Institute of Transportation Engineers' (ITE) <u>Trip Generation</u>, 10th Edition.

Office trip generation is based on the development program of 2.8 million square feet. Office trip generation was calculated based on ITE Land Use 710 (General Office Building), using the setting/location of Center City Core, splitting trips into different modes using assumptions outlined in the mode split section of this report.

Amenity trip generation is based on the development program of 388,300 square feet. The amenity use will include support space for the site, including the Helix building, and is anticipated to generate minimal additional trips during the morning and afternoon peak hours. The amenity space will primarily be used off-peak and by off users already on-site. The Helix building will be opened to the public several days per month for public tours

but will be closed to the public on a typical weekday. Amenity office trip generation was based on ITE Land Use 580 (Museum) to be conservative, using the setting/location of General Urban/Suburban, splitting trips into different modes using assumptions outlined in the mode split section of this report.

Daycare trip generation is based on the development program of 14,500 square feet. Daycare trip generation was calculated based on ITE Land Use 565 (Day Care Center), using the setting/location of General Urban/Suburban (limited data is available for person trips), splitting trips into different modes using assumptions outlined in the mode split section of this report.

Neighborhood retail trip generation is based on the development program of 82,600 square feet of neighborhood-serving ground floor retail. Retail trip generation was calculated based on ITE's baseline vehicular trips for Land Use 820 (Shopping Center), using the setting/location of General Urban/Suburban (limited data is available for person trips), splitting trips into different modes using assumptions outlined in the mode split section of this report.

Community space trip generation is based on the development program of 27,000 square feet. Community space trip generation was calculated based on ITE Land Use 495 (Recreational Community Center), using the setting/location of General Urban/Suburban, splitting trips into different modes using assumptions outlined in the mode split section of this report.

A summary of the multi-modal trip generation for the overall development for the 2025 and 2031 horizon years is shown in Table 12 for the weekday morning and weekday afternoon peak hours. Detailed trip generation calculations are included in the Technical Appendix.

Table 12: Multi-Modal Trip Generation (2025 and 2031 Horizon Years)

Mode	Land Use	ITE	Mode	Development		AM Peak Hou	r	PM Peak Hour			
Wode	Lanu USE	Code	Split	Size	In	Out	Total	In	Out	Total	
	Office	710	30%	2,777,079 SF	635 veh/hr	94 veh/hr	729 veh/hr	108 veh/hr	565 veh/hr	673 veh/hr	
	Helix	580	30%	388,272 SF	28 veh/hr	5 veh/hr	33 veh/hr	3 veh/hr	18 veh/hr	21 veh/hr	
Auto	Daycare	565	50%	14,527 SF	43 veh/hr	37 veh/hr	80 veh/hr	38 veh/hr	43 veh/hr	81 veh/hr	
Auto	Retail	820	5%	82,608 SF	2 veh/hr	2 veh/hr	4 veh/hr	8 veh/hr	8 veh/hr	16 veh/hr	
	Community Center	495	50%	27,000 SF	16 veh/hr	8 veh/hr	24 veh/hr	15 veh/hr	16 veh/hr	31 veh/hr	
				Total	724 veh/hr	146 veh/hr	870 veh/hr	172 veh/hr	650 veh/hr	822 veh/hr	
	Office	710	54%	2,777,079 SF	1347 ppl/hr	202 ppl/hr	1549 ppl/hr	228 ppl/hr	1201 ppl/hr	1429 ppl/hr	
	Helix	580	54%	388,272 SF	85 ppl/hr	13 ppl/hr	98 ppl/hr	10 ppl/hr	53 ppl/hr	63 ppl/hr	
Transit	Daycare	565	20%	14,527 SF	31 ppl/hr	27 ppl/hr	58 ppl/hr	28 ppl/hr	31 ppl/hr	59 ppl/hr	
Transit	Retail	820	15%	82,608 SF	13 ppl/hr	8 ppl/hr	21 ppl/hr	41 ppl/hr	45 ppl/hr	86 ppl/hr	
	Community Center	495	20%	27,000 SF	13 ppl/hr	7 ppl/hr	20 ppl/hr	12 ppl/hr	14 ppl/hr	26 ppl/hr	
				Total	1489 ppl/hr	257 ppl/hr	1746 ppl/hr	319 ppl/hr	1344 ppl/hr	1663 ppl/hr	
	Office	710	6%	2,777,079 SF	150 ppl/hr	22 ppl/hr	172 ppl/hr	25 ppl/hr	134 ppl/hr	159 ppl/hr	
	Helix	580	6%	388,272 SF	9 ppl/hr	2 ppl/hr	11 ppl/hr	1 ppl/hr	6 ppl/hr	7 ppl/hr	
Bike	Daycare	565	5%	14,527 SF	8 ppl/hr	7 ppl/hr	15 ppl/hr	7 ppl/hr	8 ppl/hr	15 ppl/hr	
DIKE	Retail	820	5%	82,608 SF	4 ppl/hr	3 ppl/hr	7 ppl/hr	14 ppl/hr	15 ppl/hr	29 ppl/hr	
	Community Center	495	5%	27,000 SF	3 ppl/hr	2 ppl/hr	5 ppl/hr	3 ppl/hr	4 ppl/hr	7 ppl/hr	
				Total	174 ppl/hr	36 ppl/hr	210 ppl/hr	50 ppl/hr	167 ppl/hr	217 ppl/hr	
	Office	710	10%	2,777,079 SF	250 ppl/hr	37 ppl/hr	287 ppl/hr	42 ppl/hr	223 ppl/hr	265 ppl/hr	
	Helix	580	10%	388,272 SF	16 ppl/hr	2 ppl/hr	18 ppl/hr	2 ppl/hr	10 ppl/hr	12 ppl/hr	
Marile.	Daycare	565	25%	14,527 SF	39 ppl/hr	34 ppl/hr	73 ppl/hr	35 ppl/hr	39 ppl/hr	74 ppl/hr	
Walk	Retail	820	75%	82,608 SF	65 ppl/hr	42 ppl/hr	107 ppl/hr	206 ppl/hr	224 ppl/hr	430 ppl/hr	
	Community Center	495	25%	27,000 SF	17 ppl/hr	8 ppl/hr	25 ppl/hr	15 ppl/hr	18 ppl/hr	33 ppl/hr	
	•			Total	387 ppl/hr	123 ppl/hr	510 ppl/hr	300 ppl/hr	514 ppl/hr	814 ppl/hr	

Distribution and Assignment Methodology

Trip distribution for the proposed PenPlace development was based on:

- Census Transportation Planning Products (CTPP)
 Transportation Analysis Districts (TAD) flow data;
- The Crystal City Multimodal Transportation Study;
- Existing traffic volumes and travel patterns in the study area;
 and
- StreetLight InSight® origin and destination data.

The main source of distribution and trip assignment information for this report was based on StreetLight. StreetLight metrics that are derived from a combination of two types of locational data: navigation-GPS data and Location-Based Services (LBS) data, including historical data, with a sample size of approximately 23% of the adult population. This data is then transformed into contextualized, aggregated, and normalized travel patterns that can be used to create origin and destination analyses. Please note that the Origin-Destination (OD) analysis is based on existing travel data patterns to/from the Pentagon City area. Due to the relatively limited number of office buildings in Pentagon City, proximate office buildings in Crystal City were also used in the OD analysis, as shown in Figure 38.

Existing Local and Regional Distribution

Using StreetLight LBS data (December 2017 to November 2018), the general home location of commuters to Pentagon City and the general work locations of residents in Pentagon City were mapped. The results of the Home and Work Analysis are shown in Figure 39 and Figure 40. As can be seen, the results of the Home and Work Analysis show that the majority of trips to the Pentagon City area originate along the I-395 corridor to the southeast of Pentagon City, and that the majority of work locations for residents that live in the Pentagon City area are either in Washington, DC or the Crystal City area. The proposed development is primarily office space, so the home location of commuters that work in the Pentagon City area was deemed more relevant in determining existing travel patterns for future office employees.

The results of the Home and Work Analysis were then used to define the roadways used for trips to and from Pentagon City. Using StreetLight LBS data for an average weekday (Tuesday – Thursday), during the morning (7:00AM-9:00AM) and afternoon (4:00PM-6:00PM) peak hours, from January 2018 to November

2018, specific paths and distributions were identified for trips going to/from the Pentagon City area. Figure 41 shows the inbound distribution results for the morning and afternoon peak hours, and Figure 42 shows the outbound distribution results for the morning and afternoon peak hours.

Existing Trip Assignment

Trip assignment for proposed development was primarily determined using StreetLight InSight data. Trip assignments were based on applying middle filters between the same origin and destination pairs that were used to determine the local and regional distribution of trips, as explained above. By using middle filters, it was possible to establish the approximate number of vehicles that entered or exited the study area, what route they took, how much time each route took, and where they exited the study area or ended their trip.

Adjustments to Trip Distribution and Assignments

Trip distributions and assignments for the proposed development were adjusted for the following reasons:

- Due to the location of I-395 and Route 1 on- and offramps, the distribution results based on StreetLight data needed to be adjusted to account for the location of the proposed development in relation to the location of the existing office buildings that the OD analysis is based on.
- Due to the proximity of the Pentagon Transit Center, trip distribution and assignments were adjusted to account for data skew that is most likely a result of many devices being captured going to and from the Pentagon Transit Center on S Eads Street, north of I-395.
- Improvements to the Boundary Channel Interchange will increase the number of vehicles that choose to travel to/from the proposed development via Long Bridge Drive.
- 4. Based on the I-395 Express Lanes Extension IMR, the extension of the express/HOT lanes to S Eads Street will increase the number of vehicles that use the HOVonly lanes. Reversible lanes will also alter existing travel patterns in the area.

Based on the methodology outlined above, Figure 43 shows the inbound distribution results for the morning and afternoon peak hours, and Figure 44 shows the outbound distribution results for the morning and afternoon peak hours.




Figure 38: Origin-Destination Zones Used in StreetLight InSight Analysis




Figure 39: Home Locations of Commuters to Pentagon City




Figure 40: Work Locations of Commuters from Pentagon City



Figure 41: Inbound Distribution StreetLight InSight Results



Figure 42: Outbound Distribution Streetlight InSight Results




Figure 43: Inbound Trip Distribution




Figure 44: Outbound Trip Distribution




Figure 45: Transportation Analysis District (TAD) in Study Area




Figure 46: Origins of Driving Commuters with Destinations in project TAD

Traffic Operations

This chapter provides a summary of an analysis of the existing and future roadway capacity in the study area for the 2025 and 2031 horizon years with and without the PenPlace development. Included is a VISSIM analysis of potential vehicular impacts of the proposed development and a discussion of potential improvements.

Compared to typical macroscopic analysis tools, such as Synchro, VISSIM is a microsimulation modelling tool that measures the performance of individual vehicles as they travel through the network while accounting for the influence of other vehicles, transit, pedestrians, and cyclists. Given the multimodal nature of Pentagon City and planned improvements, particularly streets directly adjacent to the site where a cycle track, protected bicycle lanes, and dedicated transit lanes will be in place, VISSIM was determined to be the appropriate analysis tool for this development as agreed upon during the scoping process.

The purpose of the capacity analysis is to:

- Determine the existing capacity of the study area roadways;
- Determine the overall impact of the proposed development on the study area roadways; and
- Discuss potential improvements and mitigation measures to accommodate the additional vehicular trips.

The capacity analysis focuses on the morning and afternoon commuter peak hours, as determined by the existing traffic volumes in the study area.

The following conclusions are reached with this chapter:

- The recommended mitigations will create additional capacity at critical locations to allow more vehicles to be processed through the analyzed network. In 2025, with the recommended mitigations, the total number of vehicles processed increases by +6.85% in the morning peak period and +6.76% in the afternoon peak period. In 2031, with the recommended mitigations, the total number of vehicles processed increases by +4.96% in the morning peak period and +3.51% in the afternoon peak period.
- The GEH statistic is a formula used in traffic modeling to compare two sets of traffic volumes and indicate whether the model processes enough vehicles in the network to be considered valid. Under the 2025 Mitigated Future scenario, all movements operate at acceptable GEH values (GEH value < 5). Under the 2031 Mitigated Future scenario, most movements operate at acceptable GEH values (GEH value)</p>

- < 5); however, the three (3) intersections along 15th Street S, at S Eads Street, S Elm Street, and S Fern Street, have one or more movements that operate above the acceptable GEH value (GEH > 5) in the afternoon peak hour. This is primarily due to vehicles being metered by the new at-grade Richmond Highway and 15th Street S intersection which experiences congestion.
- Travel times for vehicles were modeled along Army Navy
 Drive and for transit vehicles along 12th Street S. The
 mitigation measures identified decreased travel times during
 some study periods or locations and travel times increased
 in others. Simulation results indicated that increase in travel
 time between 2025/2031 Background and 2025/2031
 Mitigated Future scenarios remains below 60 seconds for
 both peak hours.
- The bicycle and pedestrian delay results under the 2025
 Mitigated Future scenario, with added site traffic and recommended mitigation measures, are comparable to that under the 2025 Background scenario.
- In completing the VISSIM analysis, several overall trends regarding existing and expected future travel patterns in the study area during the morning and afternoon peak hours were identified. Most vehicular capacity concerns in the study area can be alleviated through signal timing changes that adapt to changes in volume patterns, but at some locations, operational changes alone cannot mitigate future delays. Army Navy Drive and S Eads Street are heavily traveled corridors, and it is likely that drivers will alter their patterns and mode choices as future conditions change. However, this report does recommend that a number of intersections within the study area be improved with either signal timing adjustments, modifications to signal phasing, restriping, or new traffic signals.
- Potential mitigation measures were explored at study intersections and included the following recommendations for both 2025 and 2031 Mitigated Future Conditions (detailed in Table 1 and Figure 1):
 - Adjustments to signal timings at nine (9) intersections
 - Modifications to signal phasing and adjustments to signal timings at seven (7) intersections
 - Signal modifications at seven (7) intersections
 - o Re-striping at eight (8) intersections
 - Relocating one (1) existing bus stop along S Eads Street
 - Adding new signals at three (3) intersections, including Army Navy Drive/Parking Lot/Site Driveway, S Eads

- Street/11th Street S/Site Driveway, and S Fern Street/Site Driveway
- Providing a protected southbound bike lane along S
 Eads Street between Army Navy Drive and 12th Street

 S, a northbound protected bike lane along S Fern Street
 between Army Navy Drive and 12th Street S, and a
 southbound bike lane along S Fern Street between

 Army Navy Drive and 11th Street S/Site Driveway
- With the recommended mitigations in place, the VISSIM analysis shows that traffic operations with the proposed development are consistent with the 2025 and 2031
 Background scenario at many intersections. Nevertheless, as can be expected of urban infill there are still certain locations that are projected to experience delay and queuing issues where traffic is concentrated, especially along Army Navy Drive and S Eads Street which funnel traffic to/from I-395.

Study Area, Scope, & Methodology

This section outlines the assumptions used to develop the existing and future roadway capacity analysis, including volumes, roadway geometries, and traffic operations. The scope of the analysis contained within this report was extensively discussed with and approved by Arlington County and VDOT staff. The general methodology follows national, Arlington County, and VDOT guidelines on the preparation of transportation impact evaluations of site development.

Capacity Analysis Scenarios

The vehicular capacity analyses are performed to determine if the proposed development will lead to adverse impacts on traffic operations. This will be accomplished by comparing future scenarios: (1) without the proposed development (referred to as the Background conditions) and (2) with the development approved and constructed (including any mitigation measures, referred to as the Future conditions).

Specifically, this chapter examined the following analysis scenario:

- 1. 2020 Existing Conditions
- 2. 2025 Future Conditions without the development (2025 Background)

- 3. 2025 Mitigated Future Conditions with the development (2025 Mitigated Future)
- 4. 2031 Future Conditions without the development (2031 Background)
- 5. 2031 Mitigated Future Conditions with the development (2031 Mitigated Future)

Study Area

The study area of the analysis is a set of intersections where detailed capacity analyses are performed for the scenarios listed above. The set of intersections included are those intersections most likely to have potential impacts or require changes to traffic operations to accommodate the proposed development.

Based on the projected future trip generation and the location of the site access points, as agreed to in this report's scoping agreement, the following intersections were chosen for analysis:

- 1. Army Navy Drive and S Hayes Street/I-395 Ramp
- 2. Army Navy Drive and S Fern Street
- 3. Amy Navy Drive and Parking Lot
- 4. Army Navy Drive and S Eads Street
- 5. Army Navy Drive and VA 110 Off-Ramp
- 6. 11th Street S and S Eads Street
- 7. 12th Street S and S Hayes Street
- 8. 12th Street S and S Fern Street
- 9. 12th Street S and S Elm Street
- 10. 12th Street S and S Eads Street
- 11. 12th Street S and Army Navy Drive
- 12. 12th Street S and Long Bridge Drive/S Clark Street
- 13. 13th Street S and S Fern Street
- 14. 13th Street S and S Eads Street
- 15. 14th Street S and S Fern Street
- 16. 15th Street S and S Fern Street
- 17. 15th Street and S Elm Street
- 18. 15th Street S and S Eads Street
- 19. S Eads Street and I-395 HOT Lanes (South Node)
- 20. S Eads Street and I-395 HOT Lanes (North Node)
- 21. 14th Street S and S Eads Street (Planned)
- 22. S Fern Street and Site Driveway (Planned)

Figure 9 shows the vehicular study area intersections. Roadway characteristics, including classification, number of lanes, speed limit, the presence of on-street parking, and average daily traffic volumes (ADT) are outlined in Table 13.

Table 13: Existing Roadway Network

Classification*	Lanes	Speed	On-Street Parking	ADT**
Minor Arterial (VDOT)	6	20 mnh	Vac	11 000
Arterial Type B (Arlington)	О	so mpn	res	11,000
Major Collector (VDOT)	2-3	30 mph	Voc	7,300
Arterial Type B (Arlington)	2-3	30 mpn	1 62	7,300
Major Collector (VDOT)	2.4	25 mph	Voc	5 900
Arterial Type B (Arlington)	Z -4	25 mpn	162	5,800
Major Collector (VDOT)				
East of Eads – Arterial Type B (Arlington)	2	25 mph	Yes	6,100
West of Eads - Non-Arterial; Urban Center				
Minor Arterial (VDOT)				
West of Fern, East of Eads – Arterial Type A	2-3	30 mph	Yes	12,000
East of Hayes, West of Eads – Arterial Type B				
Major Collector (VDOT)	4.5	05h	V	7.000
Arterial Type B (Arlington)	4-5	35 mph	Yes	7,800
	Minor Arterial (VDOT) Arterial Type B (Arlington) Major Collector (VDOT) Arterial Type B (Arlington) Major Collector (VDOT) Arterial Type B (Arlington) Major Collector (VDOT) East of Eads – Arterial Type B (Arlington) West of Eads – Non-Arterial; Urban Center Minor Arterial (VDOT) West of Fern, East of Eads – Arterial Type A East of Hayes, West of Eads – Arterial Type B Major Collector (VDOT)	Classification* Minor Arterial (VDOT) Arterial Type B (Arlington) Major Collector (VDOT) East of Eads – Arterial Type B (Arlington) West of Eads – Non-Arterial; Urban Center Minor Arterial (VDOT) West of Fern, East of Eads – Arterial Type A East of Hayes, West of Eads – Arterial Type B Major Collector (VDOT) 4-5	Classification*LanesSpeedMinor Arterial (VDOT) Arterial Type B (Arlington)630 mphMajor Collector (VDOT) Arterial Type B (Arlington)2-330 mphMajor Collector (VDOT) Arterial Type B (Arlington)2-425 mphMajor Collector (VDOT) East of Eads – Arterial Type B (Arlington)225 mphWest of Eads – Non-Arterial; Urban CenterMinor Arterial (VDOT)2-330 mphWest of Fern, East of Eads – Arterial Type A East of Hayes, West of Eads – Arterial Type B2-330 mph	Classification* Lanes Speed On-Street Parking Minor Arterial (VDOT) Arterial Type B (Arlington) Major Collector (VDOT) East of Eads – Arterial Type B (Arlington) West of Eads – Non-Arterial; Urban Center Minor Arterial (VDOT) West of Fern, East of Eads – Arterial Type A East of Hayes, West of Eads – Arterial Type B Major Collector (VDOT) Major Collector (VDOT) West of Fern, East of Eads – Arterial Type B Major Collector (VDOT) 4-5 35 mph Yes

^{*}From VDOT and Arlington GIS ** VDOT ADT Data from 2019

Traffic Volume Assumptions

The following section reviews the traffic volume assumptions and methodologies used in the roadway capacity analyses.

Existing Traffic Volumes

The existing traffic volumes are comprised of turning movement count data, provided by Arlington County, which was collected in 2019 and early 2020. Existing volumes were balanced where appropriate. The existing turning movement counts, without volume balancing, are included in the Technical Appendix.

The existing peak hour traffic volumes for intersections within the vehicular study area are shown in Figure 47.

2025 Traffic Volumes

2025 Background Traffic Volumes (without the proposed development)

Traffic projections for the 2025 Background Conditions consist of the existing volumes with the addition of growth along local roadways in the study area in 2025. This local growth is accounted for by traffic generated by developments expected to be completed prior to the 2025 horizon year (known as background developments).

Background Developments (2025)

Following industry methodologies, a background development must meet the following criteria to be incorporated into the analysis:

- Be located in the study area, defined as having an origin or destination point within the cluster of study area intersections;
- Have entitlements; and
- Have a construction completion date prior or close to the proposed development.

Based on these criteria, 10 developments were included in the 2025 Background Conditions scenario. These developments are:

- 1. Crystal Drive Central District Retail
- 2. 1770 Crystal Drive Office
- 3. Century Center
- 4. 1900 S Eads (Crystal House)
- 5. The Altaire (400 Army Navy Drive)
- 6. 241 18th Street S Office
- 7. 1800 S Bell Street
- 8. Verizon Site
- 9. Metropolitan Park 6, 7, and 8

10. 1900 Crystal Drive

As part of the scoping process with Arlington County staff, Pentagon Centre (Phase I) was also identified as a background development for the 2025 Background Conditions scenario. However, at the direction of staff, no further development of the Pentagon Centre project should be accounted for in 2025 than what is already included in existing conditions.

The location of the background developments included in the 2025 Background Conditions scenario in relation to the proposed PenPlace development is shown on Figure 48. Transportation studies were available for the majority of the background developments included in the 2025 Background Condition. Details on each of the background developments included in the 2025 Background Conditions are presented below:

- 1. Crystal Drive Central District Retail: Located in the Crystal City area and bounded by 15th Street S to north, 18th Street S to the south, S Bell Street to the west, and Crystal Drive to the east, the approved Crystal Drive Central District Retail development will improve upon the existing site with the addition of approximately 5,200 square feet of office space, 10,300 square feet of retail, 17,500 square feet of grocery, and a movie theatre with approximately 940 seats. The retail portion will be spread throughout the block, including a new two-story building at the corner of 18th Street and Crystal Drive, and an expansion to 1550 Crystal Drive to accommodate the proposed grocery. The expected build out year is 2020. The development is expected to generate 56 net weekday AM peak hour vehicle trips and 322 net weekday PM peak hour vehicle trips based on the Traffic Impact Study prepared by Gorove Slade Associates dated October 13, 2017.
- 2. 1770 Crystal Drive Office: Located in the Crystal City area on the northwest corner of the intersection of 18th Street S and Crystal Drive, the existing 272,000 square foot office building was vacant when turning movement counts were collected. As such, vehicular trips were added to the network to account for the 1770 Crystal Drive Office site being vacant when turning movement counts were collected. To determine the number of trips generated by the vacant office space, ITE's Trip Generation, 10th Edition was used, with mode splits based on nearby developments that have recently been studied. During the AM peak hour 86 vehicle trips were added to the network and during the weekday PM peak hour 86 vehicle trips were added to the network.

- 3. Century Center: Located in the Crystal City area at the southwest corner of the intersection of Crystal Drive and 23rd Street S, the approved Century Center development will maintain the existing parking garage and retail on site and redevelop the existing office space with a new residential tower containing approximately 300 dwelling units. The expected build out year was initially projected to occur in 2019; however, construction has not yet begun. The Century Center development is expected to generate 53 weekday AM peak hour vehicle trips and 64 weekday PM peak hour vehicle trips based on the Traffic Impact Study prepared by Gorove Slade Associates dated January 10, 2017.
- 4. 1900 S Eads (Crystal House): Located in the Pentagon City area and bounded by 18th Street S to the north, S Eads Street to the east, 22nd Street S to the south, and S Fern Street to the west, the approved Crystal House development will raze a portion of an existing parking lot and redeveloped it with 798 residential dwelling units. The expected build-out year is 2026; however it was included as a background development in the 2025 Background Conditions as a conservative measure. The Crystal House development is expected to generate 130 weekday AM peak hour vehicle trips and 153 weekday PM peak hour vehicle trips based on the Traffic Impact Analysis prepared by Wells & Associates dated October 19, 2018.
- The Altaire (400 Army Navy Drive): Located in the Pentagon City area at the southeast corner of the Army Navy Drive and S Eads Street intersection, the approved Altaire development replaced a 235,000 square foot office building with a residential building containing approximately 452 dwelling units. Construction of the project was completed in October of 2018; however, at the time turning movement counts were collected, the Altaire was approximately 70% occupied. As such, additional vehicular trips were added to the network compensate for the Altaire being only 70% occupied. During the AM peak hour 27 vehicle trips were added to the network and during the weekday PM peak hour 32 vehicle trips were added to the network based on the Traffic Impact Study prepared by Gorove Slade Associates dated June 11, 2013.
- 6. 241 18th Street S Office: Located in the Crystal City area near the northwest corner of the intersection of 18th Street S and Crystal Drive, the existing 330,700 square foot office building was 62% vacant when turning movement counts were collected. As such, vehicular trips were added to the network to account for the 241 18th Street S site being 62% vacant when turning movement counts

- were collected. To determine the number of trips generated by the vacant office space, ITE's <u>Trip</u> <u>Generation</u>, 10th Edition was used, with mode splits based on nearby developments that have recently been studied. During the AM peak hour 48 vehicle trips were added to the network and during the weekday PM peak hour 53 vehicle trips were added to the network.
- 7. 1800 S Bell Street: Located in the Crystal City area on the southwest corner of the intersection of S Bell Street and 18th Street S, the existing 221,000 square feet office building was only 20% occupied when turning movement counts were collected. As such, vehicular trips were added to the network to account for the 1800 S Bell Street building being mostly vacant. To determine the number of trips generated by the vacant office space, ITE's <u>Trip Generation</u>, 10th Edition was used, with mode splits based on nearby developments that have recently been studied. During the AM peak hour 61 vehicle trips were added to the network and during the weekday PM peak hour 64 vehicle trips were added to the network.
- 8. Verizon Site: Located in the Crystal City area and bounded by S Eads Street to the west, 11th Street S to the north, existing office and residential buildings to the east, and 12th Street S to the south, the approved Verizon Site development will raze the existing telecommunications facility and redevelop to include one mixed-use building with approximately 306 dwelling units and 10,908 square feet of neighborhood-serving ground floor retail. The expected build out year is 2022. The development is expected to generate 42 net weekday AM peak hour vehicle trips and 40 net weekday PM peak hour vehicle trips based on the Traffic Impact Study prepared by Gorove Slade Associates dated July 19, 2019.
- 9. Metropolitan Park 6, 7, 8: Located in the Pentagon City area and bounded by 13th Street S to north, 15th Street S to the south, S Elm Street to the west, and S Eads Street to the east, the approved Metropolitan Park 6, 7, 8 development will raze the existing warehouse space and redevelop to include two buildings with approximately 2.1 million square feet of office space and 55,000 square feet of neighborhood-serving ground floor retail. The expected build out year is 2021. The development is expected to generate 558 net weekday AM peak hour vehicle trips and 524 net weekday PM peak hour vehicle trips based on the Traffic Impact Study prepared by Gorove Slade Associates dated October 22, 2019.
- 1900 Crystal Drive: Located in the Crystal City area and bounded by 18th Street S to north, 20th Street S to the south, S Bell Street to the west, and Crystal Drive to the

east, the approved 1900 Crystal Drive development will raze the existing vacant office building and redevelop to include two residential buildings with approximately 790 residential units and 40,598 square feet of neighborhoodserving ground floor retail. The expected build out year is 2023. The development is expected to generate 109 net weekday AM peak hour vehicle trips and 137 net weekday PM peak hour vehicle trips based on the Traffic Impact Study prepared by Gorove Slade Associates dated March 15, 2019.

The total traffic generated by the background developments in 2025 is shown in Table 14. Trips generated by the approved background developments in 2025 are included in the Technical

Appendix. The traffic volumes generated by background developments along the network were added to the existing traffic volumes in order to establish the 2025 Background traffic volumes. Trip distribution assumptions for the background developments were based on the distributions included in their respective studies or based on those determined for the proposed PenPlace development and altered where necessary based on anticipated travel patterns. The peak hour traffic volumes generated by background developments is provided in Figure 49. The traffic volumes for the 2025 Background conditions are shown on Figure 50.

			Trip Gen	eration		
Development	AM Peak Hour			PM Peak Hour		
	In	Out	Total	In	Out	Total
Crystal Drive Central District Retail (1)						
Total New Vehicle-Trips	36	20	56	118	204	322
1770 Crystal Drive Office/241 S 18th Street Office (2)						
Total New Vehicle Trips	117	17	134	22	117	139
Century Center (3)						
Total New Vehicle-Trips	10	43	53	42	22	64
1900 S Eads (Crystal House) (4)						
Total New Vehicle-Trips	37	93	130	92	61	153
The Altaire (400 Army Navy Drive) (5)						
Total New Vehicle Trips	5	22	27	21	11	32
1800 S Bell Street (6)						
Total New Vehicle Trips	53	8	61	10	54	64
Verizon Site (7)						
Total New Vehicle Trips	12	30	42	23	17	40
Metropolitan Park 6, 7, 8 (8)						
Total New Vehicle Trips	485	73	558	87	437	524
1900 Crystal Drive (9)						
Total New Vehicle Trips	31	78	109	75	62	137
Total Background Trips	786	384	1,170	490	985	1,475

- (1): Extracted from Central District Retail Phase I & 1770 Crystal Drive Residential TIS (10.13.2017) prepared by Gorove Slade
- (2): 241 18th Street is 77% occupied and 1770 is currently empty and both will be 100% occupied by 2023. Trip Generation was performed to determine the number of trips that will be generated when the offices are fully occupied.
- (3): Extracted from Century Center TIS (01.10.2017) prepared by Gorove Slade Associates.
- (4): Extracted from Crystal House III TIA (05.24.2017) prepared by Wells + Associates.
- (5): Extracted from 400 Army Navy Drive TIS (06.11.2013) prepared by Gorove Slade Associates. Building assumed 25% occupied at the time of data collection.
- (6): The office building is currently 42% occupied and will be 100% occupied by 2023. Trip Generation was performed to determine the number of trips that will be generated when the offices are fully occupied.
- (7): Extracted from Verizon Site MMTA (07.19.2019) prepared by Gorove Slade Associates.
- (8): Extracted from Metropolitan Park 6, 7, 8 MMTA (10.22.2019) prepared by Gorove Slade Associates.
- (9): Extracted from 1900 Crystal Drive MMTA (03.15.2019) prepared by Gorove Slade Associates.

2025 Mitigated Future Traffic Volumes (with the proposed development)

The 2025 Mitigated Future Conditions traffic volumes consist of the 2025 Background volumes with the addition of the traffic volumes generated by the proposed development (sitegenerated trips), shown in Table 12. Thus, the 2025 Mitigated Future Conditions traffic volumes include traffic generated by: the existing volumes, background developments, and the proposed development.

During the afternoon peak hour, approximately 85% of existing northbound left-turn trips at the Army Navy Drive and S Eads Street intersection were re-routed to reflect more natural travel patterns in the future, given increased demands for capacity along S Eads Street as a result of planned developments, and to increase the accuracy of the VISSIM model. Based on a review of the transportation analysis prepared for the Pentagon City Plan, re-routes were also considered at this location. No additional re-routes were assumed during the morning peak hour. These trips were re-routed to turn left at intersections further south on S Eads Street (i.e., 15th Street S and 18th Street S) toward S Hayes Street where there is available capacity. The number of trips shifted to utilize 12th Street S was minimized since the transitway will be running east-west along that corridor in the future. While not included as reported study intersections, the impacts of this shift in volumes along 18th Street and at the intersection of 15th Street S and S Hayes Street are captured in the VISSIM model. Of note, the westbound right-turn at the 15th Street S and S Hayes Street intersection increases by approximately 35% and the northbound thru at the 15th Street S and S Hayes Street intersection increases by approximately 21%. A diagram of the re-routed peak hour volumes is included in the Technical Appendix.

Trip distribution and assignments for site-generated traffic was primarily determined using StreetLight InSight® data and observations, as detailed in the Travel Demand Assumptions chapter of this report. The origin of outbound and destination of inbound vehicular trips were the access points to the belowgrade parking garage on Army Navy Drive, S Eads Street, and S Fern Street. A summary of trip distribution assumptions is shown on Figure 43 for the inbound distribution assumptions and on Figure 44 for the outbound distribution assumptions. Trip distribution and assignment assumptions were vetted and approved by Arlington County and VDOT.

Based on the trip distribution and assignment assumptions, sitegenerated trips were distributed though the study area intersections. The site-generated traffic volumes for the 2025 horizon year are shown on Figure 51. The 2025 Mitigated Future Conditions traffic volumes, which are comprised of existing volumes, background developments, and the proposed development are shown on Figure 52.

2031 Traffic Volumes

Route 1 Multimodal Improvements Study

The methodology for establishing the 2031 traffic volumes used in the capacity analysis are similar to those used for the 2025 horizon year; however, the recommendations of the Route 1 Multimodal Improvements Study would alter existing and future traffic patterns. The study proposes to bring Route 1 down to grade at the existing grade-separated intersections of 15th Street S and 18th Street S to create an urban boulevard through Pentagon City and Crystal City.

The Richmond Highway and 15th Street S intersection is not included as a study intersection, as agreed upon during the scoping process; however, it is expected that site-generated trips will utilize this intersection to access Richmond Highway.

Assumptions for re-routing volumes were generally consistent with that assumed in the Route 1 Multimodal Improvements
Study (Phase 1), published by VDOT in October 2021. As such, a portion of left- and right-turning volumes at 15th Street S and 20th Street S were re-routed to use the new at-grade 18th Street S intersection and S Eads Street, with the exception of left-turns at 18th Street S where no left-turns are permitted as part of the recommended at-grade concept identified by VDOT. To be conservative and consistent with the assumptions from the Route 1 Multimodal Improvements Study, vehicular traffic forecasts for background developments and site trips remain consistent with that assumed in 2025 scenarios.

Diagrams showing how existing trips were re-routed at intersections most likely to be affected by the recommendations of the Route 1 Multimodal Improvements Study project are included in the Technical Appendix.

Converting Richmond Highway to an at-grade urban boulevard will balance the needs of multimodal connectivity and vehicular capacity. Richmond Highway is a heavily trafficked corridor under existing conditions. Based on the findings of Phase 1 of the Route 1 Multimodal Improvements Study, increased congestion is expected with the project. Phase 2 of the Route 1

Multimodal Improvements Study is anticipated to include the development of a comprehensive TDM strategy. This TDM strategy will aim to reduce future traffic volumes below existing levels, mitigate future congestion, and discuss potential traffic diversion.

2031 Background Traffic Volumes (<u>without</u> the proposed development)

Traffic projections for the 2031 Background Conditions consist of the existing volumes with the addition of growth along local roadways in the study area in 2031. This local growth is accounted for by traffic generated by developments expected to be completed prior to the 2031 horizon year (known as background developments).

Background Developments (2031)

Following industry methodologies, a background development must meet the following criteria to be incorporated into the analysis:

- Be located in the study area, defined as having an origin or destination point within the cluster of study area intersections;
- · Have entitlements; and
- Have a construction completion date prior or close to the proposed development.

Based on these criteria, 10 developments were included in the 2031 Background Conditions scenario. These developments are:

- 1. Crystal Drive Central District Retail
- 2. 1770 Crystal Drive Office
- Century Center
- 4. 1900 S Eads (Crystal House)
- 5. The Altaire (400 Army Navy Drive)
- 6. 241 18th Street S Office
- 7. 1800 S Bell Street
- 8. Verizon Site
- 9. Metropolitan Park 6, 7, and 8
- 10. 1900 Crystal Drive

The location of the background developments included in the 2031 Background Conditions scenario in relation to the proposed PenPlace development is shown on Figure 48. All of the background developments included in the 2031 Background Conditions were included in the 2025 Background Conditions and are detailed in that section. The total traffic generated by the background developments in 2031 is shown in Table 15.

Trips generated by the approved background developments are included in the Technical Appendix. The traffic volumes generated by background developments and by regional growth along the network were added to the existing traffic volumes in order to establish the 2031 Background traffic volumes. The peak hour traffic volumes generated by background developments is provided in Figure 53. The traffic volumes for the 2031 Background conditions are shown on Figure 54.

Table 15: Traffic Generated by 2031 Background Developments

			Trip Gen	eration		
Development		AM Peak Hour		PM Po		
	In	Out	Total	In	Out	Total
Crystal Drive Central District Retail (1)						
Total New Vehicle-Trips	36	20	56	118	204	322
1770 Crystal Drive Office/241 S 18th Street Office (2)						
Total New Vehicle Trips	117	17	134	22	117	139
Century Center (3)						
Total New Vehicle-Trips	10	43	53	42	22	64
1900 S Eads (Crystal House) (4)						
Total New Vehicle-Trips	37	93	130	92	61	153
The Altaire (400 Army Navy Drive) (5)						
Total New Vehicle Trips	5	22	27	21	11	32
1800 S Bell Street (6)						
Total New Vehicle Trips	53	8	61	10	54	64
Verizon Site (7)						
Total New Vehicle Trips	12	30	42	23	17	40
Metropolitan Park 6, 7, 8 (8)						
Total New Vehicle Trips	485	73	558	87	437	524
1900 Crystal Drive (9)						
Total New Vehicle Trips	31	78	109	75	62	137
Total Background Trips	786	384	1,170	490	985	1,475

^{(1):} Extracted from Central District Retail Phase I & 1770 Crystal Drive Residential TIS (10.13.2017) prepared by Gorove Slade Associates.

^{(2): 241 18&}lt;sup>th</sup> Street is 77% occupied and 1770 is currently empty and both will be 100% occupied by 2023. Trip Generation was performed to determine the number of trips that will be generated when the offices are fully occupied.

^{(3):} Extracted from Century Center TIS (01.10.2017) prepared by Gorove Slade Associates.

^{(4):} Extracted from Crystal House III TIA (05.24.2017) prepared by Wells + Associates.

^{(5):} Extracted from 400 Army Navy Drive TIS (06.11.2013) prepared by Gorove Slade Associates. Building assumed 25% occupied at the time of data collection.

^{(6):} The office building is currently 42% occupied and will be 100% occupied by 2023. Trip Generation was performed to determine the number of trips that will be generated when the offices are fully occupied.

^{(7):} Extracted from Verizon Site MMTA (07.19.2019) prepared by Gorove Slade Associates.

^{(8):} Extracted from Metropolitan Park 6, 7, 8 MMTA (10.22.2019) prepared by Gorove Slade Associates.

^{(9):} Extracted from 1900 Crystal Drive MMTA (03.15.2019) prepared by Gorove Slade Associates.

2031 Mitigated Future Traffic Volumes (with the proposed development)

The 2031 Mitigated Future Conditions traffic volumes consist of the 2031 Background volumes with the addition of the traffic volumes generated by the proposed development (sitegenerated trips), shown in Table 12. Thus, the 2031 Mitigated Future Conditions traffic volumes include traffic generated by: the existing volumes, background developments, and the proposed development. During the afternoon peak hour, approximately 85% of existing northbound left-turn trips at the Army Navy Drive and S Eads Street intersection was re-routed to reflect more natural travel patterns in the future, given increased demands for capacity along S Eads Street as a result of planned developments, and increase the accuracy of the VISSIM model. No additional re-routes were assumed during the morning peak hour. The re-routed trips were re-routed to the turn left at intersections further south on S Eads Street (i.e., 15th Street S and 18th Street S) to S Hayes Street where there is available capacity. The number of trips shifted to utilize 12th Street S was minimized since the transitway will be running east-west along that corridor in the future. While not included as study intersections where results are reported, the impacts of this shift in volumes are captured in the VISSIM model. Of note, the westbound right-turn at the 15th Street S and S Hayes Street intersection increases by approximately 35% and the northbound thru at the 15th Street S and S Hayes Street intersection increases by approximately 21%. With this re-route, the difference in delay for the westbound right-turn at the S Hayes Street and 15th Street S intersection is marginal (an increase from 25.8 sec/veh to 32.2 sec/veh) and conditions are considered acceptable with additional capacity available for the movement. The maximum queue length is comparable to Background conditions. A diagram of the re-routed peak hour volumes is included in the Technical Appendix.

Trip distribution and assignments for site-generated traffic was primarily determined using StreetLight InSight® data and observations, as detailed in the Travel Demand Assumptions chapter of this report. The origin of outbound and destination of inbound vehicular trips were the access points to the belowgrade parking garage on Army Navy Drive, S Eads Street, and S Fern Street. A summary of trip distribution assumptions is shown on Figure 43 for the inbound distribution assumptions. Trip distribution and assignment assumptions were vetted and approved by Arlington County and VDOT.

Based on the trip distribution and assignment assumptions, sitegenerated trips were distributed though the study area intersections. The site-generated traffic volumes for the 2031 horizon year are shown on Figure 55. The 2031 Mitigated Future Conditions traffic volumes, which are comprised of existing volumes, background developments, and the proposed development are shown on Figure 56.




Figure 47: 2020 Existing Peak Hour Traffic Volumes (Balanced)




Figure 48: Future Background Developments




Figure 49: 2025 Background Development Peak Hour Traffic Volumes




Figure 50: 2025 Background Peak Hour Traffic Volumes (without the proposed development)




Figure 51: 2025 Site-Generated Peak Hour Traffic Volumes




Figure 52: 2025 Mitigated Future Peak Hour Traffic Volumes (with the proposed development)




Figure 53: 2031 Background Development Peak Hour Traffic Volumes




Figure 54: 2031 Background Peak Hour Traffic Volumes (without the proposed development)




Figure 55: 2031 Site-Generated Peak Hour Traffic Volumes




Figure 56: 2031 Mitigated Future Peak Hour Traffic Volumes (with the proposed development)

Geometry and Operations Assumptions

The following section reviews the roadway geometry and operations assumptions made and the methodologies used in the 2025 and 2031 horizon years.

2020 Existing Geometry and Operations Assumptions

The geometry and operations assumed in the existing conditions scenario are those present when the main data collection occurred. Gorove Slade made observations and confirmed the existing lane configurations and traffic controls at the intersections within the study area. Existing signal timings and offsets were obtained from Arlington County and confirmed during field reconnaissance.

A description of the roadways within the study area is presented below in Table 13. The existing local roadway network including lane configurations and intersection control is detailed in and illustrated in Figure 57.

2025 Background Geometry and Operations Assumptions (without the proposed development)

Following industry standard methodologies, a background improvement must meet the following criteria to be incorporated into the analysis:

- Be funded: and
- Have a construction completion date prior or close to the proposed development.

Based on these criteria, a number of geometry and operations improvements were included in the 2025 Background scenario. Roadway improvements that are part of the Army Navy Drive Complete Street, 12th Street Complete Street, Crystal City Transitway Extension, and Metropolitan Park 6, 7, and 8 projects were incorporated into the 2025 Background Conditions scenario.

Roadway improvements along 12th Street S are based on the Transitway Extension to Pentagon City provided by Arlington County. The section of 12th Street S is planned to include exclusive center transit lanes as part of the extension of the Crystal City/Potomac Yard Transitway. At the time of scoping, signal phasing was understudy as part of a dedicated transitway study effort, led by Arlington County, and is set to be finalized. As such, signal timings, phasing, and lane configuration assumptions were based on the signal timings and phasing included in the 2025 No-Build VISSIM files provided by the

County and discussions with County staff and lane configurations included in the Transitway Extension to Pentagon City plans provided by the County.

Army Navy Drive Complete Street

The Army Navy Drive Complete Street project includes the following changes to roadway geometry and operations to Army Navy Drive from S Hayes Street to 12th Street S:

- The reconfiguration of the Army Navy Drive and S Hayes Street intersection to convert:
 - The eastbound approach from one left-turn lane, two thru lanes, and one thru/right lane to one left-turn lane, two thru lanes, and one right-turn lane; and
 - The westbound approach from one left-turn lane, two thru lanes, and one thru/right lane to one left-turn lane, two thru lanes, and one right-turn lane.
 - Crosswalks are added across the eastbound and southbound approaches.
 - Signal timing and phasing modifications to incorporate an eastbound protected right-turn phase to minimize conflicts with the cycle track along the south side of Army Navy Drive.
- 2. The reconfiguration of the Army Navy Drive and S Fern Street intersection to include:
 - The conversion of the westbound approach from one left/thru lane, one thru lane, and one thru/right lane to one left-turn lane, one thru lane, and one thru/right lane.
 - Signal timing and phasing modifications to incorporate a new westbound left-turn permissiveprotected phase.
 - Signal timing and phasing modifications to incorporate an eastbound right-turn flashing yellow arrow phase to minimize conflicts with the cycle track along the south side of Army Navy Drive.

A portion of existing eastbound right-turning vehicles were re-routed to utilize available capacity along S Hayes Street in the morning and afternoon peak hours to adjust for the reduced capacity along Army Navy Drive. Approximately 30% of trips were re-routed in the morning peak hour and approximately 20% of trips were re-routed in the afternoon peak hour. It is anticipated that this shift in volumes will reflect more natural travel patterns in the future and increase the accuracy of the VISSIM model. A

diagram of the re-routed existing volumes is included in the Technical Appendix.

- 3. The reconfiguration of the Army Navy Drive and Parking Lot intersection to convert:
 - The eastbound approach from one left/thru lane and one thru lane to one left/thru lane and two thru lanes;
 and
 - The westbound approach from two thru lanes and one thru/right lane to one thru lane and one thru/right lane.
- 4. The reconfiguration of the Army Navy Drive and S Eads Street intersection to include:
 - The conversion of the eastbound approach from one left/thru lane and one thru/right lane to one left-turn lane, one thru lane, and one right-turn lane; and
 - The conversion of the westbound approach from one left/thru lane, one thru lane, and one thru/right lane to two thru lanes and one right-turn lane.
 - Signal timings and phasing were modified to incorporate a new southbound left-turn permissiveprotected phase.
 - Signal timing and phasing modifications to incorporate an eastbound right-turn flashing yellow arrow phase to minimize conflicts with the cycle track along the south side of Army Navy Drive.
- The reconfiguration of the Army Navy Drive and VA 110 Off-Ramp intersection to convert:
 - The eastbound approach from two thru lanes to one thru lane; and
 - The westbound approach from two thru lanes to one thru lane.
- 6. The signalization and reconfiguration of the Army Navy Drive and 12th Street S intersection to convert:
 - The eastbound approach from one left/thru lane and one right-turn lane to one thru lane and one thru/right lane;
 - The westbound approach from one left/thru/right lane to two thru lanes and one right-turn lane; and
 - The southbound approach from one left/thru lane and one right-turn lane to one left-turn lane and one thru/right lane.
 - Additionally, the signal timings and phasing at the traffic signal at this intersection were clustered with

the adjacent traffic signal at 12th Street S and Long Bridge Drive.

- Reducing the number of eastbound (and then southbound) lanes between the intersections of Army Navy Drive and S Eads Street, and Army Navy Drive and 12th Street S from two lanes to one.
- Reducing the number of northbound lanes on Army Navy Drive between the intersections of Army Navy Drive and 12th Street S, and Army Navy Drive and the Hilton DoubleTree Hotel driveway from two lanes to one.

Transitway Extension to Pentagon City

The Transitway Extension to Pentagon City includes the following roadway geometry and operations to 12th Street S with the incorporation of the transitway:

- The reconfiguration of the S Hayes Street and 12th Street S intersection to convert the westbound approach from one left-turn lane, one thru lane, and one right-turn lane to one left/thru/right lane. Transitway volumes were added based on scheduled headways.
- The reconfiguration of the S Fern Street and 12th Street S
 intersection to include a center dedicated transit lane and
 convert the eastbound approach from one left/thru/right
 lane to one thru/right lane. Transitway volumes were
 added based on scheduled headways.
- 3. The signalization and reconfiguration of the S Elm Street and 12th Street S intersection to convert:
 - The westbound approach from one left/thru lane to one thru lane; and
 - The northbound approach from one left/right lane to one right-turn lane.
 - Additionally, the intersection was reconfigured to include a center dedicated transit lane. Transitway volumes were added based on scheduled headways.
- The reconfiguration of the S Eads Street and 12th Street S intersection to include a center dedicated transit lane.
 Transitway volumes were added based on scheduled headways.

At the time of scoping, signal phasing was understudy as part of a dedicated transitway study effort, led by Arlington County. As such, signal timings and phasing were based on those included in the 2025 No-Build VISSIM models provided by Arlington County.

Crystal City Transitway Extension

The Crystal City Transitway Extension project includes the following changes to roadway geometry and operations to the 12th Street S:

1. The reconfiguration of the 12th Street S and S Clark Street/Long Bridge Drive intersection. This includes the conversion of the westbound approach from one left-turn lane and one thru/right lane to one left-turn lane, one thru lane, and one right-turn lane. Additionally, the signal timings and phasing were modified to cluster the traffic signal at this intersection with the adjacent traffic signal at 12th Street S and Army Navy Drive.

Metropolitan Park 6, 7, and 8

The Metropolitan Park 6, 7, and 8 project includes the following changes to roadway geometry and operations to S Eads Street and 15th Street S:

- The signalization and reconfiguration of the S Eads Street and 13th Street S intersection to convert:
 - The eastbound approach from one left/thru/right lane to one left-turn lane and one right-turn lane;
 - The southbound approach from one left-turn lane and one thru/right lane to one thru lane and one right-turn lane.
 - The westbound driveway for the Meridian at Pentagon City will not be included as part of the signal.
- 14th Street S and S Eads Street is a new intersection that will provide full signalized access to the new internal segment of 14th Street S. Each intersection approach is configured with the following:
 - The eastbound approach will include one left/thru/right lane.
 - The westbound approach will include one left/thru/right lane.
 - The northbound approach will include one left-turn lane and one thru/right lane.
 - The southbound approach will include one left-turn lane and one thru/right lane.
- The signalization and reconfiguration of the S Elm Street and 15th Street S intersection to break the existing median and convert:
 - The eastbound approach from two thru lanes to one left-turn lane and two thru lanes; and

- The southbound approach from one right-turn lane to one left-turn lane and one right-turn lane.
- 4. S Eads Street and 15th Street S will be reconfigured as a protected intersection. Each intersection approach is configured with the following:
 - The eastbound approach will include one left-turn lane, one thru lane, and one thru/right lane.
 - The westbound approach will include one left-turn lane, one thru lane, and one thru/right lane.
 - The northbound approach will include one left-turn lane, one thru lane, and one right-turn lane.
 - The southbound approach will include one left-turn lane, one thru lane, and one right-turn lane.

Lane configurations and traffic controls for the 2025 Background Conditions are shown in Figure 58.

2025 Mitigated Future Geometry and Operations Assumptions (with the proposed development)

The configurations and traffic controls for the 2025 Mitigated Future Conditions were based on those for the 2025 Background Conditions with the addition of the PenPlace development. One (1) new intersection was added, and 10 intersections were modified to provide access to the below-grade parking garage of the proposed development and create additional capacity at critical locations to allow more vehicles to be processed through the analyzed network.

It should be noted that the intersection of Army Navy Drive and S Hayes Street was reconfigured to include northbound and southbound dual left-turn lanes by converting an adjacent thru lane to a left-turn lane. The opposing left-turning movements is assumed to operate under lead-lag phasing and will not operate concurrently. This mitigation was identified to create additional left-turn capacity at this location, necessitated by congestion that was already present under Background (2025) conditions without the addition of the proposed development; however, this modification was not included in the analysis for Background conditions. Omitting this improvement would result in longer queues and higher delays compared to conditions with the improvements.

The modifications of the roadway network as a result of the proposed development are as follows:

 The reconfiguration of the Army Navy Drive and S Fern Street intersection to convert the southbound approach from one left-turn lane, one thru lane, and one thru/right lane to one left-turn lane, one thru lane, and one right-turn lane and convert the northbound approach from one left-turn lane, one thru lane, and one thru/right lane to one left-turn lane, one thru lane, and one right-turn lane.

- Army Navy Drive and Parking Lot will be signalized and reconfigured to provide access to the site's below-grade parking garage. Each intersection approach is configured with the following:
 - The eastbound approach will include one left/thru
 lane, two thru lanes, and one right-turn lane. Signal
 timings and phasing will incorporate a protected rightturn phase to minimize conflicts between heavy
 vehicles and the cycle track.
 - The westbound approach will include one thru lane and one thru/right lane.
 - The northbound approach will include one left/thru/right lane.
 - The southbound approach will include one left/thru/right lane.
- The reconfiguration of the S Eads Street and Army Navy Drive intersection to include:
 - Reconfiguration of the northbound approach from one left-turn lane and one thru/right lane to one leftturn lane, one thru lane and one thru/right lane.
 - Signal timing and phasing modification to convert the southbound left-turn movement from permissiveprotected to permissive phasing.
- 4. S Eads Street and 11th Street S/Site Driveway will be signalized and reconfigured to provide access to the site's below-grade parking garage. Each intersection approach is configured with the following:
 - The eastbound approach will include one left/thru lane and one right-turn lane.
 - The westbound approach will include one left/thru/right lane.
 - The northbound approach will include one left-turn lane and one thru/right lane.
 - The southbound approach will include one left/thru lane and one right-turn lane.
- 5. The reconfiguration of the S Fern Street and 12th Street S intersection to include:

- Reconfiguration of the southbound approach from one left/thru/right lane to one left-turn lane and one thru/right lane.
- Signal timing and phasing modification to convert the northbound left-turn movement from permissive to permissive-protected phasing.
- Signal timing and phasing modification to convert the southbound left-turn movement from permissive to permissive-protected phasing.
- 6. The reconfiguration of the S Eads Street and 12th Street S intersection to convert the southbound approach from one left/thru/right to one left-turn lane and one thru/right lane. Signal timings and phasing modification to convert the southbound left-turn movement from permissive to permissive-protected phasing.
- 7. S Fern Street and Site Driveway is a new access point that will provide full signalized access to the site's belowgrade parking garage. Each intersection approach is configured with the following:
 - The eastbound approach will include one left/thru/right lane.
 - The westbound approach will include one left/thru lane and one right-turn lane.
 - The northbound approach will include one left-turn lane and one thru/right lane.
 - The southbound approach will include one left-turn lane and one thru/right lane.
- 8. The modification of the S Fern Street and 15th Street S intersection to convert the southbound left-turn movement from permissive to permissive-protected phasing.
- 9. The modification of the S Eads Street and 15th Street S intersection to include:
 - Signal timing and phasing modification to convert the eastbound left-turn movement from permissive to permissive-protected phasing.
 - Signal timing and phasing modification to convert the westbound left-turn movement from permissive to permissive-protected phasing.
- The modification of the S Eads Street and I-395 Ramps (South) intersection to convert the northbound left-turn movement from protected to permissive-protected phasing.

Lane configurations and traffic controls for the 2025 Mitigated Future Conditions are shown in Figure 59. Figure 60 shows a

comparison of lane configurations and traffic controls between the Existing, 2025 Background, and 2025 Mitigated Future scenarios. Proposed turning lane storage lengths at intersections adjacent to the site are summarized in Figure 61.

2031 Background Geometry and Operations Assumptions (without the proposed development)

The geometry and operations assumptions align with that which were assumed under 2025 Background Conditions. Lane configurations and traffic controls for the 2031 Background Conditions are shown in Figure 62.

2031 Mitigated Future Geometry and Operations Assumptions (with the proposed development)

Lane configurations and traffic controls for the 2031 Mitigated Future Conditions align with that which were assumed under 2031 Background Conditions, with the addition of the PenPlace development. Lane configurations and traffic controls for the 2031 Mitigated Future Conditions are shown in Figure 63. Figure 64 shows a comparison of lane configurations and traffic controls between the Existing, 2031 Background, and 2031 Mitigated Future scenarios.




Figure 57: 2020 Existing Lane Configurations and Traffic Controls




Figure 58: 2025 Background Lane Configuration and Traffic Controls (without the proposed development)




Figure 59: 2025 Mitigated Future Lane Configuration and Traffic Controls (with the proposed development)




Figure 60: Lane Configuration and Traffic Controls Comparison by Scenario (2025)




Figure 61: Site Plan and Proposed Turning Lane Storage Lengths




Figure 62: 2031 Background Lane Configuration and Traffic Controls (without the proposed development)




Figure 63: 2031 Mitigated Future Lane Configuration and Traffic Controls (with the proposed development)




Figure 64: Lane Configuration and Traffic Controls Comparison by Scenario (2031)

Signal Warrant Analysis

This section presents the evaluation of the traffic signal control warrant for three (3) intersections surrounding the site, where the Applicant has proposed to fund the study and installation of traffic signals as part of the PenPlace development. The signal warrant analyses were performed following the procedures outlined in the 2009 Manual on Uniform Traffic Control Devices (MUTCD) for Warrant 3 (Peak Hour) and Warrant 4 (Pedestrian Volume). According to the MUTCD, only one of the warrants needs to be satisfied to allow for the installation of a traffic control signal. The criterion of each warrant was evaluated using the information obtained for the Existing (2020) and Future (2025 and 2031) with development conditions. Expected future bicycle volumes, shown in Figure 65, were incorporated into the vehicular signal warrants. The pedestrian volumes shown in the warrants are based on existing pedestrian volumes with the addition of expected future pedestrian volumes. The expected future pedestrian volumes are shown in Figure 66. A signal warrant analysis was performed for each of the following intersections:

• Army Navy Drive & Parking Lot/Site Driveway
Under existing conditions, neither Warrant 3 (Peak Hour) or
Warrant 4 (Pedestrian Volume) are met, as shown in Figure
67 and Figure 68. The southbound approach (the parking lot
entrance under existing conditions) is the minor street
approach with the higher peak hour volumes, and Army
Navy Drive is considered to be the major street.

Warrant 3 (Peak Hour) is satisfied under Future (2025 and 2031) with development conditions during the afternoon peak hour. The northbound approach is the minor street approach with the higher peak hour volumes, and Army Navy Drive is considered to be the major street. Therefore, a traffic signal is warranted at this intersection. Warrant 3 (Pedestrian Volume) is not met as there are no crosswalks present across the major approaches.

S Eads Street & 11th Street S/Site Driveway
 Under existing conditions neither Warrant 3 (Peak Hour) or Warrant 4 (Pedestrian Volume) are met, as shown in Figure 69 and Figure 70. The westbound approach of 11th Street S is the minor street approach with the higher peak hour volumes, and S Eads Street is considered to be the major

Warrant 3 (Peak Hour) is satisfied under Future (2025 and 2031) with development conditions during the afternoon peak hour. The eastbound approach is considered to be the minor street approach with the higher peak hour volumes,

and S Eads Street is considered to be the major street. Therefore, a traffic signal is warranted at this intersection. Warrant 4 (Pedestrian Volumes) is not satisfied under Future (2025 and 2031) with development conditions.

S Fern Street & Site Driveway

Under existing conditions, neither Warrant 3 (Peak Hour) or Warrant 4 (Pedestrian Volume) are met, as shown in Figure 71 and Figure 72. The eastbound approach (the existing driveway entrance under existing conditions) is the minor street approach with the higher peak hour volumes, and S Fern Street is considered to be the major street.

Warrant 3 (Peak Hour) is not satisfied under Future (2025 and 2031) with development conditions. Warrant 4 (Pedestrian Volume) is satisfied under Future (2025 and 2031) with development conditions during the morning peak hour. Therefore, a traffic signal is warranted at this intersection.

Given the data that is available at this time, this report only includes Warrant 3 (Peak Hour) and Warrant 4 (Pedestrian Volume). As agreed to by Arlington County and VDOT, if consideration of additional warrants is needed by Arlington County, additional data collection and documentation will be provided at a subsequent stage. A summary of the warrant analysis for each intersection is shown in Table 16.

Table 16: Signal Warrant Analysis Summary

	Existing (2025)		Future (2025 and 2031)		
	Warrant 3 (Vehicular Peak Hour)	Warrant 4 (Pedestrian Volumes)	Warrant 3 (Vehicular Peak Hour)	Warrant 4 (Pedestrian Volumes)	
Army Navy Drive & Parking Lot/Site Driveway	N	N	Υ	N	
S Eads Street & 11 th Street S/Site Driveway	N	N	Υ	N	
S Fern Street & Site Driveway	N	N	N	Υ	




Figure 65: Expected Site Generated Bicycle Volumes




Figure 66: Expected Site Generated Pedestrian Volumes




Figure 67: Warrant 3, Peak Hour Vehicle Volume - Army Navy Drive and Parking Lot/Site Driveway




Figure 68: Warrant 4, Pedestrian Peak Hour - Army Navy Drive and Parking Lot/Site Driveway




Figure 69: Warrant 3, Peak Hour Vehicle Volume - S Eads Street and 11th Street S/Site Driveway




Figure 70: Warrant 4, Pedestrian Peak Hour - S Eads Street and 11th Street S/Site Driveway




Figure 71: Warrant 3, Peak Hour Vehicle Volume - S Fern Street and Site Driveway




Figure 72: Warrant 4, Pedestrian Peak Hour - S Fern Street and Site Driveway

Operations Analysis Results

The MOEs used to evaluate the VISSIM microsimulation results were scoped and approved by the County. These MOEs are:

- Individual Link Vehicular Volumes/Throughput –
 measured in vehicles per hour, this metric is used to help
 identify individual link's ability to process volumes in each of
 the analysis scenario, thus identifying issues related to
 capacity;
- Simulated Vehicular Travel Times measured in seconds, this metric is used to help compare the simulated average amount of time it takes a vehicle to travel between two specified points;
- Simulated Transit Travel Times along 12th Street S
 Transit Route measured in seconds, this metric is used to help compare the simulated average amount of time it takes a transit vehicle to travel between two specified points;
- Vehicular Delay measured in seconds of delay per vehicle, this metric measures the difference between the actual vehicle travel time and its desired travel time.
- Pedestrian and Bicycle Delay measured in seconds of delay per pedestrian/bicycle, this metric measures the difference between the actual pedestrian/bicycle travel time due to stops at a signalized intersection (control delay).

2020 Analysis Results

Simulation Model Development and Existing Calibration

The base VISSIM model provided by Arlington County was reviewed and updated based on the study area characteristics, available data, and VDOT TOSAM criteria. The VISSIM network inputs used for the simulation model development are detailed in the VISSIM Model Recalibration memo approved by Arlington County.

Model calibration is the process of performing adjustments to the model to better simulate local driving behavior and operational performance. The calibration process typically compares field data (volumes, speed, travel time, queue length, etc.) to the simulation output so that the model represents actual traffic conditions in the study area. A model that is appropriately calibrated improves the model's ability to assess the future conditions of the study area. The calibration criteria were scoped and approved by Arlington County, as outlined in Table 17.

The turning movement volumes at signalized intersections and travel time field measurements, provided by Arlington County, were utilized as metrics to recalibrate the base VISSIM model.

As part of the calibration process, the vehicle routing decisions were combined at some locations to reflect more realistic lane change behavior of drivers. Combining routing decisions were performed on the case-by-case basis during the AM and PM peak periods based on the visual observation of simulated network. Since the volume data for this project was limited to turning movement counts without any origin-destination information, some traffic circulation inside the study area was inevitable. However, considerations were made when combining the routes to prevent unnecessary traffic circulation, where possible.

Some model parameters were adjusted to reflect actual network performance and driver behaviors. The models were run with adjusted parameters and the outputs were examined against field measurements.

The VISSIM modeling calibration used in this analysis met the calibration acceptance targets in 100% of cases, which is consistent with VDOT TOSAM guidance. The approved calibration memo is provided in the Technical Appendix.

Simulated Vehicular Volumes

Vehicular volume results are used to help identify each scenario's ability to process vehicular volumes on a macro and micro level. These results are expressed as the number of vehicles denied entry into network, or as individual link vehicular volumes (throughput). Simulated individual link volumes results, also known as throughput results, for the 2020 Existing analysis scenario are included in the Technical Appendix.

Simulated Vehicular Travel Times

Vehicular travel time is the amount of time it takes for a vehicle to travel from point A to point B. It is a direct reflection of motorist experience. The two (2) vehicular travel times that were analyzed as part of the *VISSIM* microsimulation analysis were:

- Eastbound Army Navy Drive from S Joyce Street to 12th Street S
- Westbound Army Navy Drive from 12th Street S to S Joyce Street

Simulated travel time results for the two (2) vehicular travel time measurement segments that were analyzed using VISSIM in the 2020 Existing analysis scenario are shown in Table 19 for the AM peak and Table 20 for the PM peak.

Simulated Vehicular Delay

Simulated vehicular delay results show the difference between the actual vehicle travel time due to stops at a signalized intersection (control delay) and is measured in seconds of delay per vehicle. Tables showing the simulated vehicular delay for study area intersections for the 2020 Existing analysis scenario are included in the Technical Appendix and shown in Table 19 and Table 20. The level of service (LOS) for signalized intersections within the study area under the 2020 Existing scenario is provided in Figure 73 and Figure 74.

Based on the VISSIM results, the majority of intersections operate at acceptable levels of service (LOS E or better) in the 2020 Existing scenario; however, one (1) intersection has one or more approach that operate beyond acceptable thresholds in one or more peak hour:

S Eads Street & I-395 HOT Lanes (North Node) – AM

Simulated Bicycle and Pedestrian Delay

Simulated bicycle and pedestrian delay results show the difference between the actual pedestrian/bicycle travel time due to stops at a signalized intersection (control delay) and is measured in seconds of delay per pedestrian/bicycle. For example, a bicycle or pedestrian may experience roughly one minute of wait time at a signalized intersection due to longer cycle lengths or adjustments to signal timings to accommodate additional traffic on the roadway. Tables showing the simulated bicycle and pedestrian delay for study area intersections for the 2020 Existing analysis scenario are included in the Technical Appendix and shown in Table 23. Bicycle delay is reported for the bicycle facilities included in the VISSIM model, as agreed upon during the scoping process, no bicycle facilities are assumed in 2020 Existing.

Table 17: VISSIM Modeling Calibration Criteria and Results

Calibration Criterion ¹	Calibration Target ¹	Res	Results	
Cambration Criterion	Calibration Target	AM Peak	PM Peak	
Simulated Traffic Volume				
Within 20% (Flow < 100 veh/h)	>85% of cases	100%	100%	
Within 15% (Flow from 100 veh/h to 1000 veh/h)	>85% of cases	100%	100%	
Within 10% (Flow from 1000 veh/h to 5000 veh/h)	>85% of cases	100%	100%	
Within 500 veh/h (Flow > 5000 veh/h)	>85% of cases	N/A	N/A	
Simulated Travel Time				
Within 30% of Observed Travel Times	>85% of cases	100%	100%	

¹⁾ Based on VDOT TOSAM Version 2 Criteria

2025 Analysis Results

Simulated Vehicular Volumes

Vehicular volume results are used to help identify each scenario's ability to process vehicular volumes on a macro and micro level. These results are expressed as the number of vehicles denied entry into network, or as individual link vehicular volumes (throughput).

Simulated individual link volumes results, also known as throughput results, for the 2020 Existing, 2025 Background, and 2025 Mitigated Future analysis scenarios are included in the Technical Appendix.

GEH Statistic

The GEH statistic is a formula used in traffic modeling to compare two sets of traffic volumes and indicate whether the model processes enough vehicles in the network to be considered valid. A GEH value that is less than 5 indicates a good fit between the input and simulated volumes. A GEH value between 5 and 10 may require further investigation. A GEH value that is greater than 10 indicates an error in the model. Under 2025 Mitigated Future conditions, all movements operate at acceptable GEH values (GEH value < 5).

Vehicles Entering the Network

The number of vehicles entered into the network for each of the analysis scenarios is shown in Table 18. The percentage of

vehicles able to enter the network for the 2025 Mitigated Future scenario was evaluated. The proposed mitigations included in the 2025 Mitigated Future scenario, discussed in a later section of this chapter, will create additional capacity at critical locations to allow more vehicles to be processed through the network. The proposed development adds an additional 1,802 vehicles (+6.70%) in the morning peak period and 1,752 vehicles (+5.73%) in the afternoon peak period, increasing the total number of vehicles that needs to be processed through the network. With the recommended mitigations, under the 2025 Mitigated Future scenario, the total number of vehicles processed increases by 1,838 vehicles (+6.85%) and 2,030 vehicles (+6.76%) in the morning and afternoon peak period, respectively.

Simulated Vehicular Travel Times

Vehicular travel time is the amount of time it takes for a vehicle to travel from point A to point B. It is a direct reflection of motorist experience. The two (2) vehicular travel times that were analyzed as part of the *VISSIM* microsimulation analysis were:

- Eastbound Army Navy Drive from S Joyce Street to 12th Street S
- Westbound Army Navy Drive from 12th Street S to S Joyce Street

Simulated travel time results for the two (2) vehicular travel time measurement segments that were analyzed using VISSIM in the 2025 Background and 2025 Mitigated Future analysis scenarios are shown in Table 19 for the AM peak and Table 20 for the PM Peak. The travel time along some segments reflect additional local traffic as well as adjustments to the corridor to accommodate a new signal. The 2025 Mitigated Future analysis includes a new signal at the Army Navy Drive and Parking Lot/Site Driveway intersection where the 2025 Background analysis does not.

Simulated Transit Travel Times

Transit travel time is the amount of time it takes for a transit vehicle to travel from point A to point B. It is a direct reflection of motorist experience. The two (2) transit travel times that were analyzed as part of the *VISSIM* microsimulation analysis were:

- Eastbound 12th Street S from S Hayes Street to Long Bridge Drive
- Westbound 12th Street S from Long Bridge Drive to S Hayes Street

Simulated travel time results for the two (2) transit travel time measurement segments that were analyzed using VISSIM in the

2025 Background and 2025 Mitigated Future analysis scenarios are shown in Table 19 for the AM peak and Table 20 for the PM Peak. The travel time along some segments reflect additional local traffic as well as adjustments to the corridor to accommodate a new signal.

Due to capacity constraints elsewhere in the network, volumes have been re-routed in PM peak hour under 2025 Mitigated Future conditions. Therefore, the travel times in 2025 Mitigated Future conditions are improved compared to 2025 Background conditions.

Simulated Vehicular Delay

Simulated vehicular delay results show the difference between the actual vehicle travel time due to stops at a signalized intersection (control delay) and is measured in seconds of delay per vehicle. Tables showing the simulated vehicular delay for study area intersections for the 2025 Background and 2025 Mitigated Future analysis scenarios are included in the Technical Appendix and shown in Table 19 and Table 20. At the majority of intersections in the network, the vehicular delay results under the 2025 Mitigated Future scenario, with added site traffic and recommended mitigation measures, are comparable to that under the 2025 Background scenario. A comparison of the level of service (LOS) between scenarios is provided in Figure 73 and Figure 74 for 2025 Background and 2025 Mitigated Future scenarios.

It is important to note that VISSIM is a microscopic analysis rather than a macroscopic analysis. Mitigation measures are recommended such that the results are comparable or better than the Background conditions throughout the network. The recommended mitigation measures are in place to address targeted issues at specific, as well as increase the vehicular throughput of the overall network, particularly at exterior intersections that are responsible for metering vehicles entering the network. Due to the increased number of vehicles being processed in the network compared to Background conditions, there may be locations where delays are higher than that seen under Background conditions.

2025 Background

Based on the VISSIM results, the majority of intersections operate at acceptable levels of service (LOS E or better) in the 2025 Background scenario; however, four (4) intersections have one or more approach that operate beyond acceptable thresholds in one or more peak hour:

- 12th Street S & S Clark Street/Long Bridge Drive PM
- S Eads Street & 13th Street S PM
- S Eads Street & I-395 HOT Lanes (South Node) AM
- S Eads Street & 14th Street S PM

2025 Mitigated Future

Based on the VISSIM results, the majority of intersections operate at acceptable levels of service (LOS E or better) in the 2025 Mitigated Future scenario; however, eight (8) intersections have one or more approach that operate beyond acceptable thresholds in one or more peak hour:

- Army Navy Drive & Parking Lot/Site Driveway PM
- S Fads Street & 12th Street S AM/PM
- 12th Street S & S Clark Street/Long Bridge Drive AM/PM
- S Eads Street & 13th Street S PM
- S Eads Street & I-395 HOT Lanes (South Node) AM
- S Eads Street & I-395 HOT Lanes (North Node) AM
- S Eads Street & 14th Street S AM/PM
- S Fern Street & 11th Street S/Site Driveway PM

Most vehicular capacity concerns in the study area can be alleviated through signal timing changes that adapt to changes in volume patterns, but at some locations, operational changes alone cannot mitigate future delays. A Transportation Management Plan (TMP) will be provided for the project based on the County's requirements, and a framework for a TMP is included in this report, to further reduce vehicular trips generated by the proposed development during peak period travel times.

Simulated Bicycle and Pedestrian Delay

Simulated bicycle and pedestrian delay results show the difference between the actual pedestrian/bicycle travel time due

to stops at a signalized intersection (control delay) and is measured in seconds of delay per pedestrian/bicycle. For example, a bicycle or pedestrian may experience roughly one minute of wait time at a signalized intersection due to longer cycle lengths or adjustments to signal timings to accommodate additional traffic on the roadway. Tables showing the simulated bicycle and pedestrian delay for study area intersections for the 2025 Background and 2025 Mitigated Future analysis scenarios are included in the Technical Appendix and shown in Table 23. Note that a number of movements do not a report bicycle delays (i.e., along 12th Street S where sharrows are planned). Bicycle delay is reported for the bicycle facilities included in the VISSIM model, as agreed upon during the scoping process. Analyzed bicycle facilities include the cycle track along the south side of Army Navy Drive between S Joyce Street and 12th Street S, protected bicycle lanes along S Eads Street between Army Navy Drive and 15th Street S, and protected bicycle lanes along S Fern Street between Army Navy Drive and 12th Street S.

The bicycle and pedestrian delay results under the 2025 Mitigated Future scenario, with added site traffic and recommended mitigation measures, are comparable to that under the 2025 Background scenario.

Evaluation of Recommended Mitigations

Based on the results of the VISSIM microsimulation analysis, the recommended mitigation measures are detailed in Table 1 and summarized in Figure 1. Tables showing the simulated delay and maximum queues for study area intersections for the 2020 Existing, 2025 Background, and 2025 Mitigated Future analysis scenarios are included in the Technical Appendix. In addition to the mitigation measures below, the analysis includes protected northbound and southbound bike lanes along S Fern Street and S Eads Street between Army Navy Drive and 12th Street S.

Table 18: Number Vehicles Entered into Network (2025)

	Backgrou	ınd (2025)	Mitigated Future (2025)		
	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	
Total Vehicle Input (veh/2 hrs)	26,904	30,590	28,706	32,342	
Number of Vehicles Entered into Network (veh/2 hrs)	26,820	30,036	28,658	32,066	
Percent Vehicles Entered (%)	99.69%	98.19%	99.83%	99.15%	

Table 19: AM Peak Hour Simulated Travel Time Results (2025)

	Travel Time (sec)			Difference*	
Travel Time Segment	Existing (2020)	Background (2025)	Mitigated Future (2025)	(sec)	
Vehicular Travel Time					
EB Army Navy Dr from S Joyce St to 12 th St S	339	219	226	+7	
WB Army Navy Dr from 12th St S to S Joyce St	159	196	191	-5	
Transit Travel Time					
EB 12 th St from S Hayes St to Long Bridge Dr		222	214	-8	
WB 12 th St from Long Bridge Dr to S Hayes St		170	177	+7	

^{*} Difference from Background (2025) scenario

Table 20: PM Peak Hour Simulated Travel Time Results (2025)

		Difference*			
Travel Time Segment	Existing (2020)	Background (2025)	Mitigated Future (2025)	(sec)	
Vehicular Travel Time					
EB Army Navy Dr from S Joyce St to 12th St S	178	232	281	+49	
WB Army Navy Dr from 12 th St S to S Joyce St	185	259	261	+2	
Transit Travel Time					
EB 12 th St S from S Hayes St to Long Bridge Dr		237	181	-56	
WB 12 th St S from Long Bridge Dr to S Hayes St		256	171	-85	

^{*} Difference from Background (2025) scenario




Figure 73: AM Peak Hour Level of Service Comparison by Scenario (2025)




Figure 74: PM Peak Hour Level of Service Comparison by Scenario (2025)

	e 21: AM Vehicular Delay				AMJ	Peak Hour		
Inte	rsection and Lane Group	Storage Length	Average o	of Maximum Que			ehicular Moveme	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
1.	S Hayes Street &				rataro			ratare
	Army Navy Drive Eastbound Left	260	84	104	110	30.8 (C)	82.6 (F)	77.8 (E)
	Eastbound Thru	450	232	252	278	36 (D)	52.0 (1) 52.1 (D)	51.6 (D)
	Eastbound Right	450	256	252	278	30 (D) 32.1 (C)	47 (D)	54.3 (D)
	Westbound Left	190	116	334	182	24.9 (C)	185.4 (F)	79.7 (E)
	Westbound Thru	430	136	199	188	35.7 (D)	43.3 (D)	37.2 (D)
	Westbound Right	430	58	28	38	0.5 (A)	1 (A)	0.5 (A)
	Northbound Left	200	133	213	120	47 (D)	77 (E)	74.9 (E)
	Northbound Thru	750	153	185	300	56.8 (E)	37.6 (D)	65.5 (E)
	Northbound Right	115	99	192	176	9 (A)	36.8 (D)	` '
	Southbound Left	2050	952	3,785	2,625	52.7 (D)	` ′	18.4 (B)
	Southbound Thru	1950	952	3,785	2,625	` ,	131 (F) 30.6 (C)	110.9 (F)
	Southbound Right	1950	353	· ·	1	33.8 (C)	` ,	51.9 (D)
	Overall	1950		3,784	2,622	8.3 (A)	17.9 (B)	34.9 (C)
	S Fern Street & Army					32.3 (C)	47.5 (D)	56.3 (E)
2.	Navy Drive							
	Eastbound Left	160	156	132	138	26.8 (C)	32.5 (C)	31 (C)
	Eastbound Thru	430	421	414	597	26.5 (C)	42.2 (D)	40.2 (D)
	Eastbound Right	180	153	254	544	6.2 (A)	33.1 (C)	45.1 (D)
	Westbound Left	80	312	346	311	52.6 (D)	121.3 (F)	125.3 (F)
	Westbound Thru	260	312	346	311	21.1 (C)	31.7 (C)	9.5 (A)
	Westbound Right	260	317	350	315	17.2 (B)	32.1 (C)	10.4 (B)
	Northbound Left	280	231	299	275	45.8 (D)	68.5 (E)	67.1 (E)
	Northbound Thru	390	67	105	53	27.5 (C)	50 (D)	24.8 (C)
	Northbound Right	80	75	105	70	7.5 (A)	51.6 (D)	31.4 (C)
	Southbound Left	75	185	253	388	31.8 (C)	44.2 (D)	51.8 (D)
	Southbound Thru	560	208	277	433	27 (C)	45.5 (D)	54.2 (D)
	Southbound Right	560	215	284	432	17.4 (B)	34.4 (C)	62.4 (E)
	Overall					26.1 (C)	43.7 (D)	42.1 (D)
3.	Army Navy Drive &					, ,	. ,	` '
J.	Parking Lot							
	Eastbound Left	120			376			2.6 (A)
	Eastbound Thru	260			376			2.5 (A)
	Eastbound Right	225			376			60 (E)
	Westbound Thru	230			215			3.7 (A)
	Westbound Right	230			232			4.6 (A)
	Northbound Left	100	Un-	Unsignalized	86	. Un-	Unsignalized	75.3 (E)
	Northbound Thru	100	signalized		89	signalized		0 (A)
	Northbound Right	100			86			73.4 (E)
	Southbound Left	100			51			71.9 (E)
	Southbound Thru	100			51			0 (A)
	Southbound Right	100			56			16.7 (B)
	Overall							6.5 (A)
4.	S Eads Street & Army Navy Drive					_		
	Eastbound Left	220	332	310	235	24.2 (C)	21.3 (C)	20.5 (C)
	Eastbound Thru	220	331	309	236	16.7 (B)	10.9 (B)	12.8 (B)
	Eastbound Right	220	359	297	234	7.9 (A)	16.3 (B)	18 (B)
	Westbound Thru	1100	181	170	184	48.9 (D)	31.8 (C)	55.5 (E)
	Westbound Right	100	181	180	194	30.6 (C)	11.8 (B)	20.3 (C)

	Northbound Left Northbound Thru Northbound Right Southbound Right Overall Army Navy Drive & 110 Ramp Eastbound Thru Southbound Right Overall S Eads Street & 11th Street S Eastbound Thru Eastbound Thru Eastbound Right Westbound Right Westbound Left Westbound Right Northbound Right Northbound Right Northbound Left Northbound Right Southbound Right Overall S Hayes Street & 12th Street S Eastbound Thru Eastbound Right Westbound Right Westbound Left Southbound Right Northbound Right Northbound Right Northbound Right Southbound Right Northbound Right Northbound Right Northbound Right Southbound Right Nortall S Fern Street & 12th Street S Eastbound Thru Southbound Right Westbound Right Westbound Right Westbound Right Westbound Right Westbound Right Westbound Right	Storage	Average	f Maximum O		Peak Hour Average of V	ehicular Movemer	nt Delay (sec/veh
Inter	rsection and Lane Group	Length (ft)	Average o	of Maximum Queu			and Level of Serv	rice
		(11)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Northbound Left	100	191	321	262	18 (B)	36.4 (D)	71.3 (E)
	Northbound Thru	240	299	321	274	35.4 (D)	25.9 (C)	14.5 (B)
	Northbound Right	240	299	321	274	32.1 (C)	26.1 (C)	11.4 (B)
	Southbound Left	140	302	352	357	32.1 (C)	35.2 (D)	26.9 (C)
	Southbound Thru	140	298	352	357	30.2 (C)	41.4 (D)	37.2 (D)
	Southbound Right	110	298	352	367	32.9 (C)	20.6 (C)	7 (A)
	Overall					6.3 (A)	25.1 (C)	26.4 (C)
5.								
•-	•				0			0.4 (4)
		1000			0			0.1 (A)
			Un- signalized	Unsignalized	111	Un- signalized	Unsignalized	3.2 (A)
	· ·	900	signalized		0	Signalized		2.1 (A)
	- · · · · · · · · · · · · · · · · · · ·							1.3 (A)
6.								
	Eastbound Left	200			105			56.9 (E)
	Eastbound Thru	200			105			0 (A)
	Eastbound Right	200			105			53.2 (D)
	ū	300			112			60.7 (E)
	Westbound Thru	300			112			0 (A)
		300			112			57.6 (E)
	ŭ	100	Un-	Unsignalized	254	Un-	Unsignalized	17.4 (B)
		250	signalized	Orisignalized	243	signalized	Orisignalized	` '
					_			9.2 (A)
	ŭ	250			246			7.3 (A)
		250 250			362			11.7 (B)
					362			10.3 (B)
	· ·	25			365			6.5 (A)
								14.2 (B)
7.								
	Eastbound Left	450	95	145	134	30.3 (C)	51.3 (D)	53.5 (D)
	Eastbound Thru	450	95	145	134	27.8 (C)	42.6 (D)	39.8 (D)
	Eastbound Right	65	94	143	132	5.3 (A)	47.9 (D)	49.6 (D)
	Westbound Left	100	161	240	191	31.6 (C)	73.5 (E)	60 (E)
		620	161	240	191	27.8 (C)	65.1 (E)	51.5 (D)
		620	171	240	191	12.5 (B)	67.8 (E)	51.9 (D)
	ŭ	75	125	172	182	59.2 (E)	73.3 (E)	75.7 (E)
		775	125	172	182	21.1 (C)	24 (C)	28.4 (C)
		75	129	176	187	5.8 (A)	10 (A)	11.3 (B)
		250	499	497	497	71 (E)	57.7 (E)	65.6 (E)
		770	499 499	497	497 497	7.1 (A)	26.7 (C)	13.7 (B)
		770	506	497	497 497	1.9 (A)	28.5 (C)	15.7 (B) 15.9 (B)
						22.9 (C)	35.8 (D)	30.6 (C)
_						22.3 (0)	33.3 (D)	30.0 (0)
8.								
	Eastbound Thru	640	373	551	589	31.4 (C)	33 (C)	30.5 (C)
	Eastbound Right	640	373	560	598	28.6 (C)	31.3 (C)	28.7 (C)
	Westbound Left	75	379	193	238	26 (C)	83.9 (F)	87.3 (F)
	Westbound Thru	225	126	193	242	31.7 (C)	15.1 (B)	4.8 (A)
	Westbound Right	225	126	202	241	19.3 (B)	8.4 (A)	8.3 (A)
	Northbound Left	100	135	403	425	11.5 (B)	43.5 (D)	42.3 (D)
	Northbound Thru	280	257	370	383	21 (C)	34.1 (C)	50.1 (D)

Intern		Storage	Average	of Maximum Queu		Peak Hour Average of V	ehicular Movemer	
Inters	ection and Lane Group	Length (ft)	Existing	Background	Mitigated	Existing	and Level of Serving	Mitigated
	N dl IB: La	000		, and the second se	Future	· ·	•	Future
	Northbound Right	280	257	369	383	10.6 (B)	28.3 (C)	45.7 (D)
	Southbound Left	130	257	517	345	10.1 (B)	70.4 (E)	55.2 (E)
	Southbound Thru	275	415	517	426	19.3 (B)	59.6 (E)	18.2 (B)
	Southbound Right	275 	415	523	426	15.5 (B)	56 (E)	14.9 (B)
	Overall S Elm Street & 12th					14 (B)	43.5 (D)	37.1 (D)
).	Street S							
	Eastbound Thru	225		398	349		15.3 (B)	17.3 (B)
	Eastbound Right	225		390	351		8.1 (A)	14.5 (B)
	Westbound Thru	325	Un- signalized	67	56	Un- signalized	1.2 (A)	0.9 (A)
	Northbound Right	270	signalized	125	95	Signalized	59.5 (E)	45 (D)
	Overall						13.8 (B)	14.2 (B)
0.	S Eads Street & 12th Street S							
	Eastbound Left	150	413	380	384	38.3 (D)	112.5 (F)	106 (F)
	Eastbound Thru	320	413	380	384	40.4 (D)	66.9 (E)	67.2 (E)
	Eastbound Right	320	417	380	384	36.8 (D)	70.8 (E)	67.1 (E)
	Westbound Left	200	231	244	445	63.7 (E)	85.3 (F)	95.2 (F)
	Westbound Thru	575	231	244	445	33.8 (C)	65.3 (E)	87.9 (F)
	Westbound Right	575	231	244	445	38.4 (D)	69.4 (E)	88.3 (F)
	Northbound Left	100	195	341	368	17.6 (B)	24.7 (C)	33.8 (C)
	Northbound Thru	270	195	341	368	11.2 (B)	17 (B)	29.1 (C)
	Northbound Right	100	199	345	259	10.3 (B)	9.8 (A)	11.6 (B)
	Southbound Left	120	343	339	302	20.5 (C)	23.6 (C)	33.4 (C)
	Southbound Thru	250	343	339	302	19.1 (B)	21.4 (C)	13.7 (B)
	Southbound Right	250	342	344	301	18.2 (B)	20.9 (C)	11 (B)
	Overall					31 (C)	39.6 (D)	43.1 (D)
1.	12th Street S & Army Navy Drive							
	Eastbound Thru	575		598	647		21.7 (C)	28 (C)
	Eastbound Right	575		609	647		17.6 (B)	30.4 (C)
	Westbound Thru	120		236	232		11.7 (B)	14.6 (B)
	Westbound Right	120		236	232		16 (B)	15.2 (B)
	Northbound Left	50	11-	62	57	1.100	0 (A)	0 (A)
	Northbound Thru	50	Un- signalized	62	57	Un- signalized	62.7 (E)	61.5 (E)
	Northbound Right	50	o.gridii20d	62	57	S.g. aZod	56.6 (E)	51.9 (D)
	Southbound Left	1000		243	268		43.8 (D)	60.2 (E)
	Southbound Thru	1000		243	268		0 (A)	0 (A)
	Southbound Right	1000		243	268		44.4 (D)	62.4 (E)
	Overall						25.2 (C)	32.7 (C)
2.	S Clark Street/Long Brid 12th Street S	dge Dr &						
	Eastbound Left	120	259	210	215	23 (C)	4.6 (A)	5.4 (A)
	Eastbound Thru	120	259	210	215	13.5 (B)	2 (A)	2.5 (A)
	Eastbound Right	120	260	210	215	7.2 (A)	2.9 (A)	3.1 (A)
	Westbound Left	100	64	76	74	15.3 (B)	22.4 (C)	21.5 (C)
	Westbound Thru	1500	365	355	323	13.5 (B)	25.8 (C)	26 (C)
	Westbound Right	1500	368	366	334	13.2 (B)	9.8 (A)	10.6 (B)
	Northbound Left	100	86	136	138	26.7 (C)	67.3 (E)	69.3 (E)
	Northbound Thru	1200	67	136	138	20.6 (C)	43 (D)	46.2 (D)
	Northbound Right	1200	69	141	143	10.4 (B)	21.4 (C)	18.8 (B)
	Southbound Left	450	195	450	870	24 (C)	54.7 (D)	82.7 (F)

					AM	Peak Hour		
Inter	section and Lane Group	Storage Length	Average o	of Maximum Queu			ehicular Movemer and Level of Serv	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Southbound Thru	450	195	450	870	22.1 (C)	52.3 (D)	80.2 (F)
	Southbound Right	150	80	326	870	7.1 (A)	56.8 (E)	91.1 (F)
	Overall					17.4 (B)	17.9 (B)	24.9 (C)
14.	S Eads Street & 13th							
	Street S	250		405	400		C4 7 (E)	70.0 (F)
	Eastbound Left	350		185	198		61.7 (E)	72.6 (E)
	Eastbound Right	350 150		185	198		58.2 (E)	56.7 (E)
	Northbound Left		Un-	294	427	Un-	1.8 (A)	8.9 (A)
	Northbound Thru	300	signalized	294	427	signalized	2.8 (A)	23.4 (C)
	Southbound Thru	280		152	167		4.7 (A)	5.6 (A)
	Southbound Right	280		154	169		2.3 (A)	3 (A)
	Overall S Fern Street & 15th						10.6 (B)	20.3 (C)
16.	Street S							
	Eastbound Left	130	338	280	297	21.2 (C)	23.5 (C)	43.6 (D)
	Eastbound Thru	630	338	280	297	29.7 (C)	24.7 (C)	38.1 (D)
	Eastbound Right	630	340	282	299	17.2 (B)	22.4 (C)	31 (C)
	Westbound Left	120	114	122	243	21.1 (C)	14.7 (B)	34.5 (C)
	Westbound Thru	260	114	122	243	11.8 (B)	8.2 (A)	23.8 (C)
	Westbound Right	260	116	124	246	6.2 (A)	5.2 (A)	20.2 (C)
	Northbound Left	750	266	467	840	19.8 (B)	49.9 (D)	62.9 (E)
	Northbound Thru	750	266	467	840	16.9 (B)	47 (D)	68.2 (E)
	Northbound Right	75	272	472	845	8.4 (A)	19.7 (B)	34.7 (C)
	Southbound Left	160	214	295	331	30.2 (C)	64.6 (E)	41.6 (D)
	Southbound Thru	300	214	295	331	16 (B)	42.3 (D)	25.7 (C)
	Southbound Right	300	229	309	336	10.8 (B)	19.9 (B)	11.5 (B)
	Overall					20.3 (C)	27.9 (C)	37.2 (D)
17.	15th Street S & S Elm Street							,
	Eastbound Left	60		359	325		12 (B)	9.1 (A)
	Eastbound Thru	270		359	325		13.7 (B)	12.2 (B)
	Westbound Thru	300		145	136		4 (A)	1.5 (A)
	Westbound Right	300	Un-	145	136	Un-	4.7 (A)	2.1 (A)
	Southbound Left	250	signalized	55	61	signalized	43.5 (D)	44.5 (D)
	Southbound Right	250		66	72		8.2 (A)	10 (A)
	Overall						10.2 (B)	8 (A)
8.	S Eads Street & 15th							
٠.	Street S	170	0.45	074	000	24.4.(2)	07.0 (0)	40.0 (5)
	Eastbound Left		345	271	339	31.1 (C)	27.6 (C)	46.8 (D)
	Eastbound Thru	300	413	369	411	46.8 (D)	17.7 (B)	44.9 (D)
	Eastbound Right	300 300	418	369	411	8.6 (A)	21.1 (C)	44.5 (D)
	Westbound Left	300	169	374	489	38.1 (D)	75.4 (E)	33.1 (C)
	Westbound Thru	300	169	374	489	15.8 (B)	25.7 (C)	43.5 (D)
	Westbound Right	300	181	374	489	12.7 (B)	33.8 (C)	59.2 (E)
	Northbound Left	130	335	895	927	24 (C)	46.2 (D)	43.8 (D)
	Northbound Thru	760 130	335	895	927	20.1 (C)	57.9 (E)	54.5 (D)
	Northbound Right	130	399	836	920	20.5 (C)	29.8 (C)	28.3 (C)
	Southbound Left	250	377	322	324	89.7 (F)	41.3 (D)	43.2 (D)
	Southbound Thru	300	345	322	324	27 (C)	34 (C)	23.6 (C)
	Southbound Right	75	348	326	327	26.9 (C)	12.5 (B)	8.9 (A)
	Overall					34 (C)	32.5 (C)	43.4 (D)

					AM I	Peak Hour		
Inter	section and Lane Group	Storage Length	Average o	f Maximum Que			ehicular Moveme and Level of Ser	nt Delay (sec/veh)
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
19.	S Eads Street & I-395 Ra	amps						
	(South Node) Eastbound Thru	1000	199	973	934	34.5 (C)	80.6 (F)	56.7 (E)
	Eastbound Right	1000	243	973	934	12.1 (B)	167.6 (F)	102.6 (F)
	Northbound Left	150				12.1 (b)	107.0 (1)	
	Northbound Thru	170	148	193	226	19.3 (B)	9.8 (A)	49.5 (D)
	Northbound Right	170	206	250	285	10.8 (B)	7.1 (A)	7.2 (A)
	Southbound Left	100	197	197	234	33.8 (C)	3.1 (A)	11 (B)
	Southbound Thru	100	194	194	234	9 (A)	29.7 (C)	43 (D)
	Overall					14.3 (B)	59.1 (E)	47.2 (D)
20	S Eads Street & I-395 Ra	amps				1 1.0 (2)	00.1 (2)	11.2 (5)
20.	(North Node)	•						
	Eastbound Left	875	1,217	480	481	120.2 (F)	49.3 (D)	50.9 (D)
	Westbound Left	1250	177	233	701	57.5 (E)	69.8 (E)	208.1 (F)
	Westbound Right	1250	224	233	701	23.5 (C)	60.4 (E)	40.4 (D)
	Northbound Thru	100	178	183	267	12 (B)	16.1 (B)	50.5 (D)
	Southbound Thru	100	151	121	255	37.6 (D)	16.7 (B)	111.3 (F)
	Southbound Right	100						
	Overall					14.3 (B)	43 (D)	78.8 (E)
21.	S Eads Street & 14th Street S							
	Eastbound Left	200		43	45		78.5 (E)	85.4 (F)
	Eastbound Thru	200		43	45		0 (A)	0 (A)
	Eastbound Right	200		42	45		0 (A)	0 (A)
	Westbound Left	150		96	98		49.4 (D)	50.7 (D)
	Westbound Thru	150		96	98		0 (A)	0 (A)
	Westbound Right	150		96	98		95.3 (F)	123 (F)
	Northbound Left	100	Future	219	406	Future	0 (A)	0 (A)
	Northbound Thru	350	Intersection	219	406	Intersection	3.5 (A)	18.4 (B)
	Northbound Right	350		232	414		3.7 (A)	18 (B)
	Southbound Left	100		313	312		68.6 (E)	77.8 (E)
	Southbound Thru	290		313	312		6.3 (A)	8.3 (A)
	Southbound Right	290		316	315		5.8 (A)	7.6 (A)
	Overall						10.1 (B)	19.2 (B)
	S Fern Street & Site						10.1 (2)	10.2 (D)
22.	Driveway							
	Eastbound Left	450			73			68.8 (E)
	Eastbound Thru	450			73			0 (A)
	Eastbound Right	450			73			70.2 (E)
	Westbound Left	150			70			52.1 (D)
	Westbound Thru	150			70			0 (A)
	Westbound Right	150	F. 14:	Fut	70	Future.	F. 15:	65.2 (E)
	Northbound Left	140	Future Intersection	Future Intersection	194	Future Intersection	Future Intersection	64.4 (E)
	Northbound Thru	275			347			28.2 (C)
	Northbound Right	275	1		347			30.2 (C)
	Southbound Left	75			375			29.6 (C)
	Southbound Thru	390			533			45.1 (D)
	Southbound Right	390			537			35.6 (D)
	Overall		1					38.2 (D)

Table 22: PM Vehicular Delay and Maximum Queue Length (2025)

					PM	Peak Hour		
Inte	rsection and Lane Group	Storage Length	Average o	of Maximum Que			ehicular Moveme	nt Delay (sec/veh) vice
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
1.	S Hayes Street & Army Navy Drive				T dtdi 0			Tuturo
	Eastbound Left	260	223	313	399	40.1 (D)	66.6 (E)	74.3 (E)
	Eastbound Thru	450	460	358	525	37.1 (D)	62 (E)	51.1 (D)
	Eastbound Right	450	483	358	525	35.8 (D)	38 (D)	107.3 (F)
	Westbound Left	190	101	162	309	33.7 (C)	74.7 (E)	206.1 (F)
	Westbound Thru	430	239	348	303	32.1 (C)	65.8 (E)	53.9 (D)
	Westbound Right	430	206	162	131	1.1 (A)	1.6 (A)	2.2 (A)
	Northbound Left	200	366	334	281	234 (F)	56.2 (E)	60.8 (E)
	Northbound Thru	750	345	327	364	47.2 (D)	28.3 (C)	35.4 (D)
	Northbound Right	115	208	203	341	13.1 (B)	5.4 (A)	26.8 (C)
	Southbound Left	2050	716	2,911	1,421	37.7 (D)	164.7 (F)	164.9 (F)
	Southbound Thru	1950	716	2,911	1,421	44.4 (D)	42.4 (D)	47.2 (D)
	Southbound Right	1950	274	2,910	1,421	7.9 (A)	25.2 (C)	31 (C)
	Overall					36.4 (D)	45.1 (D)	55 (E)
2.	S Fern Street & Army					55.7 (=)	(=)	(-)
	Navy Drive Eastbound Left	160	218	334	467	33.5 (C)	36.4 (D)	56.4 (E)
	Eastbound Thru	430	303	472	482	20.4 (C)	29.2 (C)	34.4 (C)
	Eastbound Right	180	96	135	225	5 (A)	9.2 (A)	19.3 (B)
	Westbound Left	80	383	402	349	18.2 (B)	87.2 (F)	91 (F)
	Westbound Thru	260	383	402	349	18 (B)	34.8 (C)	26.2 (C)
	Westbound Right	260	388	406	353	24.5 (C)	39.6 (D)	34.4 (C)
	Northbound Left	280	274	273	450	35.5 (D)	45.8 (D)	71.2 (E)
	Northbound Thru	390	140	138	205	25 (C)	28.9 (C)	21.4 (C)
	Northbound Right	80	148	138	86	10.8 (B)	30 (C)	24.4 (C)
	Southbound Left	75	73	171	115	47.6 (D)	40.6 (D)	36.7 (D)
	Southbound Thru	560	174	241	193	24 (C)	41.3 (D)	40.8 (D)
	Southbound Right	560	181	248	204	15.7 (B)	25.9 (C)	14 (B)
	Overall					22.6 (C)	33 (C)	35.4 (D)
3.	Army Navy Drive &					22.0 (0)	33 (5)	00.1 (2)
	Parking Lot Eastbound Left	120			370			25.9 (C)
	Eastbound Thru	260			370			10.9 (B)
	Eastbound Right	225			370			67.9 (E)
	Westbound Thru	230			333			8.4 (A)
	Westbound Right	230			350			9.1 (A)
	Northbound Left	100	Un-		237	Un-		81.3 (F)
	Northbound Thru	100	un- signalized	Unsignalized	237	signalized	Unsignalized	0 (A)
	Northbound Right	100	J. 12.1.200		237	3200		86.6 (F)
	Southbound Left	100			156			74.8 (E)
	Southbound Thru	100			156			0 (A)
	Southbound Right	100			154			27.3 (C)
	Overall							16.5 (B)
4.	S Eads Street & Army				, ,			10.3 (D)
	Navy Drive Eastbound Left	220	354	340	292	59.5 (E)	65 (E)	34.5 (C)
	Eastbound Thru	220	354	338	292	20.7 (C)	11 (B)	15.2 (B)
	Eastbound Right	220	382	334	292	13.8 (B)	13.3 (B)	38.6 (D)
	Lasibouria Rigiti	220	1 302	334	232	1 13.0 (B)	13.3 (B)	JO.0 (D)

		Storage	Avorage	of Maximum Queu		Peak Hour Average of V	ehicular Movemer	
Interse	ection and Lane Group	Length (ft)	Average o	of Maximum Quel	• • • • • • • • • • • • • • • • • • • •		and Level of Serv	rice
		(/	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Westbound Thru	1100	212	196	214	32 (C)	30.8 (C)	48.8 (D)
	Westbound Right	100	212	206	224	30.4 (C)	20.5 (C)	28.9 (C)
	Northbound Left	100	229	335	238	27.4 (C)	26.1 (C)	37.6 (D)
	Northbound Thru	240	325	335	325	31.2 (C)	26.4 (C)	29 (C)
	Northbound Right	240	325	335	325	31.8 (C)	28.3 (C)	27.4 (C)
	Southbound Left	140	331	222	329	24.2 (C)	20.5 (C)	41.3 (D)
	Southbound Thru	140	167	222	329	58.4 (E)	31.2 (C)	54 (D)
	Southbound Right	110	167	222	329	27.3 (C)	5.3 (A)	3.2 (A)
	Overall					6.1 (A)	27.8 (C)	32 (C)
5.	Army Navy Drive &					511 (13)		(-)
, .	110 Ramp							
	Eastbound Thru				0			0.1 (A)
	Westbound Thru	1000	Un-	Unsignalized	649	Un-	Unsignalized	28.9 (C)
	Southbound Right	900	signalized		258	signalized	5.1.0.g.1	10.4 (B)
	Overall							16.6 (B)
6.	S Eads Street & 11th Street S							
	Eastbound Left	200			407			57.8 (E)
	Eastbound Thru	200			407			0 (A)
	Eastbound Right	200			407			94.5 (F)
	Westbound Left	300			99			40.8 (D)
	Westbound Thru	300			99 95			0 (A)
	Westbound Right	300			95 95			56 (E)
	Northbound Left	100	Un-	Unsignalized	93 80	Un-	Unsignalized	21.9 (C)
	Northbound Thru	250	signalized	Urisignalized	345	signalized	Orisignalized	12 (B)
	Northbound Right	250			347			` ,
	Southbound Left	250			336			8.8 (A)
		250						44.1 (D)
	Southbound Thru				336			41.9 (D)
	Southbound Right	25			340			25.4 (C)
	Overall S Hayes Street & 12th							35 (C)
7.	Street S							
	Eastbound Left	450	281	212	190	99.5 (F)	46.2 (D)	64.7 (E)
	Eastbound Thru	450	281	210	234	97.5 (F)	41.7 (D)	57 (E)
	Eastbound Right	65	291	208	232	17.8 (B)	2.2 (A)	2.9 (A)
	Westbound Left	100	302	402	440	43.5 (D)	54.3 (D)	69.3 (E)
	Westbound Thru	620	302	402	440	33.6 (C)	49.1 (D)	67.4 (E)
	Westbound Right	620	313	402	440	19.1 (B)	51.2 (D)	66.9 (E)
	Northbound Left	75	529	282	360	93.1 (F)	76.6 (E)	65.9 (E)
	Northbound Thru	775	529	282	360	44.1 (D)	27.6 (C)	29.2 (C)
	Northbound Right	75	533	286	364	13.8 (B)	13.4 (B)	19 (B)
	Southbound Left	250	606	412	429	78.9 (E)	79 (E)	70.6 (E)
	Southbound Thru	770	607	412	429	35.5 (D)	10.2 (B)	15.8 (B)
	Southbound Right	770	607	412	429	9.5 (A)	9.6 (A)	14.9 (B)
	Overall					43.1 (D)	27.9 (C)	32.1 (C)
3.	S Fern Street & 12th Street S						,	, ,
	Eastbound Thru	640	533	573	537	46.7 (D)	50.3 (D)	59.7 (E)
	Eastbound Right	640	533	583	546	43.8 (D)	45.6 (D)	50.2 (D)
	Westbound Left	75	540	352	368	40.2 (D)	112.8 (F)	95.1 (F)
	Westbound Thru	225	261	352	368	39.2 (D)	46.2 (D)	39.7 (D)
	Westbound Right	225	261	361	368	24.6 (C)	39.3 (D)	42.1 (D)

		0.			PMI	Peak Hour		
Inter	section and Lane Group	Storage Length	Average o	of Maximum Queu	e Length (ft)	Average of V	ehicular Movemer and Level of Serv	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Northbound Left	100	271	372	381	19.5 (B)	27.8 (C)	45.5 (D)
	Northbound Thru	280	324	372	381	21.7 (C)	19.2 (B)	42.9 (D)
	Northbound Right	280	324	372	380	12.8 (B)	17.2 (B)	39.4 (D)
	Southbound Left	130	329	503	195	14 (B)	42.9 (D)	45.2 (D)
	Southbound Thru	275	383	503	434	20.1 (C)	33.6 (C)	31.3 (C)
	Southbound Right	275	383	509	434	15.7 (B)	27.7 (C)	26.8 (C)
	Overall					13.5 (B)	39.9 (D)	42.8 (D)
).	S Elm Street & 12th					10.0 (2)	00.0 (2)	12.0 (2)
, .	Street S							
	Eastbound Thru	225		239	359		6.3 (A)	25.8 (C)
	Eastbound Right	225	Un-	231	361	Un-	4.1 (A)	19 (B)
	Westbound Thru	325	signalized	298	273	signalized	23.4 (C)	14.4 (B)
	Northbound Right	270	3	101	123		14.1 (B)	45.4 (D)
	Overall						13.9 (B)	21.5 (C)
ΙΟ.	S Eads Street & 12th Street S							
	Eastbound Left	150	350	328	389	69.6 (E)	65.4 (E)	127.9 (F)
	Eastbound Thru	320	350	328	389	39.1 (D)	45.2 (D)	60.9 (E)
	Eastbound Right	320	354	328	389	31.4 (C)	48.1 (D)	66.5 (E)
	Westbound Left	200	497	514	606	55.6 (E)	90.4 (F)	244.1 (F)
	Westbound Thru	575	497	514	606	55.1 (E)	65.2 (E)	93.5 (F)
	Westbound Right	575	510	514	606	67.2 (E)	68.1 (E)	96.4 (F)
	Northbound Left	100	369	388	333	19.4 (B)	46.8 (D)	45.4 (D)
	Northbound Thru	270	369	388	333	20.5 (C)	36.4 (D)	49.4 (D) 29.5 (C)
	Northbound Right	100	374	389	66	6.9 (A)	10 (A)	29.3 (C) 14.8 (B)
	Southbound Left					` ,	` ,	` ,
		120	296	337	320	25.4 (C)	62.4 (E)	57.4 (E)
	Southbound Thru	250 250	296	337	351	18.5 (B)	45.3 (D)	42.4 (D)
	Southbound Right Overall		299	343	351 	15.9 (B)	41.4 (D)	37.9 (D)
	12th Street S & Army					35.2 (D)	49.3 (D)	64.9 (E)
11.	Navy Drive							
	Eastbound Thru	575		181	235		32.4 (C)	28.2 (C)
	Eastbound Right	575		192	235		20.4 (C)	29.2 (C)
	Westbound Thru	120		245	247		13.2 (B)	17.2 (B)
	Westbound Right	120		245	247		8.3 (A)	5.9 (A)
	Northbound Left	50		58	58		49.1 (D)	69.9 (E)
	Northbound Thru	50	Un- signalized	58	58	Un- signalized	0 (A)	0 (A)
	Northbound Right	50	Signalized	58	58	Signalized	45.3 (D)	45.5 (D)
	Southbound Left	1000		206	287		38.6 (D)	71.3 (E)
	Southbound Thru	1000		206	287		37 (D)	77.4 (E)
	Southbound Right	1000		206	287		35.4 (D)	95.3 (F)
	Overall						19 (B)	26.6 (C)
12.	S Clark Street/Long Brid	dge Dr &						, ,
	12th Street S	400	404	404	407	242(2)	40.0 /5)	40.4 (5)
	Eastbound Left	120	191	121	187	34.9 (C)	16.8 (B)	19.1 (B)
	Eastbound Thru	120	191	121	187	15 (B)	1.4 (A)	4.4 (A)
	Eastbound Right	120	192	121	187	5.4 (A)	2.6 (A)	2.3 (A)
	Westbound Left	100	43	180	43	28 (C)	73.8 (E)	58.2 (E)
	Westbound Thru	1500	509	1,532	1,370	25.7 (C)	81 (F)	65.8 (E)
	Westbound Right	1500	513	1,543	1,380	23.7 (C)	30.1 (C)	32.6 (C)
	Northbound Left	100	263	397	323	35.8 (D)	92.3 (F)	83.6 (F)
	Northbound Thru	1200	116	397	323	16.2 (B)	59.8 (E)	58.1 (E)

		Storage	Avorago	of Maximum Queu		Peak Hour Average of V	ehicular Movemer	
nters	ection and Lane Group	Length (ft)		1	Mitigated		and Level of Serv	
			Existing	Background	Future	Existing	Background	Future
	Northbound Right	1200	118	402	328	9.4 (A)	48 (D)	43.5 (D)
	Southbound Left	450	177	937	1,151	21.2 (C)	88.5 (F)	158.5 (F)
	Southbound Thru	450	177	937	1,151	17.1 (B)	79.7 (E)	157.8 (F)
	Southbound Right	150	169	971	1,154	11.1 (B)	97.8 (F)	122.3 (F)
	Overall					24.6 (C)	60.8 (E)	62.2 (E)
4.	S Eads Street & 13th Street S							
	Eastbound Left	350		564	940		88.3 (F)	93.1 (F)
	Eastbound Right	350		564	940		73.7 (E)	156.9 (F)
	Northbound Left	150	Un-	434	436	Un-	8.8 (A)	9.6 (A)
	Northbound Thru	300	signalized	434	436	signalized	35.8 (D)	37.9 (D)
	Southbound Thru	280		336	389	g	16.7 (B)	24.6 (C)
	Southbound Right	280		339	392		7.2 (A)	11.4 (B)
	Overall						37.3 (D)	48.5 (D)
6.	S Fern Street & 15th Street S							
	Eastbound Left	130	121	159	167	23.2 (C)	33.1 (C)	48.2 (D)
	Eastbound Thru	630	121	159	167	12.8 (B)	12.3 (B)	23.3 (C)
	Eastbound Right	630	121	161	168	9.4 (A)	9.7 (A)	18.3 (B)
	Westbound Left	120	297	363	170	16.5 (B)	55.5 (E)	8.3 (A)
	Westbound Thru	260	297	363	170	9.9 (A)	44.2 (D)	5.9 (A)
	Westbound Right	260	300	367	171	10.1 (B)	40.3 (D)	7.9 (A)
	Northbound Left	750	203	252	350	25.7 (C)	22.2 (C)	57.6 (E)
	Northbound Thru	750	203	252	350	18.5 (B)	19.3 (B)	54.6 (D)
	Northbound Right	75	209	258	355	8.9 (A)	6.3 (A)	19 (B)
	Southbound Left	160	365	343	409	21.9 (C)	21.9 (C)	40.1 (D)
	Southbound Thru	300	365	343	409	15.3 (B)	16 (B)	31.6 (C)
	Southbound Right	300	379	357	415	11.7 (B)	12.5 (B)	25.2 (C)
	Overall					16.8 (B)	28.4 (C)	22.3 (C)
7.	15th Street S & S Elm Street							
	Eastbound Left	60		193	166		2.7 (A)	7.3 (A)
	Eastbound Thru	270		193	166		5.1 (A)	7.8 (A)
	Westbound Thru	300	Un-	164	173	Un-	7.6 (A)	2.8 (A)
	Westbound Right	300	signalized	168	177	signalized	3.5 (A)	2.6 (A)
	Southbound Left	250		146	140		56.8 (E)	45.9 (D)
	Southbound Right	250		149	143		18.3 (B)	12.4 (B)
8.	S Eads Street & 15th						10.1 (B)	7 (A)
	Street S Eastbound Left	170	162	267	305	16 5 (D)	101 4 (E)	46.1 (D)
	Eastbound Left Eastbound Thru	300	244	326	305 412	46.5 (D)	101.4 (F)	46.1 (D)
	Eastbound Thru Eastbound Right	300	244 227	326	412	20.5 (C)	18.7 (B)	38.7 (D)
	Westbound Left	300	395	326 474	406	9.1 (A)	23.4 (C)	42.8 (D)
	Westbound Thru	300	395	474	406 406	43.8 (D)	24.4 (C)	38.1 (D)
	Westbound Right	300	395 408	474	406 406	20.8 (C)	36.6 (D)	34.1 (C)
	ŭ					19.1 (B)	105.5 (F)	46.7 (D)
	Northbound Left	130 760	193	882	785 785	21.6 (C)	78.6 (E)	65.7 (E)
	Northbound Thru	760 130	193	882	785 108	13.1 (B)	88.6 (F)	82.5 (F)
	Northbound Right		62	378	108 472	5.7 (A)	40.2 (D)	31.7 (C)
	Southbound Left	250	212	474	472	22.9 (C)	83.8 (F)	107.2 (F)
	Southbound Thru	300	278	474	472	17.7 (B)	67.7 (E)	49.6 (D)

					PMJ	Peak Hour		
Inter	section and Lane Group	Storage Length	Average o	f Maximum Queu			ehicular Movemer	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Overall					24 (C)	54.7 (D)	49.3 (D)
19.		amps						
	` '	1000						
		Average of Maximum Queue Length (ft)						
	•			201		20.6 (C)	20 (C)	6.1 (A)
						` '	` '	` ,
						` '		6.4 (A) 4 (A)
	· ·						` '	10.7 (B)
	Southbound Thru					` '	` '	10.7 (B) 12.2 (B)
	Overall							7 (A)
		amps				14.7 (D)	9.4 (٨)	<i>I</i> (A)
20.	(North Node)							
	Eastbound Left	875						
	Westbound Left		270	211	551	24.1 (C)	33.2 (C)	88.7 (F)
	Westbound Right	1250	339	211	551	26.3 (C)	25.9 (C)	51.5 (D)
	Northbound Thru	100	179	186	205	8.6 (A)	5.7 (A)	7.4 (A)
	Southbound Thru	100	217		193	` '	4.8 (A)	12.3 (B)
	Southbound Right	100	139	154	190	0.7 (A)	0.3 (A)	0.5 (A)
	Overall					7.7 (A)	6.7 (A)	16.4 (B)
21.	S Eads Street & 14th Street S							
	Eastbound Left	200		124	164		73.3 (F)	113.1 (F)
	Eastbound Thru						` '	0 (A)
		200					1 1	122.3 (F)
	Westbound Left							211.5 (F)
	Westbound Thru						` '	0 (A)
							1 1	216.9 (F)
			Future			Future	` '	
			Intersection			Intersection	1 1	0 (A)
							` ′	27.6 (C)
	· ·							20.7 (C)
							` '	96.7 (F)
							` ′	32.9 (C)
							1 1	20.9 (C)
	Overall S Fern Street & Site						41.7 (D)	42.6 (D)
22.	Driveway							
	Eastbound Left	450	1		540			353 (F)
	Eastbound Thru	450			540			0 (A)
	Eastbound Right	450	1		540			362.6 (F)
	Westbound Left	150	1		256			51.7 (D)
	Westbound Thru	150	1		256			0 (A)
	Westbound Right		1		256			65.1 (E)
	Northbound Left	140			6			28 (C)
	Northbound Thru		intersection	iritersection		mersection	intersection	25.5 (C)
	Northbound Right	275	1					21.9 (C)
	Southbound Left							31.9 (C)
	Southbound Thru							34.4 (C)
	Southbound Right							14.1 (B)
	Overall							68 (E)

Table 23: Bicycle and Pedestrian Delay (2025)

		Average	e Pedestria					Averag		Delay (se		
Intersection/	Existin	ıg (2020)		ground 025)	_	d Future (25)	Existin	g (2020)		ground 025)	_	gated (2025)
Approach	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM
	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peal
1. Army Navy Drive												
and S Hayes Street Overall			69.0	65.3	76.8	63.7			81.9	51.2	52.0	55.6
Eastbound	46.5	49.9	69.6	65.1	76.5	64.0			86.6	43.3	52.3	57.6
Westbound	0.0	0.2	57.9	67.8	96.9	50.4			79.0	63.4	51.7	53.9
Northbound									79.0			
Southbound												
2. Army Navy Drive												
and S Fern Street												
Overall			65.5	62.5	65.3	65.0			10.3	6.4	14.0	15.9
Eastbound	49.4	46.9	67.0	65.6	66.6	66.1			6.6	4.2	23.7	21.
Westbound	49.6	47.2	65.5	58.6	64.8	65.1			12.5	9.2	4.5	12.1
Northbound	51.3	50.7	66.8	60.9	64.5	64.4			12.5	9.2	15.2	14.4
Southbound	50.0	49.5	64.3	63.1	65.2	64.5					15.2	14.4
3. Army Navy Drive	30.0	+3.3	04.5	JJ. I	00.2	04.0		===				
and Parking Lot												
Overall					60.8	62.3					1.9	5.2
Eastbound					65.8	64.6					4.2	7.9
Westbound					32.1	49.3					0.8	0.2
Northbound												
Southbound												
4. Army Navy Drive												
and S Eads Street												
Overall			70.2	69.0	66.5	67.2			26.3	10.4	24.4	20.2
Eastbound	52.4	51.1	89.9	75.6	68.5	67.6			22.2	2.3	12.0	14.0
Westbound	50.4	50.9	67.7	63.8	67.2	65.9			35.2	3.2	29.4	46.7
Northbound	49.6	51.8	66.2	68.9	63.8	68.9			24.0	26.4	26.6	11.9
Southbound	50.7	49.4	63.7	70.7	65.8	68.3						
5. Army Navy Drive					.,	. , ,						
and 110 Ramp					Ur	nsignalized	Intersection	on				
6. S Eads Street and												
11th Street S/Site												
Driveway												
Overall					65.9	63.6					4.7	8.0
Eastbound					65.1	65.1						
Westbound					63.6	64.1						
Northbound					66.1	64.0					0.5	3.7
Southbound					67.6	62.0					8.2	12.5
7. 12 th Street S and												
S Hayes Street			60.4	04.5	04.5	05.0						
Overall		40.7	63.4	64.0	64.0	65.3						
Eastbound	51.6	49.7	63.3	64.6	64.1	64.9						
Westbound	49.7	50.7	63.2	60.8	64.9	66.0						
Northbound	50.6	48.5	65.1	63.0	64.4	64.1						
Southbound	0.0	0.0	0.0	0.0	62.3	66.1						
8. 12 th Street S and												
S Fern Street			64.2	64.6	64.6	64.2						
Overall	 25 0	24.4	64.3	64.6	64.6	64.2						
Eastbound	35.0	34.4	65.1	64.6	64.5	64.5						
Westbound	34.9	34.5	62.3	65.1	64.5	64.1						

		Average	Pedestria	an Delay (s	sec/ped)	Average Bicycle Delay (sec/bike)						
Intersection/	Existin	g (2020)		ground 025)	Mitigate (20		Existing	g (2020)		round 25)		gated (2025)
Approach	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak
Northbound	34.6	34.3	62.8	65.4	64.0	63.7						
Southbound	34.9	34.2	64.4	64.4	65.3	64.0						
9. 12 th Street S and S Elm Street												
Overall			24.6	70.0	36.0	67.4						
Eastbound			3.3	70.2	3.5	69.1						
Westbound												
Northbound			65.0	69.4	64.6	65.6						
10. 12 th Street S and S Eads Street												
Overall			64.7	64.9	64.8	65.9			14.9	25.1	17.7	27.5
Eastbound	50.0	34.9	64.5	66.0	64.2	65.9						
Westbound	48.3	36.0	64.4	65.0	65.1	66.2						
Northbound	51.0	34.9	64.3	63.5	64.7	65.1			8.3	35.3	17.3	35.9
Southbound	25.3	34.7	68.0	63.7	65.7	66.2			22.6	20.2	18.5	24.2
11. 12 th Street S and												
Army Navy Drive Overall			65.4	63.9	65.7	64.4			39.4	50.4	33.1	52.6
Eastbound			65.4 65.1	65.6	65.3	65.4			3 9.4 34.8	30.4 49.7	26.0	52.7
Westbound			65.7	63.6	65.8	64.0			43.7	50.9	35.9	52.7 52.5
Northbound												
Southbound			0.0	0.0 65.2	0.0	0.0 64.5						
12. 12 th Street and			0.0	00.2	0.0	04.5						
Long Bridge Drive/S Clark Street												
Overall			63.5	64.0	63.9	64.8			43.4	41.0	44.2	41.5
Eastbound	34.8	34.3	64.3	63.7	64.2	64.9						
Westbound	34.3	34.8	63.0	64.4	64.1	64.8						
Northbound	35.5	34.7	63.1	61.8	62.8	64.1			32.7	24.0	32.7	28.0
Southbound	31.7	35.7	63.9	68.1	64.2	66.6			57.6	54.9	57.3	54.1
13. S Fern Street and 13 th Street S					Ur	signalized	Intersection	on				
14. 13 th Street S and												
S Eads Street			64.0	04.4	64.4	60.4			0.0	0.0	0.5	0.0
Overall			61.6	31.1	61.1	62.4			0.6	2.0	0.5	2.0
Eastbound Northbound			69.4	39.4	67.6	65.1 			0.1	0.0	0.2	0.4
Southbound			52.2	 26.5	 58.8	61.6			0.1 1.1	0.0 3.7	0.2 1.3	0.4 2.8
15. S Fern Street and 14 th Street S			53.2	20.5		signalized	Intersection		1.1	3.1	1.3	2.0
16. 15 th Street S and S Fern Street												
Overall			67.1	64.6	65.9	65.0						
Eastbound	34.8	35.2	68.4	63.0	64.9	64.7						
Westbound	38.0	34.5	65.7	64.5	63.0	65.9						
Northbound	36.8	34.8	67.7	65.7	68.2	64.6						
Southbound	35.2	34.6	66.1	64.1	66.1	65.2						
17. 15 th Street S and S Elm Street												
			62.6	51.4	65.8	63.7						
Overall			02.0	J1. T	03.0	03.7						

		Average	e Pedestria	ın Delay (s	sec/ped)			Averag	e Bicycle	Delay (se	c/bike)	
Intersection/ Approach	Existin	g (2020)		round 25)		d Future 25)	Existin	g (2020)	Backg (20	round 25)	Mitig Future	
Арргоасп	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM
	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak
Westbound			63.0	45.0	66.3	63.6						
Southbound			61.4	75.5	61.4	65.2						
18. 15 th Street S and												
S Eads Street												
Overall			127.6	127.4	128.1	126.4			38.1	35.3	23.7	21.2
Eastbound	33.6	35.2	64.6	64.9	66.0	64.6						
Westbound	32.7	35.8	65.0	64.2	65.8	65.0						
Northbound	39.1	34.8	186.4	185.5	185.7	185.8			37.5	43.5	27.2	33.2
Southbound	35.3	34.4	190.3	186.9	189.7	188.3			38.5	24.8	18.8	9.9
19. S Eads Street and I-395 HOT Lanes (South Node)												
Overall												
Eastbound												
Northbound												
Southbound												
20. S Eads Street and I-395 HOT												
Lanes (North Node)												
Overall												
Eastbound												
Westbound												
Northbound												
Southbound												
21. 14 th Street S and S Eads Street												
Overall			58.5	65.7	58.6	66.7			3.3	2.1	4.3	6.6
Eastbound												
Westbound			65.3	65.9	66.4	65.1						
Northbound			52.6	65.6	51.4	68.5			0.7	1.8	0.5	2.5
Southbound			60.5	65.3	66.5	64.3			6.2	2.6	12.1	9.9
22. S Fern Street and 11 th Street												
S/Site Driveway												
Overall					64.9	65.6					16.0	18.0
Eastbound					66.7	64.9						
Westbound					65.7	65.0						
Northbound					62.7	66.5					13.3	18.2
Southbound					63.7	65.0					17.9	17.8

2031 Analysis Results

Simulated Vehicular Volumes

Vehicular volume results are used to help identify each scenario's ability to process vehicular volumes on a macro and micro level. These results are expressed as the number of vehicles denied entry into network, or as individual link vehicular volumes (throughput).

Simulated individual link volumes results, also known as throughput results, for 2031 Background and 2031 Mitigated Future analysis scenarios are included in the Technical Appendix.

GEH Statistic

The GEH statistic is a formula used in traffic modeling to compare two sets of traffic volumes and indicate whether the model processes enough vehicles in the network to be considered valid. A GEH value that is less than 5 indicates a good fit between the input and simulated volumes. A GEH value between 5 and 10 may require further investigation. A GEH value that is greater than 10 indicates an error in the model.

Under 2031 Mitigated Future conditions, most movements operate at acceptable GEH values (GEH value < 5); however, the three (3) intersections along 15th Street S, at S Eads Street, S Elm Street, and S Fern Street, have one or more movements that operate above the acceptable GEH value (GEH > 5) in the afternoon peak hour. This is primarily due to vehicles being metered by the new at-grade Richmond Highway and 15th Street S intersection. Based on the VISSIM simulation, Richmond Highway experiences congestion as a result of the intersection at 15th Street S coming down to grade. This intersection will be studied further as part of Phase 2 of the Route 1 Multimodal Improvements Study, which aims to further analyze the recommended alternative and identify TDM measures to mitigate future congestion. No additional site-generated trips were assumed at this intersection compared to 2025.

Vehicles Entering the Network

The number of vehicles entered into the network for each of the analysis scenarios is shown in Table 24. The percentage of vehicles able to enter the network for the 2031 Mitigated Future scenario was evaluated. The proposed mitigations included in the 2031 Mitigated Future scenario, discussed in a later section of this chapter, will create additional capacity at critical locations to allow more vehicles to be processed through the network. The proposed development adds an additional 1,798 vehicles

(+5.09%) in the morning peak period and 1,752 vehicles (+4.72%) in the afternoon peak period, increasing the total number of vehicles that needs to be processed through the network. With the recommended mitigations, under the 2031 Mitigated Future scenario, the total number of vehicles processed increases by 1,570 vehicles (+4.96%) and 1,224 vehicles (+3.51%) in the morning and afternoon peak period, respectively.

Simulated Vehicular Travel Times

Vehicular travel time is the amount of time it takes for a vehicle to travel from point A to point B. It is a direct reflection of motorist experience. The two (2) vehicular travel times that were analyzed as part of the *VISSIM* microsimulation analysis were:

- Eastbound Army Navy Drive from S Joyce Street to 12th Street S
- Westbound Army Navy Drive from 12th Street S to S Joyce Street

Simulated travel time results for the two (2) vehicular travel time measurement segments that were analyzed using *VISSIM* in the 2031 Background and 2031 Mitigated Future analysis scenarios are shown in Table 25 for the AM peak and Table 26 for the PM Peak. The travel time along some segments reflect additional local traffic as well as adjustments to the corridor to accommodate a new signal. The 2031 Mitigated Future analysis includes a new signal at the Army Navy Drive and Parking Lot/Site Driveway intersection where the 2031 Background analysis does not.

Simulated Transit Travel Times

Transit travel time is the amount of time it takes for a transit vehicle to travel from point A to point B. It is a direct reflection of motorist experience. The two (2) transit travel times that were analyzed as part of the *VISSIM* microsimulation analysis were:

- Eastbound 12th Street S from S Hayes Street to Long Bridge Drive
- Westbound 12th Street S from Long Bridge Drive to S Hayes Street

Simulated travel time results for the two (2) transit travel time measurement segments that were analyzed using *VISSIM* in the 2031 Background and 2031 Mitigated Future analysis scenarios are shown in Table 25 for the AM peak and Table 26 for the PM Peak. The travel time along some segments reflect additional local traffic as well as adjustments to the corridor to accommodate a new signal.

Due to capacity constraints elsewhere in the network, volumes have been re-routed in PM peak hour under 2031 Mitigated Future conditions. Therefore, the travel times in 2031 Mitigated Future conditions are improved compared to 2031 Background conditions.

Simulated Vehicular Delay

Simulated vehicular delay results show the difference between the actual vehicle travel time due to stops at a signalized intersection (control delay) and is measured in seconds of delay per vehicle. Tables showing the simulated vehicular delay for study area intersections for the 2020 Existing, 2031 Background, and 2031 Mitigated Future analysis scenarios are included in the Technical Appendix and shown in Table 27 and Table 28. At the majority of intersections in the network, the vehicular delay results under the 2031 Mitigated Future scenario, with added site traffic and recommended mitigation measures, are comparable to that under the 2031 Background scenario. A comparison of the level of service (LOS) between scenarios is provided in Figure 75 and Figure 76 for Existing, 2031 Background, and 2031 Mitigated Future scenarios.

It is important to note that VISSIM is a microscopic analysis rather than a macroscopic analysis. Mitigation measures are recommended such that the results are comparable or better than the Background conditions throughout the network. The recommended mitigation measures are in place to address targeted issues at specific, as well as increase the vehicular throughput of the overall network, particularly at exterior intersections that are responsible for metering vehicles entering the network. Due to the increased number of vehicles being processed in the network compared to Background conditions, there may be locations where delays are higher than that seen under Background conditions.

2031 Background

Based on the VISSIM results, the majority of intersections operate at acceptable levels of service (LOS E or better) in the 2031 Background scenario; however, three (3) intersections have one or more approach that operate beyond acceptable thresholds in one or more peak hour:

- 12th Street S & S Clark Street/Long Bridge Drive PM
- S Eads Street & I-395 HOT Lanes (South Node) AM
- S Eads Street & 14th Street S PM

2031 Mitigated Future

Based on the VISSIM results, the majority of intersections operate at acceptable levels of service (LOS E or better) in the 2031 Mitigated Future scenario; however, eight (8) intersections have one or more approach that operate beyond acceptable thresholds in one or more peak hour:

- Army Navy Drive & S Hayes Street PM
- Army Navy Drive & Parking Lot/Site Driveway PM
- S Eads Street & 12th Street S AM/PM
- 12th Street S & S Clark Street/Long Bridge Drive PM
- S Eads Street & I-395 HOT Lanes (South Node) AM
- S Eads Street & I-395 HOT Lanes (North Node) AM
- S Eads Street & 14th Street S AM/PM
- S Fern Street & 11th Street S/Site Driveway PM

Most vehicular capacity concerns in the study area can be alleviated through signal timing changes that adapt to changes in volume patterns, but at some locations, operational changes alone cannot mitigate future delays. A Transportation Management Plan (TMP) will be provided for the project based on the County's requirements, and a framework for a TMP is included in this report, to further reduce vehicular trips generated by the proposed development during peak period travel times.

Simulated Bicycle and Pedestrian Delay

Simulated intersection delay results show the difference between the actual pedestrian/bicycle travel time due to stops at a signalized intersection (control delay) and is measured in seconds of delay per pedestrian/bicycle. For example, a bicycle or pedestrian may experience roughly one minute of wait time at a signalized intersection due to longer cycle lengths or adjustments to signal timings to accommodate additional traffic on the roadway. Tables showing the simulated bicycle and pedestrian delay for study area intersections for the 2031 Background and 2031 Mitigated Future analysis scenarios are included in the Technical Appendix and shown in Table 29. Note that a number of movements do not a report bicycle delays (i.e., along 12th Street S where sharrows are planned). Bicycle delay is reported for the bicycle facilities included in the VISSIM model, as agreed upon during the scoping process. Analyzed bicycle facilities include the cycle track along the south side of Army Navy Drive between S Joyce Street and 12th Street S, protected bicycle lanes along S Eads Street between Army Navy Drive and

15th Street S, and protected bicycle lanes along S Fern Street between Army Navy Drive and 12th Street S.

The bicycle and pedestrian delay results under the 2031 Mitigated Future scenario, with added site traffic and recommended mitigation measures, are comparable to that under the 2031 Background scenario.

Evaluation of Recommended Mitigations

Based on the results of the VISSIM microsimulation analysis, the recommended mitigation measures for 2031 are consistent with that of 2025 (Detailed in Table 1 and summarized in Figure 1). Tables showing the simulated delay and maximum queues for study area intersections for the 2031 Background and 2031 Mitigated Future analysis scenarios are included in the Technical Appendix. In addition to the recommended mitigation measures, the analysis includes protected northbound and southbound bike lanes along S Fern Street and S Eads Street between Army Navy Drive and 12th Street S.

Table 24: Number Vehicles Entered into Network (2031)

	Backgrou	ınd (2031)	Mitigated Future (2031)		
	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour	
Total Vehicle Input (veh/2 hrs)	35,318	37,092	37,120	38,844	
Number of Vehicles Entered into Network (veh/2 hrs)	31,642	34,913	33,212	36,137	
Percent Vehicles Entered (%)	89.59%	94.13%	89.47%	93.03%	

Table 25: AM Peak Hour Simulated Travel Time Results (2031)

		Travel Time (sec	;)	Difference*
Travel Time Segment	Existing (2020)	Background (2031)	Mitigated Future (2031)	Difference* (sec)
Vehicular Travel Time				
EB Army Navy Dr from S Joyce St to 12 th St S	339	177	225	+48
WB Army Navy Dr from 12 th St S to S Joyce St	159	201	200	-1
Transit Travel Time	<u>.</u>			
EB 12 th St from S Hayes St to Long Bridge Dr		182	213	+31
WB 12 th St from Long Bridge Dr to S Hayes St		263	180	-83

^{*} Difference from Background (2031) scenario

Table 26: PM Peak Hour Simulated Travel Time Results (2031)

	Travel Time (sec)						
Travel Time Segment	Existing (2020)	Background (2031)	Mitigated Future (2031)	Difference* (sec)			
Vehicular Travel Time							
EB Army Navy Dr from S Joyce St to 12 th St S	178	245	293	+48			
WB Army Navy Dr from 12 th St S to S Joyce St	185	255	270	+15			
Transit Travel Time							
EB 12 th St S from S Hayes St to Long Bridge Dr		240	181	-59			
WB 12 th St S from Long Bridge Dr to S Hayes St		269	167	-102			

^{*} Difference from Background (2031) scenario




Figure 75: AM Peak Hour Level of Service Comparison by Scenario (2031)




Figure 76: PM Peak Hour Level of Service Comparison by Scenario (2031)

	e 27: AM Vehicular Delay					Peak Hour		
Inte	rsection and Lane Group	Storage Length	Average o	of Maximum Que			ehicular Moveme	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
1.	S Hayes Street &				ruture			ratare
	Army Navy Drive	260	0.4	104	110	20.8 (C)	92 F (F)	92 G (F)
	Eastbound Left Eastbound Thru	260	84	104	110	30.8 (C)	82.5 (F)	82.6 (F)
		450	232	236	275	36 (D)	53.9 (D)	51.7 (D)
	Eastbound Right	450	256	236	275	32.1 (C)	47.8 (D)	54 (D)
	Westbound Left	190	116	294	185	24.9 (C)	181 (F)	80.8 (F)
	Westbound Thru	430	136 58	166 27	163	35.7 (D)	41 (D)	37.6 (D)
	Westbound Right Northbound Left	430	133	190	16 124	0.5 (A)	0.9 (A)	0.6 (A)
	Northbound Left Northbound Thru	200 750	153	229	314	47 (D)	67.8 (E) 61.1 (E)	70.6 (E)
				-	_	56.8 (E)	` '	63.2 (E)
	Northbound Right	115 2050	99	238	149	9 (A)	66.7 (E)	17 (B)
	Southbound Left		952	3,781	2,708	52.7 (D)	132.5 (F)	110 (F)
	Southbound Thru	1950	952	3,781	2,708	33.8 (C)	31.7 (C)	51.8 (D)
	Southbound Right	1950	353	3,780	2,705	8.3 (A)	17.4 (B)	34 (C)
	Overall S Fern Street & Army					32.3 (C)	50.4 (D)	55.9 (E)
2.	Navy Drive							
	Eastbound Left	160	156	112	123	26.8 (C)	30.6 (C)	30.3 (C)
	Eastbound Thru	430	421	443	591	26.5 (C)	41.1 (D)	40 (D)
	Eastbound Right	180	153	318	549	6.2 (A)	47.1 (D)	42.8 (D)
	Westbound Left	80	312	304	285	52.6 (D)	96.2 (F)	125.6 (F)
	Westbound Thru	260	312	304	285	21.1 (C)	27.7 (C)	8 (A)
	Westbound Right	260	317	309	288	17.2 (B)	27.2 (C)	8.5 (A)
	Northbound Left	280	231	221	186	45.8 (D)	22.6 (C)	49.2 (D)
	Northbound Thru	390	67	56	61	27.5 (C)	9.5 (A)	24.1 (C)
	Northbound Right	80	75	56	72	7.5 (A)	9.7 (A)	29.9 (C)
	Southbound Left	75	185	256	387	31.8 (C)	45 (D)	52.4 (D)
	Southbound Thru	560	208	278	431	27 (C)	45.6 (D)	55.8 (E)
	Southbound Right	560	215	285	430	17.4 (B)	32.9 (C)	58.7 (E)
	Overall					26.1 (C)	37.7 (D)	40.3 (D)
_	Army Navy Drive &					==== (=)	J (=)	(=)
3.	Parking Lot							
	Eastbound Left	120			336			3.5 (A)
	Eastbound Thru	260			336			2.3 (A)
	Eastbound Right	225			336			62.9 (E)
	Westbound Thru	230			171			3 (A)
	Westbound Right	230			188			4.5 (A)
	Northbound Left	100	Un-	Unsignalized	86	Un-	Unsignalized	74.1 (E)
	Northbound Thru	100	signalized	oneignam_cu	89	signalized	oneignazea	0 (A)
	Northbound Right	100			86			74.2 (E)
	Southbound Left	100			51			71.6 (E)
	Southbound Thru	100			51			0 (A)
	Southbound Right	100			56			15.9 (B)
	Overall							6.3 (A)
4.	S Eads Street & Army Navy Drive							
	Eastbound Left	220	332	287	237	24.2 (C)	21.9 (C)	16.8 (B)
	Eastbound Thru	220	331	286	238	16.7 (B)	9.1 (A)	9.2 (A)
	Eastbound Right	220	359	272	238	7.9 (A)	20 (B)	14.9 (B)
	Westbound Thru	1100	181	143	181	48.9 (D)	36.1 (D)	55.7 (E)
	Westbound Right	100	181	153	190	30.6 (C)	11.5 (B)	17.3 (B)

Inte	continuoud and Comme	Storage	Average o	f Maximum Queu		Peak Hour Average of V	ehicular Movemen	
Inter	section and Lane Group	Length (ft)			Mitigated		and Level of Serv	rice Mitigated
			Existing	Background	Future	Existing	Background	Future
	Northbound Left	100	191	317	301	18 (B)	29 (C)	72.9 (E)
	Northbound Thru	240	299	317	251	35.4 (D)	23.9 (C)	13.9 (B)
	Northbound Right	240	299	317	251	32.1 (C)	25.1 (C)	11.2 (B)
	Southbound Left	140	302	351	361	32.1 (C)	34.6 (C)	26.4 (C)
	Southbound Thru	140	298	351	361	30.2 (C)	39.6 (D)	40.6 (D)
	Southbound Right	110	298	351	371	32.9 (C)	19.1 (B)	7.2 (A)
	Overall					6.3 (A)	24.7 (C)	25.5 (C)
5.	Army Navy Drive &							
	110 Ramp Eastbound Thru				0			0.1 (A)
	Westbound Thru	1000	1.1-		85	1.1-		` '
			Un- signalized	Unsignalized	0	Un- signalized	Unsignalized	2.4 (A)
	Southbound Right Overall	900	Signalized			Signalized		2.1 (A)
	S Eads Street & 11th							1.1 (A)
6.	Street S							
	Eastbound Left	200			105			54.2 (D)
	Eastbound Thru	200			105			0 (A)
	Eastbound Right	200			105			54 (D)
	Westbound Left	300			112			60.7 (E)
	Westbound Thru	300			112			0 (A)
	Westbound Right	300			112			57.6 (E)
	Northbound Left	100	Un-	Unsignalized	266	Un-	Unsignalized	18.6 (B)
	Northbound Thru	250	signalized	onoignam20a	232	signalized	onorginanzoa	8 (A)
	Northbound Right	250			235			5.9 (A)
	Southbound Left	250			368			9.8 (A)
	Southbound Thru	250			368			10.3 (B)
	Southbound Right	25			364			6.2 (A)
	Overall							13.9 (B)
7.	S Hayes Street & 12th Street S							10.0 (2)
	Eastbound Left	450	95	153	134	30.3 (C)	50.2 (D)	51.6 (D)
	Eastbound Thru	450	95	153	134	27.8 (C)	47.3 (D)	43.9 (D)
	Eastbound Right	65	94	151	132	5.3 (A)	46.3 (D)	49.9 (D)
	Westbound Left	100	161	184	204	31.6 (C)	40.2 (D)	56.1 (E)
	Westbound Thru	620	161	184	204	27.8 (C)	39.8 (D)	52 (D)
	Westbound Right	620	171	184	204	12.5 (B)	40.2 (D)	55.7 (E)
	Northbound Left	75	125	147	177	59.2 (E)	77.5 (E)	77.3 (E)
	Northbound Thru	775	125	147	177	21.1 (C)	19.9 (B)	26.6 (C)
	Northbound Right	75	129	150	181	5.8 (A)	9.1 (A)	12.3 (B)
	Southbound Left	250	499	496	494	71 (E)	63.9 (E)	68.3 (E)
	Southbound Thru	770	499	496	494	7.1 (A)	11.9 (B)	13.4 (B)
	Southbound Right	770	506	496	494	1.9 (A)	13.7 (B)	14.2 (B)
	Overall					22.9 (C)	26.7 (C)	30.7 (C)
3.	S Fern Street & 12th Street S							,
	Eastbound Thru	640	373	431	606	31.4 (C)	10.6 (B)	33.4 (C)
	Eastbound Right	640	373	440	615	28.6 (C)	7.8 (A)	31.7 (C)
	Westbound Left	75	379	221	232	26 (C)	60.3 (E)	87.7 (F)
	Westbound Thru	225	126	221	236	31.7 (C)	17.7 (B)	5.3 (A)
	Westbound Right	225	126	230	235	19.3 (B)	11.6 (B)	10.7 (B)
	Northbound Left	100	135	406	433	11.5 (B)	37.9 (D)	43.7 (D)
	Northbound Thru	280	257	373	391	21 (C)	27.3 (C)	52.2 (D)

Intern		Storage	Average	of Maximum Queu		Peak Hour Average of V	/ehicular Moveme	
Inters	section and Lane Group	Length (ft)		<u> </u>	Mitigated		and Level of Ser	vice Mitigated
			Existing	Background	Future	Existing	Background	Future
	Northbound Right	280	257	372	390	10.6 (B)	23.9 (C)	50 (D)
	Southbound Left	130	257	526	310	10.1 (B)	83.8 (F)	52 (D)
	Southbound Thru	275	415	526	430	19.3 (B)	74.2 (E)	20.1 (C)
	Southbound Right	275	415	533	430	15.5 (B)	71.1 (E)	17.2 (B)
	Overall 0.51					14 (B)	37.4 (D)	38.7 (D)
) .	S Elm Street & 12th Street S							
	Eastbound Thru	225		393	361		16.5 (B)	19.4 (B)
	Eastbound Right	225		386	363		10.5 (B)	15 (B)
	Westbound Thru	325	Un-	125	37	Un-	6.4 (A)	0.9 (A)
	Northbound Right	270	signalized	90	83	signalized	31.1 (C)	42.5 (D)
	Overall						14.2 (B)	15.4 (B)
10.	S Eads Street & 12th Street S						, ,	
	Eastbound Left	150	413	373	382	38.3 (D)	98.6 (F)	104.8 (F)
	Eastbound Thru	320	413	373	382	40.4 (D)	59.5 (E)	68 (E)
	Eastbound Right	320	417	373	382	36.8 (D)	62.2 (E)	70.3 (E)
	Westbound Left	200	231	202	404	63.7 (E)	94.3 (F)	97 (F)
	Westbound Thru	575	231	202	404	33.8 (C)	28.9 (C)	81.6 (F)
	Westbound Right	575	231	202	404	38.4 (D)	32.9 (C)	81.8 (F)
	Northbound Left	100	195	183	359	17.6 (B)	24.9 (C)	31.5 (C)
	Northbound Thru	270	195	183	359	11.2 (B)	13.6 (B)	28.3 (C)
	Northbound Right	100	199	184	285	10.3 (B)	7.2 (A)	11 (B)
	Southbound Left	120	343	350	305	20.5 (C)	32.3 (C)	32.7 (C)
	Southbound Thru	250	343	350	284	19.1 (B)	29.8 (C)	14.4 (B)
	Southbound Right	250	342	355	283	18.2 (B)	28.5 (C)	11.8 (B)
	Overall					31 (C)	37.1 (D)	42.3 (D)
1.	12th Street S & Army Navy Drive							
	Eastbound Thru	575		609	658		25.6 (C)	28.5 (C)
	Eastbound Right	575		620	658		21.4 (C)	34.7 (C)
	Westbound Thru	120		216	238		13.6 (B)	17 (B)
	Westbound Right	120		216	238		13.6 (B)	13.7 (B)
	Northbound Left	50	11-	58	60	1.100	0 (A)	0 (A)
	Northbound Thru	50	Un- signalized	58	60	Un- signalized	71.7 (E)	69 (E)
	Northbound Right	50	oigiiazoa	58	60	oignan20a	66.2 (E)	55.1 (E)
	Southbound Left	1000		286	289		47.7 (D)	60.9 (E)
	Southbound Thru	1000		286	289		0 (A)	0 (A)
	Southbound Right	1000		286	289		45.4 (D)	64.4 (E)
	Overall						28.6 (C)	33.7 (C)
12.	S Clark Street/Long Brid 12th Street S	dge Dr &						
	Eastbound Left	120	259	223	210	23 (C)	4.8 (A)	6.5 (A)
	Eastbound Thru	120	259	223	210	13.5 (B)	2.3 (A)	2.8 (A)
	Eastbound Right	120	260	223	210	7.2 (A)	2.8 (A)	3.2 (A)
	Westbound Left	100	64	81	81	15.3 (B)	22.7 (C)	20 (B)
	Westbound Thru	1500	365	250	298	13.5 (B)	26.7 (C)	28.7 (C)
	Westbound Right	1500	368	261	309	13.2 (B)	20.4 (C)	23.6 (C)
	Northbound Left	100	86	116	133	26.7 (C)	61.7 (E)	62.3 (E)
	Northbound Thru	1200	67	116	133	20.6 (C)	34.6 (C)	45.8 (D)
	Northbound Right	1200	69	121	138	10.4 (B)	16.5 (B)	18.3 (B)
	Southbound Left	450	195	463	727	24 (C)	55.2 (E)	71.9 (E)

					AM	Peak Hour		
Inter	section and Lane Group	Storage Length	Average o	of Maximum Queu	ıe Length (ft)	Average of V	ehicular Movemer and Level of Serv	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Southbound Thru	450	195	463	727	22.1 (C)	52.7 (D)	65.6 (E)
	Southbound Right	150	80	341	691	7.1 (A)	56.3 (E)	66.9 (E)
	Overall					17.4 (B)	18.7 (B)	23 (C)
14.	S Eads Street & 13th Street S							
	Eastbound Left	350		230	231		60.3 (E)	63.4 (E)
	Eastbound Right	350		230	231		68.5 (E)	65.8 (E)
	Northbound Left	150		248	425		1.6 (A)	7.6 (A)
	Northbound Thru	300	Un-	248	425	Un-	1.9 (A)	20.7 (C)
	Southbound Thru	280	signalized	276	219	signalized	5.2 (A)	8.9 (A)
	Southbound Right	280		278	222		3 (A)	3.8 (A)
	Overall						11.4 (B)	20.4 (C)
16.	S Fern Street & 15th						11.4 (D)	20.4 (0)
10.	Street S					24.242	24.242	(5)
	Eastbound Left	130	338	299	287	21.2 (C)	24.6 (C)	35.5 (D)
	Eastbound Thru	630	338	299	287	29.7 (C)	24.5 (C)	35.5 (D)
	Eastbound Right	630	340	301	289	17.2 (B)	22.7 (C)	32.5 (C)
	Westbound Left	120	114	131	192	21.1 (C)	15 (B)	32.5 (C)
	Westbound Thru	260	114	131	192	11.8 (B)	6.5 (A)	19.5 (B)
	Westbound Right	260	116	133	195	6.2 (A)	4.2 (A)	13.3 (B)
	Northbound Left	750	266	501	773	19.8 (B)	52.6 (D)	61.4 (E)
	Northbound Thru	750	266	501	773	16.9 (B)	48 (D)	64.2 (E)
	Northbound Right	75	272	506	778	8.4 (A)	20.6 (C)	31.3 (C)
	Southbound Left	160	214	331	268	30.2 (C)	60 (E)	40.7 (D)
	Southbound Thru	300	214	331	268	16 (B)	35.1 (D)	31.8 (C)
	Southbound Right	300	229	346	274	10.8 (B)	16 (B)	15.7 (B)
	Overall					20.3 (C)	27.6 (C)	34.7 (C)
17.	15th Street S & S Elm Street							
	Eastbound Left	60		374	318		13.9 (B)	7.5 (A)
	Eastbound Thru	270		374	318		13.8 (B)	10.6 (B)
	Westbound Thru	300		162	143		4.4 (A)	1.5 (A)
	Westbound Right	300	Un- signalized	162	143	Un- signalized	5.8 (A)	2.3 (A)
	Southbound Left	250	signalized	55	55	Signalized	43.5 (D)	43.6 (D)
	Southbound Right	250		67	66		8.1 (A)	8.5 (A)
	Overall						10.8 (B)	7.4 (A)
18.	S Eads Street & 15th							
	Street S Eastbound Left	170	345	272	325	31.1 (C)	24.3 (C)	32.7 (C)
	Eastbound Thru	300	413	378	410	46.8 (D)	17.7 (B)	37.8 (D)
	Eastbound Right	300	418	378	410	8.6 (A)	17.7 (B) 18.9 (B)	42.5 (D)
	Westbound Left	300	169	339	363	38.1 (D)	53 (D)	42.5 (D) 45.7 (D)
	Westbound Thru	300	169	339	363	15.8 (B)	35.1 (D)	45.7 (D) 53.3 (D)
	Westbound Right	300	181	339	363	15.6 (B) 12.7 (B)		
	Northbound Left	130	335	929	928	, ,	42.5 (D)	62.3 (E)
	Northbound Lett Northbound Thru					24 (C)	46.8 (D)	41.4 (D)
		760 130	335	929	928	20.1 (C)	59 (E)	51.3 (D)
	Northbound Right Southbound Left		399 377	884	926 307	20.5 (C)	33.5 (C)	30.9 (C)
		250	377	388	397	89.7 (F)	77.3 (E)	90.2 (F)
	Southbound Thru	300	345	388	397	27 (C)	49.8 (D)	25.3 (C)
	Southbound Right	75	348	392	399	26.9 (C)	22.1 (C)	10.3 (B)
	Overall					34 (C)	38.3 (D)	46.9 (D)

					AM	Peak Hour		
Inters	section and Lane Group	Storage Length	Average o	f Maximum Queu			ehicular Movemer and Level of Serv	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
19.	S Eads Street & I-395 R	amps						
	(South Node)	1000	100	962	926	24 5 (C)	75 6 (E)	55 5 (E)
	Eastbound Thru		199 243	962 962		34.5 (C)	75.6 (E)	55.5 (E)
	Eastbound Right Northbound Left	1000			926	12.1 (B)	159.5 (F)	115.7 (F)
	Northbound Thru	150	4.40	 164	224			 F4.6 (D)
	Northbound Right	170 170	148 206	223	283	19.3 (B) 10.8 (B)	10.6 (B)	54.6 (D)
	Southbound Left	100	197	223	237	33.8 (C)	7.1 (A) 2.9 (A)	6.9 (A) 8.3 (A)
	Southbound Thru	100	194	208	237	9 (A)	26.6 (C)	53.6 (D)
	Overall				237	14.3 (B)	57.1 (E)	53.7 (D)
	S Eads Street & I-395 Ra					14.5 (b)	37.1 (L)	33.7 (D)
20.	(North Node)	po						
	Eastbound Left	875	1,217	472	484	120.2 (F)	49.8 (D)	50.7 (D)
	Westbound Left	1250	177	214	840	57.5 (E)	67.4 (E)	271 (F)
	Westbound Right	1250	224	214	840	23.5 (C)	59.6 (E)	36.9 (D)
	Northbound Thru	100	178	207	263	12 (B)	16.7 (B)	56.3 (E)
	Southbound Thru	100	151	137	250	37.6 (D)	17 (B)	130.4 (F)
	Southbound Right	100						
	Overall					14.3 (B)	43.1 (D)	89.1 (F)
21.	S Eads Street & 14th Street S							
	Eastbound Left	200		43	45		78.5 (E)	85.3 (F)
	Eastbound Thru	200		43	45		0 (A)	0 (A)
	Eastbound Right	200		42	45		0 (A)	0 (A)
	Westbound Left	150		96	104		56.4 (E)	74.7 (E)
	Westbound Thru	150		96	104		0 (A)	0 (A)
	Westbound Right	150		96	104		95.3 (F)	120.1 (F)
	Northbound Left	100	Future	179	382	Future	0 (A)	0 (A)
	Northbound Thru	350	Intersection	179	382	Intersection	3 (A)	14.3 (B)
	Northbound Right	350		192	390			` ,
	Southbound Left			188	334		3.1 (A) 74.2 (E)	12.6 (B)
		100					` '	74.6 (E)
	Southbound Thru	290		188	334		9.1 (A)	17.9 (B)
	Southbound Right	290		191	337		7.8 (A)	15.3 (B)
	Overall S Fern Street & Site						11.4 (B)	20.8 (C)
22.	Driveway							
	Eastbound Left	450			74			68.7 (E)
	Eastbound Thru	450			73			0 (A)
	Eastbound Right	450			73			70.2 (E)
	Westbound Left	150			74			54.5 (D)
	Westbound Thru	150			74			0 (A)
	Westbound Right	150			74			65.4 (E)
	Northbound Left	140	Future	Future	181	Future	Future	60.5 (E)
	Northbound Thru	275	Intersection	Intersection	321	Intersection	Intersection	25.6 (C)
	Northbound Right	275			321			20.4 (C)
	Southbound Left	75			346			20.4 (C) 29.1 (C)
	Southbound Thru	390			532			29.1 (C) 44.8 (D)
	Southbound Right	390 			536			34.5 (C) 35.9 (D)

					PM	Peak Hour		
Inter	rsection and Lane Group	Storage Length	Average o	of Maximum Que			ehicular Moveme and Level of Ser	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
1.	S Hayes Street &				ruture			ratare
	Army Navy Drive	260	222	240	266	40.1 (D)	66.7 (F)	66.4 (F)
	Eastbound Left Eastbound Thru	260	223	349	366	40.1 (D)	66.7 (E)	66.4 (E)
		450	460	365	560	37.1 (D)	65.7 (E)	54.1 (D)
	Eastbound Right	450	483	365	560	35.8 (D)	37.3 (D)	101.1 (F)
	Westbound Left	190	101	176	358	33.7 (C)	76.5 (E)	235.7 (F)
	Westbound Thru	430	239	288	312	32.1 (C)	66.5 (E)	47.7 (D)
	Westbound Right	430	206	169	106	1.1 (A)	1.4 (A)	2.1 (A)
	Northbound Left	200	366	329	280	234 (F)	59.2 (E)	64.1 (E)
	Northbound Thru	750	345	337	364	47.2 (D)	29.3 (C)	37.8 (D)
	Northbound Right	115	208	215	361	13.1 (B)	5.5 (A)	30.2 (C)
	Southbound Left	2050	716	2,927	1,499	37.7 (D)	149.2 (F)	212.5 (F)
	Southbound Thru	1950	716	2,927	1,499	44.4 (D)	41.3 (D)	47.5 (D)
	Southbound Right	1950	274	2,926	1,498	7.9 (A)	24.8 (C)	30.7 (C)
	Overall					36.4 (D)	44.3 (D)	59.2 (E)
2.	S Fern Street & Army Navy Drive							
	Eastbound Left	160	218	305	449	33.5 (C)	37 (D)	56.5 (E)
	Eastbound Thru	430	303	505	514	20.4 (C)	34.5 (C)	45.2 (D)
	Eastbound Right	180	96	137	268	5 (A)	9.7 (A)	24.8 (C)
	Westbound Left	80	383	408	367	18.2 (B)	88.4 (F)	99.2 (F)
	Westbound Thru	260	383	408	367	18 (B)	33.3 (C)	35.1 (D)
	Westbound Right	260	388	412	372	24.5 (C)	37.5 (D)	44 (D)
	Northbound Left	280	274	263	442	35.5 (D)	44.8 (D)	50.8 (D)
	Northbound Thru	390	140	134	220	25 (C)	28.7 (C)	17.8 (B)
	Northbound Right	80	148	134	111	10.8 (B)	31.2 (C)	19.4 (B)
	Southbound Left	75	73	166	124	47.6 (D)	41.1 (D)	36.9 (D)
	Southbound Thru	560	174	245	207	24 (C)	41.3 (D)	42 (D)
	Southbound Right	560	181	252	218	15.7 (B)	25.3 (C)	12.7 (B)
	Overall					22.6 (C)	33.7 (C)	38.7 (D)
_	Army Navy Drive &					22.0 (0)	00.7 (0)	00.7 (2)
3.	Parking Lot							
	Eastbound Left	120			381			15.1 (B)
	Eastbound Thru	260			381			10.6 (B)
	Eastbound Right	225			381			54.5 (D)
	Westbound Thru	230			346			13.5 (B)
	Westbound Right	230			363			12.8 (B)
	Northbound Left	100	Un-	Unsignalized	245	Un-	Unsignalized	85.5 (F)
	Northbound Thru	100	signalized	Orisignalized	245	signalized	Orisignanzea	0 (A)
	Northbound Right	100			245			84.6 (F)
	Southbound Left	100			130			67.2 (E)
	Southbound Thru	100			130			0 (A)
	Southbound Right	100			129			23.9 (C)
	Overall							18.4 (B)
4.	S Eads Street & Army Navy Drive							
	Eastbound Left	220	354	335	292	59.5 (E)	64.7 (E)	40.5 (D)
	Eastbound Thru	220	354	333	292	20.7 (C)	11.4 (B)	21.3 (C)
	Eastbound Right	220	382	327	292	13.8 (B)	9.3 (A)	23.6 (C)
	Westbound Thru	1100	212	199	207	32 (C)	30.5 (C)	48.9 (D)
	Westbound Right	100	212	209	217	30.4 (C)	20.7 (C)	27.4 (C)

leste		Storage	Average	f Maximum Queu		Peak Hour Average of V	ehicular Movemen	
Inter	section and Lane Group	Length (ft)			Mitigated		and Level of Serv	rice Mitigated
	Street S Eastbound Left Eastbound Thru Eastbound Right Westbound Left Westbound Thru Westbound Right Northbound Left		Existing	Background	Future	Existing	Background	Future
	Northbound Left	100	229	330	159	27.4 (C)	25.7 (C)	37.1 (D)
	Northbound Thru	240	325	330	327	31.2 (C)	24.6 (C)	29.2 (C)
	Northbound Right	240	325	330	327	31.8 (C)	20.2 (C)	27.2 (C)
	Southbound Left	140	331	204	283	24.2 (C)	22.2 (C)	32.9 (C)
	Southbound Thru	140	167	204	283	58.4 (E)	23.9 (C)	30.4 (C)
	Southbound Right	110	167	204	283	27.3 (C)	5.1 (A)	2.4 (A)
	Overall					6.1 (A)	26.7 (C)	30.8 (C)
5.								
	•				0			0.1 (A)
		1000	11-		638	1.1-		28.8 (C)
			Un- signalized	Unsignalized		Un- signalized	Unsignalized	
	•	900	Signalized		298	Signalized		9.3 (A)
	e : e : e ::							16.3 (B)
3 .								
	Eastbound Left	200			364			52.1 (D)
	Eastbound Thru	200			364			0 (A)
	Eastbound Right	200			364			72.3 (E)
	Westbound Left	300			92			33.7 (C)
	Westbound Thru	300			88			0 (A)
		300			88			54.4 (D)
	· ·	100	Un-	Unsignalized	40	Un-	Unsignalized	10.2 (B)
		250	signalized	onoignam20a	332	signalized	onorginanzoa	9.4 (A)
		250			334			7.7 (A)
	· ·	250			322			33.6 (C)
		250			322			27 (C)
		25			322			13.7 (B)
	· ·							27 (C)
7.	S Hayes Street & 12th							27 (0)
		450	281	212	236	99.5 (F)	45.8 (D)	60.8 (E)
	Eastbound Thru	450	281	212	217	97.5 (F)	41 (D)	52.1 (D)
	Eastbound Right	65	291	210	215	17.8 (B)	2.3 (A)	3 (A)
	Westbound Left	100	302	381	404	43.5 (D)	56.5 (E)	70.7 (E)
		620	302	381	404	33.6 (C)	47.2 (D)	65.7 (E)
		620	313	381	404	19.1 (B)	50.3 (D)	66.4 (E)
	ŭ	75	529	269	384	93.1 (F)	77.7 (E)	69.5 (E)
	Northbound Thru	775	529	269	384	44.1 (D)	22.9 (C)	24.7 (C)
	Northbound Right	75	533	273	388	13.8 (B)	11.7 (B)	14.9 (B)
	Southbound Left	250	606	392	460	78.9 (E)	77.4 (E)	54.5 (D)
	Southbound Thru	770	607	392	460	35.5 (D)	10.2 (B)	19.7 (B)
	Southbound Right	770	607	392	460	9.5 (A)	9.7 (A)	19.7 (B) 19.7 (B)
	Overall					43.1 (D)	26.3 (C)	30.7 (C)
3.	S Fern Street & 12th Street S					1011 (2)	2010 (0)	- Co (C)
	Eastbound Thru	640	533	571	477	46.7 (D)	49.8 (D)	42.9 (D)
	Eastbound Right	640	533	580	487	43.8 (D)	44.8 (D)	35.9 (D)
	Westbound Left	75	540	357	369	40.2 (D)	115.4 (F)	94.4 (F)
	Westbound Thru	225	261	357	369	39.2 (D)	42.9 (D)	41.4 (D)
	Westbound Right	225	261	367	369	24.6 (C)	35.9 (D)	48 (D)
	Northbound Left	100	271	373	383	19.5 (B)	26.9 (C)	42 (D)
	TOTAL DOGING ECIL		411	010	505	10.0(0)	20.0 (0)	74 (U)

		Storage			PM I	Peak Hour	/ala:auta: M	of Dolon (co)
Inters	section and Lane Group	Length	Average o	of Maximum Queu	ıe Length (ft)	Average of V	ehicular Moveme and Level of Ser	
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future
	Northbound Right	280	324	372	383	12.8 (B)	16.6 (B)	35.4 (D)
	Southbound Left	130	329	510	163	14 (B)	47.5 (D)	37 (D)
	Southbound Thru	275	383	510	438	20.1 (C)	35.5 (D)	29.8 (C)
	Southbound Right	275	383	516	437	15.7 (B)	27.8 (C)	28.4 (C)
	Overall					13.5 (B)	40.3 (D)	38.2 (D)
).	S Elm Street & 12th Street S							
	Eastbound Thru	225		212	235		8.3 (A)	8.9 (A)
	Eastbound Right	225	110	204	237	1.100	5 (A)	6.1 (A)
	Westbound Thru	325	Un- signalized	336	279	Un- signalized	28.1 (C)	13 (B)
	Northbound Right	270	org/ram20a	93	91	oignan20a	12.7 (B)	17.2 (B)
	Overall						16.7 (B)	11.1 (B)
0.	S Eads Street & 12th Street S							
	Eastbound Left	150	350	338	367	69.6 (E)	62.7 (E)	97.7 (F)
	Eastbound Thru	320	350	338	367	39.1 (D)	46.7 (D)	51.5 (D)
	Eastbound Right	320	354	338	367	31.4 (C)	52.1 (D)	50.9 (D)
	Westbound Left	200	497	494	576	55.6 (E)	85.2 (F)	205.4 (F)
	Westbound Thru	575	497	494	576	55.1 (E)	62 (E)	78.9 (E)
	Westbound Right	575	510	494	576	67.2 (E)	66 (E)	80.6 (F)
	Northbound Left	100	369	388	313	19.4 (B)	37.2 (D)	41.1 (D)
	Northbound Thru	270	369	388	313	20.5 (C)	34 (C)	29.3 (C)
	Northbound Right	100	374	389	165	6.9 (A)	10.7 (B)	16.5 (B)
	Southbound Left	120	296	334	275	25.4 (C)	57.4 (E)	53.3 (D)
	Southbound Thru	250	296	334	352	18.5 (B)	42.4 (D)	34.6 (C)
	Southbound Right	250	299	339	352	15.9 (B)	39.6 (D)	32.9 (C)
	Overall					35.2 (D)	47.2 (D)	56.4 (E)
1.	12th Street S & Army Navy Drive							
	Eastbound Thru	575		186	210		33.4 (C)	27.7 (C)
	Eastbound Right	575		197	210		20.9 (C)	25.9 (C)
	Westbound Thru	120		250	251		15.2 (B)	17.9 (B)
	Westbound Right	120		250	251		10 (A)	9.7 (A)
	Northbound Left	50	Un-	57	63	Un-	54.4 (D)	56.3 (E)
	Northbound Thru	50	signalized	57	63	signalized	0 (A)	0 (A)
	Northbound Right	50		57	63		45.6 (D)	58.4 (E)
	Southbound Left	1000		203	234		36.7 (D)	60.5 (E)
	Southbound Thru	1000		203	234		46.1 (D)	63.6 (E)
	Southbound Right	1000		203	234		36.5 (D)	66.8 (E)
	Overall S Clark Street/Long Brid	dae Dr. 9					20.1 (C)	25.3 (C)
2.	12th Street S	uge Di &						
	Eastbound Left	120	191	141	225	34.9 (C)	18.9 (B)	42.1 (D)
	Eastbound Thru	120	191	141	225	15 (B)	1.7 (A)	8.2 (A)
	Eastbound Right	120	192	141	225	5.4 (A)	2.6 (A)	2.2 (A)
	Westbound Left	100	43	493	354	28 (C)	65.2 (E)	50.3 (D)
	Westbound Thru	1500	509	1,429	1,344	25.7 (C)	89.7 (F)	71.2 (E)
	Westbound Right	1500	513	1,440	1,354	23.7 (C)	96.2 (F)	80 (E)
	Northbound Left	100	263	378	397	35.8 (D)	92.8 (F)	100.2 (F)
	Northbound Thru	1200	116	378	397	16.2 (B)	59.1 (E)	64.5 (E)
	Northbound Right	1200	118	383	402	9.4 (A)	47.1 (D)	50.6 (D)
	Southbound Left	450	177	949	1,146	21.2 (C)	85.2 (F)	167.6 (F)

Intersection and Lane Group		Storage	PM Peak Hour Average of Maximum Queue Length (ft) Average of Vehicular Movement Delay (sec/ve										
Inter	section and Lane Group	Length (ft)			Mitigated		and Level of Serv	/ice Mitigated					
			Existing	Background	Future	Existing	Background	Future					
	Southbound Thru	450	177	949	1,146	17.1 (B)	77.7 (E)	162.6 (F)					
	Southbound Right	150	169	965	1,149	11.1 (B)	99.9 (F)	111.1 (F)					
	Overall					24.6 (C)	68.1 (E)	72.4 (E)					
14.	S Eads Street & 13th Street S												
	Eastbound Left	350		453	336		79.2 (E)	67.5 (E)					
	Eastbound Right	350		453	336		74.7 (E)	53.3 (D)					
	Northbound Left	150		429	423		7.7 (A)	6.7 (A)					
	Northbound Thru	300	Un-	429	423	Un-	26.3 (C)	33.1 (C)					
	Southbound Thru	280	signalized	315	349	signalized	14.5 (B)	20.5 (C)					
	Southbound Right	280		318	352		6.2 (A)	10 (A)					
	Overall						31.9 (C)	31.6 (C)					
16.	S Fern Street & 15th						, ,	. , ,					
10.	Street S												
	Eastbound Left	130	121	147	159	23.2 (C)	26 (C)	32 (C)					
	Eastbound Thru	630	121	147	159	12.8 (B)	12.9 (B)	22.9 (C)					
	Eastbound Right	630	121	149	161	9.4 (A)	9.8 (A)	15.5 (B)					
	Westbound Left	120	297	361	167	16.5 (B)	54.6 (D)	7.3 (A)					
	Westbound Thru	260	297	361	167	9.9 (A)	41.2 (D)	4.4 (A)					
	Westbound Right	260	300	364	171	10.1 (B)	35.1 (D)	4.5 (A)					
	Northbound Left	750	203	270	376	25.7 (C)	25.9 (C)	53.9 (D)					
	Northbound Thru	750	203	270	376	18.5 (B)	19.7 (B)	53.8 (D)					
	Northbound Right	75	209	275	381	8.9 (A)	6.1 (A)	19.3 (B)					
	Southbound Left	160	365	346	414	21.9 (C)	21.2 (C)	41 (D)					
	Southbound Thru	300	365	346	414	15.3 (B)	16 (B)	32.5 (C)					
	Southbound Right	300	379	360	420	11.7 (B)	13.5 (B)	27 (C)					
	Overall					16.8 (B)	26 (C)	23.6 (C)					
17.	15th Street S & S Elm Street												
	Eastbound Left	60		173	147		2.7 (A)	12.1 (B)					
	Eastbound Thru	270		173	147		4.1 (A)	7.4 (A)					
	Westbound Thru	300		122	236		3.8 (A)	3.4 (A)					
	Westbound Right	300	Un-	125	239	Un-	2.6 (A)	4.7 (A)					
	Southbound Left	250	signalized	146	138	signalized	57.2 (E)	45.8 (D)					
	Southbound Right	250		149	141		12.4 (B)	8.9 (A)					
	Overall						8 (A)	7.9 (A)					
18.	S Eads Street & 15th						. ,	,					
	Street S	170		2.5		(0.7 (7))	(D)	.= . (5)					
	Eastbound Left	170	162	215	112	46.5 (D)	50.2 (D)	17.4 (B)					
	Eastbound Thru	300	244	289	341	20.5 (C)	19.6 (B)	24.2 (C)					
	Eastbound Right	300	227	289	341	9.1 (A)	24.5 (C)	30.9 (C)					
	Westbound Left	300	395	364	313	43.8 (D)	27.3 (C)	24.5 (C)					
	Westbound Thru	300	395	364	313	20.8 (C)	20.4 (C)	32.4 (C)					
	Westbound Right	300	408	364	313	19.1 (B)	37.6 (D)	39.3 (D)					
	Northbound Left	130	193	914	845	21.6 (C)	84.8 (F)	68.6 (E)					
	Northbound Thru	760 130	193	914	845	13.1 (B)	87.5 (F)	83.7 (F)					
	Northbound Right	130	62	508	83	5.7 (A)	42.7 (D)	35.5 (D)					
	Southbound Left	250	212	462	472	22.9 (C)	68.7 (E)	65.4 (E)					
	Southbound Thru	300	278	462	472	17.7 (B)	63.5 (E)	55.4 (E)					
	Southbound Right	75	282	462	475	17.8 (B)	41.4 (D)	35.2 (D)					
	Overall					24 (C)	44.5 (D)	43.8 (D)					

			PM Peak Hour									
Inter	section and Lane Group	Storage Length	Average o	f Maximum Queu		Average of Vehicular Movement Delay (sec/veh) and Level of Service						
		(ft)	Existing	Background	Mitigated Future	Existing	Background	Mitigated Future				
19.	S Eads Street & I-395 R	amps			T ditail 0			r drui o				
	(South Node) Eastbound Thru	1000										
	Eastbound Right	1000										
	Northbound Left	150	335	309	325	30.6 (C)	27.6 (C)	5.7 (A)				
	Northbound Thru	170	335	309	325	16.4 (B)	6.1 (A)	6 (A)				
	Northbound Right	170	393	353	325	10.4 (B) 12.8 (B)	7.2 (A)	3.8 (A)				
	Southbound Left	100	160	216	177	14.1 (B)	3.2 (A)	10.6 (B)				
	Southbound Thru	100	157	213	174	5.5 (A)	3.8 (A)	4.3 (A)				
	Overall					14.7 (B)	8.6 (A)	5.4 (A)				
	S Eads Street & I-395 R	amps				14.7 (D)	0.0 (71)	0.4 (71)				
20.	(North Node)	•										
	Eastbound Left	875										
	Westbound Left	1250	270	212	384	24.1 (C)	33.4 (C)	63 (E)				
	Westbound Right	1250	339	212	384	26.3 (C)	26.1 (C)	53.4 (D)				
	Northbound Thru	100	179	174	198	8.6 (A)	5.7 (A)	6.8 (A)				
	Southbound Thru	100	217	161	180	13.8 (B)	4.9 (A)	8.1 (A)				
	Southbound Right	100	139	158	176	0.7 (A)	0.3 (A)	0.4 (A)				
	Overall S Eads Street & 14th					7.7 (A)	6.7 (A)	12.6 (B)				
21.	Street S											
	Eastbound Left	200		128	133		73.1 (E)	79.7 (E)				
	Eastbound Thru	200		128	133		0 (A)	0 (A)				
	Eastbound Right	200		127	133		74.7 (E)	91.1 (F)				
	Westbound Left	150		121	165		57.5 (E)	205.9 (F)				
	Westbound Thru	150		125	169		0 (A)	0 (A)				
	Westbound Right	150		121	165		114.1 (F)	158 (F)				
	Northbound Left	100	Future	438	401	Future	0 (A)	0 (A)				
	Northbound Thru	350	Intersection	438	401	Intersection	24.1 (C)	10.5 (B)				
	Northbound Right	350		452	411		21.7 (C)	8.3 (A)				
	Southbound Left	100		379	367		91.6 (F)	91.3 (F)				
	Southbound Thru	290		379	367		30.7 (C)	23.9 (C)				
	Southbound Right	290		382	371		28 (C)	24.2 (C)				
	Overall						32.6 (C)	29.5 (C)				
	S Fern Street & Site						02.0 (0)	25.5 (0)				
22.	Driveway											
	Eastbound Left	450			312			294.1 (F)				
	Eastbound Thru	450			312			0 (A)				
	Eastbound Right	450			312			295 (F)				
	Westbound Left	150			264			56.3 (E)				
	Westbound Thru	150			264			0 (A)				
	Westbound Right	150		- .	264		- .	71.9 (E)				
	Northbound Left	140	Future Intersection	Future Intersection	7	Future Intersection	Future Intersection	27.7 (C)				
	Northbound Thru	275	"" " " " " " " " " " " " " " " " " " "	THO GOOD IN	305	microcolori	morocolon	22 (C)				
	Northbound Right	275			307			20 (B)				
	Southbound Left	75			68			43.8 (D)				
	Southbound Thru	390			416			44.8 (D)				
	Southbound Right	390			419			25.9 (C)				
	Overall							62.8 (E)				

able 29: Bicycle and			Pedestria	ın Delay (s	sec/ped)		Averag	ge Bicycle	Delay (se	c/bike)		
Intersection/ Approach	Existin	ıg (2020)	Backo	ground) (25)	Mitigate	d Future (25)	Existin	g (2020)	Backo	ground (25)		jated (2025)
Арргоасп	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Pea
. Army Navy Drive	reak	reak	reak	reak	reak	reak	reak	reak	reak	reak	reak	rea
and S Hayes Street												
Overall			70.3	65.8	76.4	62.8			71.3	51.4	50.7	49.
Eastbound	46.5	49.9	70.9	65.7	76.7	63.0			86.8	43.7	52.4	54.
Westbound	0.0	0.2	57.9	67.7	62.6	54.6			61.6	63.2	48.8	44.
Northbound												
Southbound												
2. Army Navy Drive												
and S Fern Street												
Overall			65.5	62.9	65.9	65.0			16.3	6.3	14.7	18.
Eastbound	49.4	46.9	67.6	66.0	67.2	65.6			2.3	4.0	25.6	35.
Westbound	49.6	47.2	66.5	61.3	64.1	64.8			24.1	9.3	4.7	10.
Northbound	51.3	50.7	65.7	61.3	64.5	64.2					14.5	6.4
Southbound	50.0	49.5	64.6	62.9	66.6	64.9						
3. Army Navy Drive	00.0		0	02.0	00.0	0						
and Parking Lot												
Overall					61.2	61.4					1.9	5.8
Eastbound					66.3	63.4					4.3	8.6
Westbound					32.1	50.0					0.8	0.4
Northbound												
Southbound												
4. Army Navy Drive												
and S Eads Street												
Overall			70.1	70.0	66.1	66.8			19.1	10.6	24.5	21.
Eastbound	52.4	51.1	90.3	75.4	67.9	65.9			29.5	2.3	10.7	16.3
Westbound	50.4	50.9	69.5	63.8	67.3	65.9			1.0	3.3	29.8	47.0
Northbound	49.6	51.8	64.1	72.9	65.8	68.9			22.9	27.1	27.5	12.
Southbound	50.7	49.4	62.1	73.4	63.9	68.2						
5. Army Navy Drive	00.7	70.7	02.1	70.4								
and 110 Ramp					Un	signalized	Intersection	on				
6. S Eads Street and												
11th Street S/Site												
Driveway												
Overall					65.9	63.7					5.3	7.8
Eastbound					65.1	65.3						
Westbound					63.6	63.2						
Northbound					66.1	64.6					0.5	3.4
Southbound					67.6	62.3					9.5	12.3
7. 12th Street S and												
S Hayes Street												
Overall			63.5	64.0	64.2	65.3						
Eastbound	51.6	49.7	64.6	64.6	64.3	64.7						
Westbound	49.7	50.7	63.8	60.8	64.9	66.0						
Northbound	50.6	48.5	53.8	62.9	64.8	66.0						
Southbound	0.0	0.0	0.0	0.0	62.7	66.3						
8. 12th Street S and S Fern Street												
Overall			64.4	64.7	64.5	64.3						
Eastbound	35.0	34.4	63.9	64.6	64.2	64.4						
Westbound	34.9	34.5	65.3	65.1	64.5	64.1						

		Average	e Pedestria	ın Delay (s	sec/ped)	Average Bicycle Delay (sec/bike)						
Intersection/	Fyistir	visting (2020) Background		Mitigate	d Future	Fyistin	g (2020)	Backo	ground	Mitigated		
Approach		,		25)		25)				025)	Future	
	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak
Northbound	34.6	34.3	65.8	65.4	64.2	64.2						
Southbound	34.9	34.2	64.1	64.4	65.0	64.5						
9. 12th Street S and S Elm Street												
Overall			24.6	65.2	36.0	64.7						
Eastbound			3.3	65.2	3.5	65.0						
Westbound												
Northbound			65.0	65.5	64.6	64.4						
10. 12th Street S and S Eads Street												
Overall			64.5	65.4	64.9	65.5			6.9	24.4	17.5	27.5
Eastbound	50.0	34.9	65.0	66.6	64.7	65.7						
Westbound	48.3	36.0	64.7	65.2	65.4	66.2						
Northbound	51.0	34.9	63.4	64.0	64.0	64.4			8.4	34.3	17.5	40.8
Southbound	25.3	34.7	63.4	64.2	66.1	65.7			5.2	19.7	17.5	22.3
11. 12th Street S and Army Navy Drive												
Overall			63.3	63.9	65.7	64.3			42.2	49.8	34.3	51.0
Eastbound			63.9	65.6	65.3	65.4			37.2	48.0	27.5	50.2
Westbound			62.8	63.6	65.8	64.0			46.7	51.1	37.1	52.4
Northbound			0.0	0.1	0.0	0.0						
Southbound			0.0	65.2	0.0	55.2						
12. 12th Street and Long Bridge Drive/S Clark Street												
Overall			65.7	64.0	63.9	64.7			44.3	40.6	43.8	42.0
Eastbound	34.8	34.3	64.5	63.7	64.2	64.9						
Westbound	34.3	34.8	65.7	64.4	64.1	64.4						
Northbound	35.5	34.7	68.4	61.8	62.8	64.4			31.2	23.5	32.2	28.8
Southbound	31.7	35.7	63.3	68.1	64.5	66.7			61.9	54.5	57.1	54.3
13. S Fern Street and 13th Street S					Un	signalized	Intersectio	on				
14. 13th Street S and S Eads Street												
Overall			60.5	30.6	61.1	59.3			0.7	1.9	0.5	1.7
Eastbound			69.4	38.1	67.4	66.0						
Northbound									0.1	0.1	0.1	0.1
Southbound 15. S Fern Street			50.9	26.7	58.9	57.5			1.4	3.5	1.3	2.5
and 14th Street S					Un	signalized	Intersection	on	T		T	
16. 15th Street S and S Fern Street												
Overall			67.1	64.6	66.7	65.1						
Eastbound	34.8	35.2	68.8	63.3	66.0	64.5						
Westbound	38.0	34.5	64.1	64.5	66.1	65.4						
Northbound	36.8	34.8	67.7	65.7	67.3	65.1						
Southbound	35.2	34.6	66.1	64.1	67.2	65.2						
17. 15th Street S and S Elm Street												
Overall			62.6	51.3	65.1	63.7			Ì			

		Average	Pedestria	ın Delay (s	sec/ped)	Average Bicycle Delay (sec/bike)						
Intersection/	Existin	g (2020)	Backo	ground)25)	Mitigate	d Future 25)	Existing (2020)		Background (2025)		Mitigated Future (2025)	
Approach	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM	AM	PM
	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak	Peak
Eastbound												
Westbound			63.0	44.9	65.5	63.6						
Southbound			61.4	75.4	61.4	65.2						
18. 15th Street S												
and S Eads Street			400.0	40=0	40= 0	40= 4			40.0	0.4 -		
Overall			128.0	127.3	127.8	127.1			43.6	34.5	23.9	39.3
Eastbound	33.6	35.2	64.6	64.9	64.6	64.5						
Westbound	32.7	35.8	64.9	64.0	64.7	64.9						
Northbound	39.1	34.8	187.7	185.4	186.9	185.8			37.5	43.5	27.7	36.0
Southbound	35.3	34.4	190.3	186.9	189.4	187.5			47.3	23.0	18.5	42.3
19. S Eads Street and I-395 HOT												
Lanes (South Node)												
Overall												
Eastbound												
Northbound												
Southbound												
20. S Eads Street and I-395 HOT Lanes (North Node)												
Overall												
Eastbound												
Westbound												
Northbound												
Southbound												
21. 14th Street S												
and S Eads Street												
Overall			58.2	65.7	58.8	65.9			2.0	2.1	4.3	13.0
Eastbound												
Westbound			65.3	66.0	66.4	65.7						
Northbound			52.0	65.4	51.8	66.1			8.0	1.9	0.5	9.3
Southbound			60.6	65.4	66.4	65.2			3.4	2.4	12.0	15.9
22. S Fern Street and 11th Street												
S/Site Driveway												
Overall					64.8	65.2					16.3	13.6
Eastbound					66.6	64.8						
Westbound					65.7	64.4						
Northbound					62.7	66.8					13.4	16.6
Southbound					63.6	64.2					18.2	10.6
Southbould					03.0	04.2					10.2	10.0

Transportation Management Plan

A Transportation Management Plan (TMP) has many components that are tailored to accommodate a given facility with the goal being the reduction of automobile trips by encouraging alternative forms of transportation. A few of the typical TMP components include the establishment of a TMP coordinator, the distribution of transit literature, the establishment of ride-sharing programs, and the on-site sale of discounted fare media. Management measures taken by the proposed PenPlace development can be monitored and adjusted as needed to continually create opportunities to reduce the amount of vehicular traffic generated by the site.

The TMP will include a schedule and details of implementation and continued operation of the elements in the plan. The location of the site near the Pentagon City Metro Station, Pentagon Metro Station, and Crystal City Metro Station allows for a TMP that may include, but not be limited to, the following:

Participation and Funding

- Establish and maintain an active, ongoing relationship with Arlington Transportation Partners (ATP), or successor entity, at no cost to the developer, on behalf of the property owner, as directed by applicable adopted Site Plan Conditions.
- 2. Designate and keep current a member of building management as Property Transportation Coordinator (PTC) to be primary point of contact with the County and undertake the responsibility for coordinating and completing all Transportation Management Plan (TMP) obligations, as directed by applicable adopted Site Plan Conditions. The PTC shall be trained, to the satisfaction of ACCS, to provide transit, bicycle, walk, rideshare and other information provided by Arlington County intended to assist with transportation to and from the site.
- 3. Contribute annually to ACCS, or successor, to sustain direct and indirect on-site and off-site services in support of TMP activities. Payment on this commitment shall begin as a condition of issuance of the First Partial Certificate of Occupancy for Tenant Occupancy for each respective building or phase of construction, or as directed by applicable adopted Site Plan Conditions. Subsequent payments shall be made annually.

Facilities and Improvements

 Provide transportation information such as nearby transit routes, stop locations, transit schedules, on-site bike amenities, off-site bike facilities and connections, carpool

- options, and other services. The format and mechanism to distribute information may change over time, and could include displays, electronic kiosks, on-site staff, or alternative electronic formats such as intranet and/or smart phones. The information provided and distribution mechanism shall be approved by ACCS. The developer agrees that the required transportation information displays shall meet the Arlington County Neighborhood Transportation Information Display Standards in effect on the date of the site plan approval, or equivalent as approved by the County Manager.
- Comply with requirements of the Site Plan Conditions to provide bicycle parking/storage facilities, a Parking Management Plan (PMP), a Bicycle Facilities Management Plan, and construction worker parking.

Carpool and Vanpool Parking

- Operate a carpool/vanpool program with elements including:
 - Reserved, signed spaces for carpools/vanpools located near main entrances/elevators
 - Parking subsidy for two-person or more carpools
 - Free parking for vanpools (recognized by Internal Revenue Service)

Promotions, Services, Policies

- Prepare, reproduce and distribute, in digital or hard copy, materials provided by Arlington County, which includes site-specific transit, bicycle, walk, and rideshare related information, to each new office, retail, property management, or maintenance employee, from initial occupancy through the life of the site plan. These materials shall be distributed as a part of prospective tenant marketing materials, as well as communications associated with lease signing, on-boarding, or similar activities.
- 2. Provide one time, per person, to each new office, retail, property management, or maintenance employee, whether employed part-time or full-time, directly employed or contracted, who begins employment in the building throughout initial occupancy, the choice of one of the following:
 - Metro fare on a SmarTrip card or successor fare medium (amount to be determined)
 - A one-year bikeshare membership

- A one-year carshare membership
- Implement a guaranteed ride home program for employees who are part of a registered carpool, a registered vanpool, or take transit to work and need to return home in an emergency.
- 4. The County Manager may approve additions to, or substitution of one or more of these choices with a comparable transportation program incentive, as technology and service options change, if he/she finds that an incentive shall be designed to provide the individual with an option other than driving alone in a personal vehicle, either by removing a barrier to program entry, such as a membership cost, or by providing a similar level of subsidized access to a public or shared transportation system, program or service.
- 5. Provide, administer, or cause the provision of a sustainable commute benefit program for each employee, whether employed part-time or full-time, directly employed or contracted. This commute benefit program shall offer, at a minimum, a monthly pre-tax transit benefit or a monthly subsidized/direct transit benefit.
- 6. Provide, under a "transportation information" heading on the Developer and property manager's websites regarding this development:
 - Links to the most appropriate Arlington County Commuter Services and/or external transportationrelated web page(s). Confirmation of most appropriate link will be obtained from ACCS.
 - A description of key transportation benefits and services provided at the building, pursuant to the TMP.

Performance and Monitoring

- During the first year of start-up of the TMP and on an annual basis thereafter, the Developer shall submit an annual report, which may be of an online, or e-mail variety, to the County Manager, describing completely and correctly, the TDM related activities of the site and changes in commercial tenants during each year.
- 2. The Developer agrees to conduct and/or participate in, a transportation and parking performance monitoring study at two years, five years, and each subsequent five years (at the County's option), after issuance of the First Certificate of Occupancy for Tenant Occupancy. The County may conduct the study or ask the owner to conduct the study (in the latter case, no reimbursement payment shall be required). As part of the study, a report

shall be produced as specified below by the County. The study may include building occupancy rates, average vehicle occupancy, average garage occupancy for various days of the week and times of day, parking availability by time of day, average duration of stay for short term parkers on various days of the week and times of day, pedestrian traffic, a seven-day count of site-generated vehicle traffic, a voluntary mode-split survey, and hourly, monthly, and special event parking rates.

The building owner and/or operator shall notify, assist, and encourage building occupants and visitors on site to participate in mode-split surveys which may be of an on-line or email variety.

Summary and Conclusions

This report concludes that the proposed development will have a manageable impact on the surrounding transportation and roadway assuming that all planned site design elements and recommended mitigation measures are implemented.

The PenPlace site is well served by transit and is surrounded by a well-connected pedestrian and bicycle network. The site is located near several principal arterials such as Route 1, VA-27 (Washington Boulevard), VA-244 (Columbia Pike), and VA-110. The arterials create connections to I-395, I-66, George Washington Memorial Parkway, and ultimately the Capital Beltway (I-495) and I-95.

The proposed development will consist of four (4) buildings with approximately 2.8 million square feet of office space, 388,000 square feet of amenity space, 14,500 square feet of daycare, 82,600 square feet of neighborhood-serving ground floor retail space, and 27,000 square feet of community space. The proposed development will provide 1,984 parking spaces in a below-grade parking garage shared between the four (4) buildings.

The proposed development will provide seven (7) large loading berths and six (6) van parking stalls, for a total of 13 loading spaces, in shared loading area. The number of loading facilities on-site will accommodate the practical needs of the site. Vehicular parking will be provided via Army Navy Drive, S Fern Street and S Eads Street for the four (4) buildings. Loading access will be provided via Army Navy Drive for the four (4) buildings. While the loading dock and ramp have been designed to accommodate a WB-67, trucks of this size will be very infrequent. The arrival of a WB-67 would be scheduled and permitted during off-peak only.

A number of significant infrastructure improvements are being proposed as part of this development:

- Improving pedestrian facilities along the perimeter of the site to meet or exceed Arlington County and ADA standards;
- The signalization of two (2) existing intersections and the addition of one (1) new signalized intersection within the vicinity of the proposed development, providing access to the on-site loading facilities and below-grade garage, allowing streets to function as a complete network rather than a series of major corridors for commuter traffic, and providing signalized pedestrian crossings where none currently exist;

- The reconfiguration of S Eads Street adjacent to the site, to include southbound protected bicycle lanes and on-street parking; and
- 4. The reconfiguration of S Fern Street adjacent to the site, to include northbound protected bicycle lanes between Army Navy Drive and 12th Street S and southbound protected bicycle lanes between Army Navy Drive and 11th Street S/Site Driveway, new striped medians, and on-street parking.
- 5. The reconfiguration of the Army Navy Drive and S Eads Street intersection to add a northbound thru lane.
- 6. The reconfiguration of the 12th Street S and S Eads Street intersection to add a dedicated southbound left-turn lane.
- 7. The reconfiguration of the 12th Street S and S Fern Street intersection to add a dedicated southbound left-turn lane.

A number of planned transportation improvements in the vicinity of the PenPlace development are expected to be complete by 2031. The full list of improvements is detailed in the report, but examples include (detailed in Table 1 and Figure 1):

- Army Navy Drive Complete Street
- 12th Street S Complete Street
- 15th Street S/S Clark-Bell Street Realignment
- Crystal City Transitway Extension
- Route 1 Multimodal Improvements Study

A capacity analysis was developed, using the VISSIM microsimulation modelling tool, to compare the future roadway network with and without the proposed development. Compared to typical macroscopic analysis tools, such as Synchro, VISSIM is a microsimulation modelling tool that measures the performance of individual vehicles as they travel through the network while accounting for the influence that other vehicles, transit, pedestrians, and cyclists. Given the multimodal nature of Pentagon City and planned improvements, particularly streets directly adjacent to the site where a cycle track, protected bicycle lanes, and a dedicated transit lanes will be in place, VISSIM was determined to be the appropriate analysis tool for this development as agreed upon during the scoping process.

Traffic projections for 2025 and 2031 are based on existing volumes, plus traffic generated by approved nearby background developments, regional growth on the roadway, and traffic generated by the proposed PenPlace development.

As described in the Geometry and Operations section of this report, the proposed development will include several improvements to adjacent roadways, including the signalization

of three (3) intersections and the addition of protected bike facilities. In addition to the improvements outlined above, mitigation measures recommended based on the MOEs outlined in the approved scoping document.

Based on the results of the VISSIM analysis, potential mitigation measures were explored at study area intersections and included the following recommendations for both 2025 and 2031 Mitigated Future Conditions:

- Adjustments to signal timings at nine (9) intersections
- Modifications to signal phasing and adjustments to signal timings at seven (7) intersections
- Signal modifications at seven (7) intersections
- Re-striping at eight (8) intersections
- Relocating one (1) existing bus stop along S Eads Street
- Adding new signals at three (3) intersections, including Army Navy Drive/Parking Lot/Site Driveway, S Eads Street/11th Street S/Site Driveway, and S Fern Street/Site Driveway
- Providing a protected southbound bike lane along S Eads
 Street between Army Navy Drive and 12th Street S, a
 northbound protected bike lane along S Fern Street between
 Army Navy Drive and 12th Street S, and a southbound bike
 lane along S Fern Street between Army Navy Drive and 11th
 Street S/Site Driveway

With the recommended mitigations in place, the VISSIM analysis shows, at the majority of intersections in the network, the vehicular delay results under the 2025 and 2031 Mitigated Future scenarios, with added site traffic and recommended mitigation measures, are comparable to that under the 2025 and 2031 Background scenarios. Nevertheless, as can be expected of urban infill there are still certain locations that are projected to experience delay and queuing issues where traffic is concentrated, especially along Army Navy Drive and S Eads Street, which funnel traffic to/from I-395, where congestion exists today. A comparison of the level of service (LOS) between scenarios is provided in Figure 73 and Figure 74 for 2025 and Figure 75 and Figure 76 for 2031.

It is important to note that VISSIM is a microscopic analysis rather than a macroscopic analysis. Mitigation measures are recommended such that the results are comparable or better than the Background conditions throughout the network. The recommended mitigation measures are in place to address targeted issues at specific, as well as increase the vehicular throughput of the overall network, particularly at exterior

intersections that are responsible for metering vehicles entering the network. Due to the increased number of vehicles being processed in the network compared to Background conditions, there may be locations where delays are higher than that seen under Background conditions.

Most vehicular capacity concerns in the study area can be alleviated through signal timing changes that adapt to changes in volume patterns, but at some locations, operational changes alone cannot mitigate future delays. As part of the proposed PenPlace project, a Transportation Management Plan (TMP) will be provided based on the County's requirements, and a framework for a TMP is included in this report, to further reduce vehicular trips generated by the proposed development during peak period travel times.

The development has many positive elements contained within its design that minimize potential transportation impacts, including:

- The proposed development's close proximity to the Pentagon City Metro Station, Pentagon Metro Station, Crystal City Metro and VRE Stations, and multiple bus lines.
- Improvements to the pedestrian facilities adjacent to the site that meet or exceed Arlington County and ADA requirements.
- Limited on-site parking, which will promote the use of nonauto modes of travel to and from the proposed development.
- The installation of new signals on Army Navy Drive, S Fern Street, and S Eads Street which provide additional signalized pedestrian crossing points, significantly improving pedestrian infrastructure near the site.
- The inclusion of publicly accessible plazas, parks, a northsouth forest walk, and an east-west multimodal path that improve pedestrian circulation and break-up a superblock.
- The provision of protected southbound bike lanes along the
 western side of S Eads Street between Army Navy Drive
 and 12th Street S, northbound protected bike lanes on S
 Fern Street S between Army Navy Drive and 12th Street S,
 and southbound protected bike lanes on S Fern Street
 between Army Navy Drive and 11th Street S/Site Driveway.
- The inclusion of secure-long-term bicycle parking significantly exceeding zoning requirements.
- The installation of short-term bicycle parking spaces within and around the perimeter of the site that meet zoning requirements.

- The inclusion of shower and locker facilities within each building that meet or exceed zoning requirements.
- A Transportation Management Plan (TMP) that aims to reduce the demand of single-occupancy, private vehicles to/from the proposed development during peak period travel times or shifts single-occupancy vehicular demand to offpeak periods.

As mentioned, this report concludes that the proposed development will have a manageable impact on the surrounding transportation and roadway network assuming that all planned site design elements and recommended mitigation measures are implemented.